

**FORM  
5A**  
Rev  
06/12

**State of Colorado**  
**Oil and Gas Conservation Commission**  
1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:  
400323343

Date Received:

**COMPLETED INTERVAL REPORT**

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: <u>100322</u>	4. Contact Name: <u>Sarah Finnegan</u>
2. Name of Operator: <u>NOBLE ENERGY INC</u>	Phone: <u>(720) 587-2265</u>
3. Address: <u>1625 BROADWAY STE 2200</u>	Fax: <u>(303) 228-4286</u>
City: <u>DENVER</u> State: <u>CO</u> Zip: <u>80202</u>	

5. API Number <u>05-123-35254-00</u>	6. County: <u>WELD</u>
7. Well Name: <u>DECHANT STATE</u>	Well Number: <u>H36-33D</u>
8. Location: QtrQtr: <u>NESW</u> Section: <u>36</u> Township: <u>3N</u> Range: <u>65W</u> Meridian: <u>6</u>	
9. Field Name: <u>WATTENBERG</u> Field Code: <u>90750</u>	

**Completed Interval**

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 06/16/2012 End Date: 06/16/2012 Date of First Production this formation: 06/20/2012

Perforations Top: 7305 Bottom: 7317 No. Holes: 48 Hole size: 0.42

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

Pumped 249,686 lbs of Ottawa Proppant and 115,332 gallons of 15% HCL, Slick Water, and Vistar.  
 The Codell is producing through a composite flow through plug.  
 Commingle the Niobrara and Codell.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 2746 Max pressure during treatment (psi): 4657

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): 0.93

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: 7

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: RECYCLE

Total proppant used (lbs): 249686 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: J-NIOBRARA-CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 06/06/2012 End Date: 06/16/2012 Date of First Production this formation: 06/20/2012  
Perforations Top: 7064 Bottom: 7782 No. Holes: 144 Hole size: \_\_\_\_\_

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on [FracFocus.org](http://FracFocus.org)**

**Test Information:**

Date: 06/25/2012 Hours: 24 Bbl oil: 10 Mcf Gas: 25 Bbl H2O: 1

Calculated 24 hour rate: Bbl oil: 10 Mcf Gas: 25 Bbl H2O: 1 GOR: 2604

Test Method: Flowing Casing PSI: 250 Tubing PSI: 0 Choke Size: 14/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1281 API Gravity Oil: 48

Tubing Size: 2 + 3/8 Tubing Setting Depth: 7734 Tbg setting date: 08/14/2012 Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: J SAND Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 06/06/2012 End Date: 06/16/2012 Date of First Production this formation: 06/20/2012  
Perforations Top: 7752 Bottom: 7782 No. Holes: 48 Hole size: 0.4

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

Pumped 256,182 lbs of Ottawa Proppant, 14,848 lbs of LC Super Proppant and 152,838 gallons of Slick Water and Vistar.  
The J-Sand is producing through a composite flow through plug.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3639 Max pressure during treatment (psi): 3588

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): 0.59

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: 10

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: RECYCLE

Total proppant used (lbs): 271030 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 06/16/2012 End Date: 06/16/2012 Date of First Production this formation: 06/20/2012

Perforations Top: 7064 Bottom: 7317 No. Holes: 96 Hole size: \_\_\_\_\_

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production:

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 06/16/2012 End Date: 06/16/2012 Date of First Production this formation: 06/20/2012  
Perforations Top: 7064 Bottom: 7172 No. Holes: 48 Hole size: 0.73

Provide a brief summary of the formation treatment: Open Hole:

Pumped 245,046 lbs of Ottawa Proppant and 152,040 gallons of Slick Water and Vistar.  
Commingle the Niobrara and Codell.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3620 Max pressure during treatment (psi): 4639

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: Max frac gradient (psi/ft): 0.94

Total acid used in treatment (bbl): Number of staged intervals: 7

Recycled water used in treatment (bbl): Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE

Total proppant used (lbs): 245046 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized:

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O:

Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:

Test Method: Casing PSI: Tubing PSI: Choke Size:

Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze:  Yes  No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Sarah Finnegan  
Title: Regulatory Analyst Date: Email: sfinnegan@nobleenergyinc.com

**Attachment Check List**

Att Doc Num	Name

Total Attach: 0 Files

**General Comments**

User Group	Comment	Comment Date

Total: 0 comment(s)