

FORM  
5A  
Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:  
400304599

Date Received:  
07/11/2012

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: <u>100322</u>	4. Contact Name: <u>Tania McNutt</u>
2. Name of Operator: <u>NOBLE ENERGY INC</u>	Phone: <u>(303) 228-4392</u>
3. Address: <u>1625 BROADWAY STE 2200</u>	Fax: <u>(303) 228-4286</u>
City: <u>DENVER</u> State: <u>CO</u> Zip: <u>80202</u>	

5. API Number <u>05-123-34740-00</u>	6. County: <u>WELD</u>
7. Well Name: <u>Strohauer PC</u>	Well Number: <u>G04-30D</u>
8. Location: QtrQtr: <u>NENE</u> Section: <u>5</u> Township: <u>4N</u> Range: <u>65W</u> Meridian: <u>6</u>	
9. Field Name: <u>WATTENBERG</u> Field Code: <u>90750</u>	

Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 02/29/2012 End Date: 02/29/2012 Date of First Production this formation: 03/07/2012  
Perforations Top: 7156 Bottom: 7171 No. Holes: 60 Hole size: 0.4

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

Pumped 218,016 lbs of Ottawa Proppant and 116,719 gallons of 15% HCL, Slick Water and Silverstim.  
The Codell is producing through a composite flow through plug  
Commingling the Niobrara and Codell

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3007 Max pressure during treatment (psi): 3915  
Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): 8.34  
Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): 0.76  
Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: 1  
Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_  
Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: RECYCLE  
Total proppant used (lbs): 218016 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: \_\_\_\_\_

Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date of First Production this formation: \_\_\_\_\_

Perforations Top: 6848 Bottom: 7171 No. Holes: 108 Hole size: \_\_\_\_\_

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: 03/14/2012 Hours: 24 Bbl oil: 65 Mcf Gas: 851 Bbl H2O: 38

Calculated 24 hour rate: Bbl oil: 65 Mcf Gas: 851 Bbl H2O: 38 GOR: 13092

Test Method: FLOWING Casing PSI: 1135 Tubing PSI: \_\_\_\_\_ Choke Size: 14/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1262 API Gravity Oil: 62

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 02/29/2012 End Date: 02/29/2012 Date of First Production this formation: 03/07/2012  
Perforations Top: 6848 Bottom: 6986 No. Holes: 48 Hole size: 0.72

Provide a brief summary of the formation treatment: Open Hole:

Pumped 233,769 lbs of Ottawa Proppant and 153,843 gallons of Slick Water and Silverstim.  
Commingling the Niobrara and Codell

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3896 Max pressure during treatment (psi): 4787

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: Min frac gradient (psi/ft): 0.91

Total acid used in treatment (bbl): Number of staged intervals: 1

Recycled water used in treatment (bbl): Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE

Total proppant used (lbs): 233769 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized:

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O:

Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:

Test Method: Casing PSI: Tubing PSI: Choke Size:

Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze:  Yes  No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Tania McNutt

Title: Regulatory Analyst Date: 7/11/2012 Email: tmcnutt@nobleenergyinc.com

**Attachment Check List**

Att Doc Num	Name
400304599	FORM 5A SUBMITTED

Total Attach: 1 Files

**General Comments**

**User Group Comment Comment Date**

User Group	Comment	Comment Date
------------	---------	--------------

Total: 0 comment(s)