

FORM  
5A

Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400337211

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 96850  
2. Name of Operator: WPX ENERGY ROCKY MOUNTAIN LLC  
3. Address: 1001 17TH STREET - SUITE #1200  
City: DENVER State: CO Zip: 80202  
4. Contact Name: Matt Barber  
Phone: (303) 606-4385  
Fax: (303) 629-8268

5. API Number 05-103-11898-00  
6. County: RIO BLANCO  
7. Well Name: Federal  
Well Number: RG 321-23-298  
8. Location: QtrQtr: SESW Section: 14 Township: 2S Range: 98W Meridian: 6  
9. Field Name: SULPHUR CREEK Field Code: 80090

Completed Interval

FORMATION: COZZETTE Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 07/29/2012 End Date: 08/01/2012 Date of First Production this formation: 07/31/2012

Perforations Top: 10061 Bottom: 10063 No. Holes: 4 Hole size: 0.35

Provide a brief summary of the formation treatment: Open Hole: ☐

91 gals 10% HCL; 1,472# 20/40; 21,000# 30/50; 4,000# 100-MESH; 485 BBL SLICKWATER

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): 487

Max pressure during treatment (psi):

Total gas used in treatment (mcf):

Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment:

Min frac gradient (psi/ft): 0.68

Total acid used in treatment (bbl): 2

Number of staged intervals: 1

Recycled water used in treatment (bbl): 485

Flowback volume recovered (bbl):

Fresh water used in treatment (bbl):

Disposition method for flowback: RECYCLE

Total proppant used (lbs): 26472

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O:

Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:

Test Method: Casing PSI: Tubing PSI: Choke Size:

Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

FORMATION: <u>CORCORAN</u>		Status: <u>PRODUCING</u>		Treatment Type: <u>FRACTURE STIMULATION</u>	
Treatment Date: <u>07/29/2012</u>		End Date: <u>08/01/2012</u>		Date of First Production this formation: <u>07/31/2012</u>	
Perforations	Top: <u>10113</u>	Bottom: <u>10337</u>	No. Holes: <u>21</u>	Hole size: <u>0.35</u>	

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole: ☐

474 gals 10% HCL; 8,002# 20/40, 108,175# 30/50, 20,775# 100-MESH; 2,823 BBLS SLICKWATER

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): <u>2834</u>	Max pressure during treatment (psi): _____
Total gas used in treatment (mcf): _____	Fluid density at initial fracture (lbs/gal): <u>8.43</u>
Type of gas used in treatment: _____	Min frac gradient (psi/ft): <u>0.68</u>
Total acid used in treatment (bbl): <u>11</u>	Number of staged intervals: <u>1</u>
Recycled water used in treatment (bbl): <u>2823</u>	Flowback volume recovered (bbl): _____
Fresh water used in treatment (bbl): _____	Disposition method for flowback: <u>RECYCLE</u>
Total proppant used (lbs): <u>136952</u>	Rule 805 green completion techniques were utilized: <input checked="" type="checkbox"/>

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: _____	Hours: _____	Bbl oil: _____	Mcf Gas: _____	Bbl H2O: _____
Calculated 24 hour rate: _____	Bbl oil: _____	Mcf Gas: _____	Bbl H2O: _____	GOR: _____
Test Method: _____	Casing PSI: _____	Tubing PSI: _____	Choke Size: _____	
Gas Disposition: _____	Gas Type: _____	Btu Gas: _____	API Gravity Oil: _____	
Tubing Size: _____	Tubing Setting Depth: _____	Tbg setting date: _____	Packer Depth: _____	

Reason for Non-Production:

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: <u>SEGO</u>		Status: <u>PRODUCING</u>		Treatment Type: <u>FRACTURE STIMULATION</u>	
Treatment Date: <u>07/29/2012</u>		End Date: <u>08/01/2012</u>		Date of First Production this formation: <u>07/31/2012</u>	
Perforations	Top: <u>10434</u>	Bottom: <u>10734</u>	No. Holes: <u>45</u>	Hole size: <u>0.35</u>	

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole: ☐

746 gals 10% HCL, 14,300# 20/40, 144,700# 30/50, 28,100# 100-MESH, 6,718 BBLS SLICKWATER

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): <u>6736</u>	Max pressure during treatment (psi): _____
Total gas used in treatment (mcf): _____	Fluid density at initial fracture (lbs/gal): <u>8.43</u>
Type of gas used in treatment: _____	Min frac gradient (psi/ft): <u>0.60</u>
Total acid used in treatment (bbl): <u>18</u>	Number of staged intervals: <u>2</u>
Recycled water used in treatment (bbl): <u>6718</u>	Flowback volume recovered (bbl): _____
Fresh water used in treatment (bbl): _____	Disposition method for flowback: <u>RECYCLE</u>
Total proppant used (lbs): <u>187100</u>	Rule 805 green completion techniques were utilized: <input checked="" type="checkbox"/>

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: _____	Hours: _____	Bbl oil: _____	Mcf Gas: _____	Bbl H2O: _____
Calculated 24 hour rate: _____	Bbl oil: _____	Mcf Gas: _____	Bbl H2O: _____	GOR: _____
Test Method: _____	Casing PSI: _____	Tubing PSI: _____	Choke Size: _____	
Gas Disposition: _____	Gas Type: _____	Btu Gas: _____	API Gravity Oil: _____	
Tubing Size: _____	Tubing Setting Depth: _____	Tbg setting date: _____	Packer Depth: _____	

Reason for Non-Production:

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: <u>WILLIAMS FORK - CAMEO</u>		Status: <u>PRODUCING</u>		Treatment Type: <u>FRACTURE STIMULATION</u>	
Treatment Date: <u>07/29/2012</u>		End Date: <u>08/01/2012</u>		Date of First Production this formation: <u>07/31/2012</u>	
Perforations	Top: <u>8277</u>	Bottom: <u>9659</u>	No. Holes: <u>126</u>	Hole size: <u>0.35</u>	

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole: ☐

3,090 gals 10% HCL; 36,400# 20/40; 371,800# 30/50; 166,500# 100-MESH; 20,501 BBLS SLICKWATER

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): <u>20575</u>	Max pressure during treatment (psi): _____
Total gas used in treatment (mcf): _____	Fluid density at initial fracture (lbs/gal): <u>8.43</u>
Type of gas used in treatment: _____	Min frac gradient (psi/ft): <u>0.60</u>
Total acid used in treatment (bbl): <u>73</u>	Number of staged intervals: <u>6</u>
Recycled water used in treatment (bbl): <u>20501</u>	Flowback volume recovered (bbl): _____
Fresh water used in treatment (bbl): _____	Disposition method for flowback: <u>RECYCLE</u>
Total proppant used (lbs): <u>574700</u>	Rule 805 green completion techniques were utilized: <input checked="" type="checkbox"/>

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: _____	Hours: _____	Bbl oil: _____	Mcf Gas: _____	Bbl H2O: _____
Calculated 24 hour rate: _____	Bbl oil: _____	Mcf Gas: _____	Bbl H2O: _____	GOR: _____
Test Method: _____	Casing PSI: _____	Tubing PSI: _____	Choke Size: _____	
Gas Disposition: _____	Gas Type: _____	Btu Gas: _____	API Gravity Oil: _____	
Tubing Size: _____	Tubing Setting Depth: _____	Tbg setting date: _____	Packer Depth: _____	

Reason for Non-Production:

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: WILLIAMS FORK-ILES Status: COMMINGLED Treatment Type: FRACTURE STIMULATION  
Treatment Date: 07/29/2012 End Date: 08/01/2012 Date of First Production this formation: 07/31/2012  
Perforations Top: 8277 Bottom: 10734 No. Holes: 196 Hole size: 0.35

Provide a brief summary of the formation treatment:

Open Hole: ☐

4,401 gals 10% HCL, 60,174# 20/40, 645,675# 30/50, 219,375# 100-MESH, 30,528 BBL SLICKWATER

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 30633

Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_

Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment: \_\_\_\_\_

Min frac gradient (psi/ft): 0.60

Total acid used in treatment (bbl): 105

Number of staged intervals: 10

Recycled water used in treatment (bbl): 30528

Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_

Disposition method for flowback: RECYCLE

Total proppant used (lbs): 925224

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

#### Test Information:

Date: 08/30/2012 Hours: 24 Bbl oil: \_\_\_\_\_ Mcf Gas: 1905 Bbl H2O: \_\_\_\_\_  
Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: 1905 Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: FLOWING Casing PSI: 2265 Tubing PSI: 1718 Choke Size: 17/64  
Gas Disposition: SOLD Gas Type: DRY Btu Gas: 1055 API Gravity Oil: \_\_\_\_\_  
Tubing Size: 2 + 3/8 Tubing Setting Depth: 10366 Tbg setting date: 08/08/2012 Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Matt Barber

Title: Sr. Regulatory Specialist Date: \_\_\_\_\_ Email matt.barber@wpenergy.com

#### Attachment Check List

Att Doc Num	Name
400337381	WELLBORE DIAGRAM

Total Attach: 1 Files

#### General Comments

User Group	Comment	Comment Date

Total: 0 comment(s)