



		TARGET DETAILS						
Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape
SL #1-26	0.00	0.00	0.00	1474458.59	3401087.99	40°37'36.505N	104°03'18.027W	Point
600' entry #1-26	6208.19	344.61	-287.70	1474803.20	3400800.29	40°37'39.956N	104°03'21.685W	Point
BHL #1-26	6233.37	4074.46	-249.52	1478533.05	3400838.47	40°38'16.801N	104°03'20.402W	Point
PBHL #1-26	6246.68	4378.03	-265.81	1478836.62	3400822.18	40°38'19.803N	104°03'20.549W	Point

Precision Directional Services, Inc.

Survey Report

Company: CARRIZO OIL & GAS, INC. Field: Niobrara CONZ'83 Site: Hemberger 26 Pad Well: 1-26-34-8-60 Wellpath: Original Hole	Date: 10/19/2012 Co-ordinate(NE) Reference: Vertical (TVD) Reference: Section (VS) Reference: Survey Calculation Method:	Time: 11:46:05 Well: 1-26-34-8-60, Grid North 4874'GL+17'KB 4891.0 Well (0.00N,0.00E,0.05Azi) Minimum Curvature	Page: 1 Db: Adapti
---	---	--	-------------------------------------

Field: Niobrara CONZ'83			
Map System: US State Plane Coordinate System 1983		Map Zone: Colorado, Northern Zone	
Geo Datum: GRS 1980		Coordinate System: Well Centre	
Sys Datum: Mean Sea Level		Geomagnetic Model: IGRF2010	

Site: Hemberger 26 Pad			
Weld County, CO			
Site Position:	Northing: 1474476.56 ft	Latitude: 40 37 36.689 N	
From: Map	Easting: 3401047.83 ft	Longitude: 104 3 18.544 W	
Position Uncertainty: 0.00 ft		North Reference: Grid	
Ground Level: 4874.00 ft		Grid Convergence: 0.93 deg	

Well: 1-26-34-8-60		Slot Name:	
SL adjusted 10-17 post drill			
Well Position: +N/-S -17.97 ft	Northing: 1474458.59 ft	Latitude: 40 37 36.505 N	
+E/-W 40.16 ft	Easting : 3401087.99 ft	Longitude: 104 3 18.027 W	
Position Uncertainty: 0.00 ft			

Wellpath: Original Hole		Drilled From: Surface	
		Tie-on Depth: 0.00 ft	
Current Datum: 4874'GL+17'KB	Height 4891.00 ft	Above System Datum: Mean Sea Level	
Magnetic Data: 07/27/2012		Declination: 8.35 deg	
Field Strength: 53246 nT		Mag Dip Angle: 67.31 deg	
Vertical Section: Depth From (TVD)	+N/-S	+E/-W	Direction
ft	ft	ft	deg
0.00	0.00	0.00	0.05

Survey Program for Definitive Wellpath					
Date: 08/22/2012		Validated: No		Version: 2	
Actual From	To	Survey	Toolcode	Tool Name	
ft	ft				
234.00	10172.00	Survey #1 (234.00-10172.00)	MWD	Std MWD	
10240.00	10240.00	Survey #2 (10240.00-10240.00)	Project	Projection	

Survey										
MD	Incl	Azim	TVD	+N/-S	+E/-W	VS	DLS	Build	Turn	Tool/Comment
ft	deg	deg	ft	ft	ft	ft	deg/100ft	deg/100ft	deg/100ft	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	TIE LINE
234.00	0.60	284.30	234.00	0.30	-1.19	0.30	0.26	0.26	0.00	MWD
326.00	1.00	274.10	325.99	0.48	-2.45	0.48	0.46	0.43	-11.09	MWD
420.00	2.60	274.20	419.94	0.69	-5.40	0.69	1.70	1.70	0.11	MWD
512.00	4.30	276.20	511.77	1.22	-10.91	1.21	1.85	1.85	2.17	MWD
604.00	4.50	280.20	603.50	2.23	-17.89	2.22	0.40	0.22	4.35	MWD
697.00	4.50	279.00	696.21	3.45	-25.08	3.43	0.10	0.00	-1.29	MWD
788.00	4.20	278.60	786.95	4.50	-31.91	4.48	0.33	-0.33	-0.44	MWD
879.00	4.30	269.50	877.70	4.97	-38.61	4.94	0.75	0.11	-10.00	MWD
971.00	5.20	248.40	969.39	3.41	-45.94	3.37	2.12	0.98	-22.93	MWD
1063.00	4.30	235.90	1061.07	-0.06	-52.67	-0.11	1.49	-0.98	-13.59	MWD
1154.00	4.00	219.40	1151.84	-4.43	-57.51	-4.48	1.35	-0.33	-18.13	MWD
1246.00	4.50	211.70	1243.59	-9.98	-61.44	-10.03	0.82	0.54	-8.37	MWD
1338.00	4.50	209.90	1335.30	-16.18	-65.14	-16.23	0.15	0.00	-1.96	MWD
1421.00	4.20	211.10	1418.06	-21.60	-68.33	-21.66	0.38	-0.36	1.45	MWD
1513.00	3.80	225.00	1509.84	-26.64	-72.23	-26.70	1.14	-0.43	15.11	MWD
1605.00	3.50	222.70	1601.65	-30.86	-76.29	-30.93	0.36	-0.33	-2.50	MWD
1696.00	3.30	218.00	1692.49	-34.97	-79.78	-35.04	0.38	-0.22	-5.16	MWD
1782.00	3.40	219.10	1778.35	-38.90	-82.92	-38.97	0.14	0.12	1.28	MWD
1867.00	3.00	232.60	1863.22	-42.20	-86.27	-42.28	1.00	-0.47	15.88	MWD
1951.00	2.60	227.70	1947.12	-44.82	-89.43	-44.90	0.55	-0.48	-5.83	MWD
2036.00	3.40	236.30	2032.00	-47.52	-92.95	-47.60	1.08	0.94	10.12	MWD

Precision Directional Services, Inc.

Survey Report

Company: CARRIZO OIL & GAS, INC. Field: Niobrara CONZ'83 Site: Hemberger 26 Pad Well: 1-26-34-8-60 Wellpath: Original Hole	Date: 10/19/2012 Co-ordinate(NE) Reference: Well: 1-26-34-8-60, Grid North Vertical (TVD) Reference: 4874'GL+17"KB 4891.0 Section (VS) Reference: Well (0.00N,0.00E,0.05Azi) Survey Calculation Method: Minimum Curvature	Time: 11:46:05 Page: 2 Db: Adapti
---	--	--

Survey

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	Tool/Comment
2121.00	2.90	239.10	2116.87	-50.02	-96.89	-50.10	0.62	-0.59	3.29	MWD
2207.00	2.90	238.00	2202.76	-52.29	-100.61	-52.38	0.06	0.00	-1.28	MWD
2292.00	2.70	236.80	2287.66	-54.52	-104.10	-54.62	0.25	-0.24	-1.41	MWD
2378.00	2.60	240.50	2373.57	-56.59	-107.50	-56.69	0.23	-0.12	4.30	MWD
2460.00	3.10	235.70	2455.46	-58.76	-110.95	-58.86	0.68	0.61	-5.85	MWD
2545.00	2.60	225.40	2540.36	-61.41	-114.22	-61.51	0.84	-0.59	-12.12	MWD
2631.00	4.00	236.10	2626.22	-64.45	-118.10	-64.55	1.77	1.63	12.44	MWD
2716.00	3.60	235.60	2711.03	-67.61	-122.76	-67.72	0.47	-0.47	-0.59	MWD
2801.00	3.70	233.50	2795.86	-70.75	-127.17	-70.86	0.20	0.12	-2.47	MWD
2886.00	3.80	235.20	2880.67	-73.99	-131.68	-74.11	0.18	0.12	2.00	MWD
2970.00	3.90	227.80	2964.49	-77.50	-136.09	-77.62	0.60	0.12	-8.81	MWD
3054.00	3.70	232.40	3048.30	-81.07	-140.35	-81.19	0.43	-0.24	5.48	MWD
3139.00	3.60	226.60	3133.13	-84.58	-144.46	-84.70	0.45	-0.12	-6.82	MWD
3224.00	3.30	225.40	3217.97	-88.13	-148.14	-88.26	0.36	-0.35	-1.41	MWD
3310.00	3.30	215.50	3303.83	-91.88	-151.34	-92.01	0.66	0.00	-11.51	MWD
3395.00	4.00	221.20	3388.66	-96.10	-154.72	-96.24	0.93	0.82	6.71	MWD
3480.00	4.00	216.80	3473.45	-100.71	-158.44	-100.85	0.36	0.00	-5.18	MWD
3565.00	4.70	224.70	3558.21	-105.56	-162.67	-105.70	1.08	0.82	9.29	MWD
3650.00	4.80	219.40	3642.92	-110.78	-167.38	-110.93	0.53	0.12	-6.24	MWD
3736.00	4.90	221.50	3728.61	-116.31	-172.09	-116.46	0.24	0.12	2.44	MWD
3821.00	4.70	218.00	3813.31	-121.78	-176.64	-121.93	0.42	-0.24	-4.12	MWD
3906.00	4.60	226.10	3898.03	-126.88	-181.24	-127.04	0.78	-0.12	9.53	MWD
3990.00	4.70	227.00	3981.76	-131.57	-186.19	-131.73	0.15	0.12	1.07	MWD
4074.00	3.80	229.10	4065.52	-135.74	-190.81	-135.90	1.09	-1.07	2.50	MWD
4159.00	2.80	209.60	4150.38	-139.39	-193.96	-139.55	1.75	-1.18	-22.94	MWD
4244.00	3.60	220.80	4235.25	-143.21	-196.73	-143.38	1.19	0.94	13.18	MWD
4330.00	2.30	224.00	4321.14	-146.50	-199.70	-146.67	1.52	-1.51	3.72	MWD
4415.00	2.30	221.90	4406.07	-148.99	-202.02	-149.17	0.10	0.00	-2.47	MWD
4500.00	1.20	227.80	4491.03	-150.86	-203.82	-151.04	1.31	-1.29	6.94	MWD
4585.00	1.80	249.50	4576.00	-151.93	-205.73	-152.11	0.96	0.71	25.53	MWD
4671.00	2.80	222.00	4661.93	-153.96	-208.40	-154.14	1.70	1.16	-31.98	MWD
4756.00	2.30	210.40	4746.85	-156.97	-210.65	-157.16	0.84	-0.59	-13.65	MWD
4841.00	3.20	209.60	4831.75	-160.51	-212.69	-160.69	1.06	1.06	-0.94	MWD
4925.00	3.70	215.50	4915.60	-164.75	-215.42	-164.94	0.73	0.60	7.02	MWD
5010.00	3.30	213.80	5000.44	-169.02	-218.37	-169.21	0.49	-0.47	-2.00	MWD
5095.00	3.60	219.20	5085.28	-173.12	-221.42	-173.31	0.52	0.35	6.35	MWD
5181.00	2.70	221.50	5171.15	-176.73	-224.47	-176.93	1.06	-1.05	2.67	MWD
5266.00	3.00	217.10	5256.05	-180.00	-227.14	-180.20	0.44	0.35	-5.18	MWD
5351.00	4.10	227.70	5340.88	-183.82	-230.73	-184.02	1.50	1.29	12.47	MWD
5436.00	3.30	215.90	5425.71	-187.85	-234.41	-188.05	1.29	-0.94	-13.88	MWD
5522.00	3.90	220.50	5511.54	-192.08	-237.76	-192.29	0.77	0.70	5.35	MWD
5581.00	3.50	220.60	5570.41	-194.97	-240.23	-195.18	0.68	-0.68	0.17	MWD
5623.00	3.30	222.90	5612.34	-196.83	-241.89	-197.04	0.58	-0.48	5.48	MWD
5666.00	5.50	275.50	5655.23	-197.54	-244.79	-197.75	10.16	5.12	122.33	MWD
5708.00	10.70	305.20	5696.81	-195.10	-249.98	-195.31	15.51	12.38	70.71	MWD
5751.00	15.00	325.90	5738.74	-188.18	-256.37	-188.40	14.50	10.00	48.14	MWD
5793.00	19.30	341.40	5778.89	-177.09	-261.64	-177.32	14.86	10.24	36.90	MWD
5835.00	23.60	351.40	5817.98	-162.19	-265.11	-162.42	13.41	10.24	23.81	MWD
5878.00	26.00	354.60	5857.02	-144.29	-267.28	-144.52	6.39	5.58	7.44	MWD
5920.00	29.60	353.00	5894.16	-124.82	-269.41	-125.06	8.75	8.57	-3.81	MWD
5963.00	35.40	353.70	5930.41	-101.88	-272.08	-102.12	13.52	13.49	1.63	MWD
6006.00	39.80	352.60	5964.47	-75.84	-275.22	-76.08	10.35	10.23	-2.56	MWD
6048.00	43.40	353.00	5995.88	-48.18	-278.71	-48.43	8.59	8.57	0.95	MWD

Precision Directional Services, Inc.

Survey Report

Company: CARRIZO OIL & GAS, INC. Field: Niobrara CONZ'83 Site: Hemberger 26 Pad Well: 1-26-34-8-60 Wellpath: Original Hole	Date: 10/19/2012 Co-ordinate(NE) Reference: Well: 1-26-34-8-60, Grid North Vertical (TVD) Reference: 4874'GL+17'KB 4891.0 Section (VS) Reference: Well (0.00N,0.00E,0.05Azi) Survey Calculation Method: Minimum Curvature	Time: 11:46:05 Page: 3 Db: Adapti
---	--	--

Survey

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	Tool/Comment
6090.00	46.60	353.50	6025.57	-18.69	-282.20	-18.94	7.67	7.62	1.19	MWD
6132.00	50.00	354.90	6053.51	12.50	-285.35	12.25	8.47	8.10	3.33	MWD
6175.00	52.60	355.60	6080.39	45.94	-288.13	45.69	6.18	6.05	1.63	MWD
6286.00	60.10	358.40	6141.86	138.14	-292.86	137.88	7.07	6.76	2.52	MWD
6332.00	65.90	359.30	6162.74	179.10	-293.68	178.84	12.73	12.61	1.96	MWD
6378.00	70.20	0.90	6179.93	221.75	-293.59	221.50	9.89	9.35	3.48	MWD
6425.00	74.70	2.80	6194.10	266.53	-292.14	266.27	10.32	9.57	4.04	MWD
6470.00	80.40	3.40	6203.80	310.39	-289.76	310.13	12.73	12.67	1.33	MWD
6504.58	84.99	3.48	6208.19	344.61	-287.70	344.36	13.26	13.26	0.22	600' entry
6516.00	86.50	3.50	6209.04	355.98	-287.01	355.73	13.26	13.26	0.22	MWD
6559.00	88.00	3.40	6211.10	398.85	-284.43	398.60	3.50	3.49	-0.23	MWD
6601.00	90.00	2.10	6211.84	440.79	-282.41	440.55	5.68	4.76	-3.10	MWD
6644.00	89.60	2.00	6211.99	483.77	-280.87	483.52	0.96	-0.93	-0.23	MWD
6686.00	89.50	1.60	6212.32	525.74	-279.55	525.50	0.98	-0.24	-0.95	MWD
6729.00	89.10	1.40	6212.84	568.73	-278.43	568.48	1.04	-0.93	-0.47	MWD
6771.00	89.20	1.30	6213.47	610.71	-277.44	610.47	0.34	0.24	-0.24	MWD
6814.00	90.90	1.10	6213.43	653.70	-276.54	653.46	3.98	3.95	-0.47	MWD
6856.00	90.40	0.60	6212.95	695.69	-275.92	695.45	1.68	-1.19	-1.19	MWD
6899.00	90.20	0.20	6212.73	738.69	-275.62	738.45	1.04	-0.47	-0.93	MWD
6942.00	90.20	0.40	6212.58	781.69	-275.39	781.45	0.47	0.00	0.47	MWD
6984.00	90.10	0.40	6212.47	823.69	-275.10	823.45	0.24	-0.24	0.00	MWD
7027.00	90.00	0.20	6212.43	866.69	-274.87	866.45	0.52	-0.23	-0.47	MWD
7069.00	89.90	0.00	6212.47	908.69	-274.80	908.45	0.53	-0.24	-0.48	MWD
7112.00	90.00	0.20	6212.50	951.69	-274.72	951.45	0.52	0.23	0.47	MWD
7154.00	90.10	0.40	6212.47	993.69	-274.50	993.45	0.53	0.24	0.48	MWD
7197.00	88.70	0.70	6212.92	1036.68	-274.09	1036.44	3.33	-3.26	0.70	MWD
7240.00	88.30	0.60	6214.04	1079.66	-273.60	1079.42	0.96	-0.93	-0.23	MWD
7282.00	87.80	0.20	6215.47	1121.64	-273.31	1121.40	1.52	-1.19	-0.95	MWD
7325.00	88.20	359.50	6216.97	1164.61	-273.42	1164.37	1.87	0.93	-1.63	MWD
7367.00	87.80	359.30	6218.44	1206.58	-273.86	1206.34	1.06	-0.95	-0.48	MWD
7410.00	89.60	0.00	6219.41	1249.57	-274.13	1249.33	4.49	4.19	1.63	MWD
7452.00	91.00	0.90	6219.19	1291.57	-273.80	1291.33	3.96	3.33	2.14	MWD
7495.00	90.60	0.90	6218.59	1334.56	-273.12	1334.32	0.93	-0.93	0.00	MWD
7538.00	92.00	0.70	6217.62	1377.54	-272.52	1377.30	3.29	3.26	-0.47	MWD
7580.00	91.80	0.60	6216.23	1419.51	-272.04	1419.28	0.53	-0.48	-0.24	MWD
7623.00	91.50	0.20	6214.99	1462.50	-271.74	1462.26	1.16	-0.70	-0.93	MWD
7666.00	91.10	359.90	6214.01	1505.48	-271.71	1505.25	1.16	-0.93	-0.70	MWD
7708.00	90.60	359.50	6213.39	1547.48	-271.93	1547.24	1.52	-1.19	-0.95	MWD
7751.00	90.00	359.00	6213.16	1590.47	-272.49	1590.24	1.82	-1.40	-1.16	MWD
7793.00	89.20	357.70	6213.46	1632.45	-273.70	1632.21	3.63	-1.90	-3.10	MWD
7836.00	89.00	357.40	6214.13	1675.41	-275.54	1675.17	0.84	-0.47	-0.70	MWD
7879.00	92.20	358.60	6213.68	1718.37	-277.04	1718.13	7.95	7.44	2.79	MWD
7921.00	92.40	358.60	6212.00	1760.33	-278.06	1760.09	0.48	0.48	0.00	MWD
7963.00	92.00	358.30	6210.38	1802.28	-279.20	1802.04	1.19	-0.95	-0.71	MWD
8005.00	92.00	357.70	6208.92	1844.23	-280.66	1843.98	1.43	0.00	-1.43	MWD
8047.00	91.40	0.00	6207.67	1886.20	-281.50	1885.95	5.66	-1.43	5.48	MWD
8089.00	91.60	0.70	6206.57	1928.19	-281.25	1927.94	1.73	0.48	1.67	MWD
8131.00	91.00	2.70	6205.62	1970.15	-280.00	1969.91	4.97	-1.43	4.76	MWD
8174.00	89.70	4.10	6205.36	2013.08	-277.45	2012.83	4.44	-3.02	3.26	MWD
8216.00	88.60	3.90	6205.98	2054.97	-274.52	2054.73	2.66	-2.62	-0.48	MWD
8259.00	88.50	3.90	6207.07	2097.85	-271.60	2097.62	0.23	-0.23	0.00	MWD
8302.00	88.00	4.10	6208.38	2140.73	-268.60	2140.49	1.25	-1.16	0.47	MWD
8344.00	88.00	3.70	6209.85	2182.61	-265.75	2182.37	0.95	0.00	-0.95	MWD
8387.00	89.60	1.60	6210.75	2225.55	-263.76	2225.32	6.14	3.72	-4.88	MWD

Precision Directional Services, Inc.

Survey Report

Company: CARRIZO OIL & GAS, INC. Field: Niobrara CONZ'83 Site: Hemberger 26 Pad Well: 1-26-34-8-60 Wellpath: Original Hole	Date: 10/19/2012 Co-ordinate(NE) Reference: Well: 1-26-34-8-60, Grid North Vertical (TVD) Reference: 4874'GL+17'KB 4891.0 Section (VS) Reference: Well (0.00N,0.00E,0.05Azi) Survey Calculation Method: Minimum Curvature	Time: 11:46:05 Page: 4 Db: Adapti
---	--	--

Survey

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100ft	Build deg/100ft	Turn deg/100ft	Tool/Comment
8429.00	89.40	1.60	6211.11	2267.53	-262.59	2267.30	0.48	-0.48	0.00	MWD
8472.00	89.50	1.40	6211.53	2310.51	-261.46	2310.28	0.52	0.23	-0.47	MWD
8514.00	89.30	1.30	6211.97	2352.50	-260.47	2352.27	0.53	-0.48	-0.24	MWD
8557.00	89.80	0.90	6212.30	2395.49	-259.65	2395.26	1.49	1.16	-0.93	MWD
8599.00	89.40	0.70	6212.60	2437.48	-259.06	2437.26	1.06	-0.95	-0.48	MWD
8641.00	89.30	0.90	6213.07	2479.48	-258.47	2479.25	0.53	-0.24	0.48	MWD
8684.00	89.50	1.10	6213.52	2522.47	-257.72	2522.24	0.66	0.47	0.47	MWD
8727.00	88.70	1.10	6214.20	2565.45	-256.90	2565.23	1.86	-1.86	0.00	MWD
8769.00	88.80	0.40	6215.12	2607.44	-256.35	2607.22	1.68	0.24	-1.67	MWD
8812.00	88.90	359.10	6215.98	2650.43	-256.54	2650.21	3.03	0.23	-3.02	MWD
8855.00	89.10	358.60	6216.73	2693.42	-257.40	2693.19	1.25	0.47	-1.16	MWD
8897.00	89.30	359.50	6217.32	2735.40	-258.09	2735.18	2.19	0.48	2.14	MWD
8940.00	89.50	0.00	6217.77	2778.40	-258.28	2778.18	1.25	0.47	1.16	MWD
8983.00	90.00	1.10	6217.95	2821.40	-257.87	2821.17	2.81	1.16	2.56	MWD
9025.00	89.60	1.10	6218.10	2863.39	-257.06	2863.17	0.95	-0.95	0.00	MWD
9067.00	89.40	2.00	6218.47	2905.37	-255.93	2905.15	2.20	-0.48	2.14	MWD
9109.00	89.80	2.50	6218.76	2947.34	-254.28	2947.12	1.52	0.95	1.19	MWD
9152.00	89.40	3.50	6219.06	2990.28	-252.03	2990.06	2.50	-0.93	2.33	MWD
9194.00	88.70	2.50	6219.76	3032.21	-249.83	3032.00	2.91	-1.67	-2.38	MWD
9236.00	88.60	1.60	6220.75	3074.18	-248.33	3073.96	2.16	-0.24	-2.14	MWD
9278.00	90.00	4.40	6221.26	3116.11	-246.13	3115.89	7.45	3.33	6.67	MWD
9320.00	89.60	4.80	6221.41	3157.97	-242.76	3157.76	1.35	-0.95	0.95	MWD
9363.00	90.00	7.80	6221.56	3200.71	-238.04	3200.50	7.04	0.93	6.98	MWD
9406.00	89.70	8.30	6221.67	3243.29	-232.02	3243.08	1.36	-0.70	1.16	MWD
9448.00	90.00	8.10	6221.78	3284.86	-226.03	3284.66	0.86	0.71	-0.48	MWD
9491.00	89.50	6.00	6221.97	3327.53	-220.75	3327.33	5.02	-1.16	-4.88	MWD
9533.00	89.60	5.70	6222.30	3369.31	-216.47	3369.12	0.75	0.24	-0.71	MWD
9576.00	91.10	4.80	6222.03	3412.12	-212.54	3411.94	4.07	3.49	-2.09	MWD
9619.00	88.50	0.60	6222.18	3455.06	-210.51	3454.88	11.49	-6.05	-9.77	MWD
9661.00	87.70	357.60	6223.58	3497.03	-211.17	3496.84	7.39	-1.90	-7.14	MWD
9704.00	87.10	357.20	6225.53	3539.94	-213.12	3539.75	1.68	-1.40	-0.93	MWD
9746.00	89.20	357.60	6226.88	3581.87	-215.03	3581.68	5.09	5.00	0.95	MWD
9789.00	88.90	357.40	6227.60	3624.83	-216.90	3624.64	0.84	-0.70	-0.47	MWD
9831.00	88.80	357.40	6228.44	3666.78	-218.81	3666.58	0.24	-0.24	0.00	MWD
9874.00	89.20	356.90	6229.19	3709.72	-220.94	3709.52	1.49	0.93	-1.16	MWD
9917.00	88.80	357.00	6229.94	3752.65	-223.23	3752.45	0.96	-0.93	0.23	MWD
9959.00	89.50	355.80	6230.56	3794.56	-225.87	3794.36	3.31	1.67	-2.86	MWD
10002.00	88.50	355.80	6231.31	3837.44	-229.02	3837.24	2.33	-2.33	0.00	MWD
10044.00	88.00	355.50	6232.60	3879.30	-232.20	3879.09	1.39	-1.19	-0.71	MWD
10087.00	87.90	355.80	6234.13	3922.14	-235.46	3921.94	0.73	-0.23	0.70	MWD
10130.00	90.00	355.50	6234.92	3965.01	-238.72	3964.80	4.93	4.88	-0.70	MWD
10172.00	91.00	354.10	6234.56	4006.84	-242.53	4006.62	4.10	2.38	-3.33	MWD
10240.00	91.00	354.10	6233.37	4074.46	-249.52	4074.25	0.00	0.00	0.00	Project

Annotation

MD ft	TVD ft	
6504.58	6208.19	600' entry