Company: Sundance Energy Inc.
API # (NE): 4501306
Well Name: Hellerung
Unit:
Field: Cabernet
County: Pecos
State: Texas
Country: USA
Surface Location: Abstract 1, Block 139, H&TC RR Co. Survey
Latitude: 30° 54' 29.2" N
Longitude: 102° 49' 39.1" W
Datum: NAD 83
Projection: Texas Centric Mapping System, Lambert Conformal
Elevation: KB: 2,977.00 ft above MSL
GL: 2,952.00 ft above MSL
Spud Date: 9/6/2012
Drilling Completed: 9/15/2012
Surface Casing: 9 5/8" @ 1,500 ft MD
Production Casing: 5 1/2" @ 16,945 ft MD
Open Hole: 8 3/4" OH from 1,500 ft MD to 16,945 ft MD
Survey Type: Definitive
Survey Company: Ryan Directional Services, Inc.
Job Number: 12-0000

All interpretations are opinions based on inferences from electrical or other measurements our Pioneer Oklahoma Agency, LLC service and does not guarantee the accuracy or correctness of any interpretations, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss or damages incurred by any of our officers, agents or employees.

Comments

Annular volume calculated for 4.5" casing
Tie-in to Surface Gyro
Thank you for using Pioneer Wireline!
No repeat pass due to hole conditions.

Database File: 12345.db
Dataset Pathname: pass1
Presentation Format: main
Dataset Creation: Sat Oct 13 09:51:56 2012
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GAPI) 150
Density Caliper (in) 16
SP (MV) 200
Deep Resistivity (Ohm-m) .2000 20
Medium Resistivity (Ohm-m) .2000 20
Shallow Resistivity (Ohm-m) .2000 20
Bit Diameter (in) 20
Density Porosity (pu) 60
Neutron Porosity (pu) -30

Depth (ft)

Gamma Ray (GAPI) 150
Density Caliper (in) 16
SP (MV) 200
Deep Resistivity (Ohm-m) .2000 20
Medium Resistivity (Ohm-m) .2000 20
Shallow Resistivity (Ohm-m) .2000 20
Bit Diameter (in) 20
Density Porosity (pu) 60
Neutron Porosity (pu) -30

Depth (ft)

Database File: 12345.db
Dataset Pathname: main
Presentation Format: main
Dataset Creation: Sat Oct 13 09:51:56 2012
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GAPI) 150
Density Caliper (in) 16
SP (MV) 200
Deep Resistivity (Ohm-m) .2000 20
Medium Resistivity (Ohm-m) .2000 20
Shallow Resistivity (Ohm-m) .2000 20
Bit Diameter (in) 20
Density Porosity (pu) 60
Neutron Porosity (pu) -30

Depth (ft)

Gamma Ray (GAPI) 150
Density Caliper (in) 16
SP (MV) 200
Deep Resistivity (Ohm-m) .2000 20
Medium Resistivity (Ohm-m) .2000 20
Shallow Resistivity (Ohm-m) .2000 20
Bit Diameter (in) 20
Density Porosity (pu) 60
Neutron Porosity (pu) -30

Depth (ft)

Database File: 12345.db
Dataset Pathname: main
Presentation Format: main
Dataset Creation: Sat Oct 13 09:51:56 2012
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GAPI) 150
Density Caliper (in) 16
SP (MV) 200
Deep Resistivity (Ohm-m) .2000 20
Medium Resistivity (Ohm-m) .2000 20
Shallow Resistivity (Ohm-m) .2000 20
Bit Diameter (in) 20
Density Porosity (pu) 60
Neutron Porosity (pu) -30

Depth (ft)

Gamma Ray (GAPI) 150
Density Caliper (in) 16
SP (MV) 200
Deep Resistivity (Ohm-m) .2000 20
Medium Resistivity (Ohm-m) .2000 20
Shallow Resistivity (Ohm-m) .2000 20
Bit Diameter (in) 20
Density Porosity (pu) 60
Neutron Porosity (pu) -30

Depth (ft)