

WEXPRO COMPANY
CONSTRUCTION LAYOUT FOR

DONNELL #20
SECTION 6, T11N, R97W, 6th P.M.
652' FNL 1972' FWL

FIGURE #1

SCALE: 1" = 60'
DATE: 09-16-09
DRAWN BY: L.K.
REV: 12-14-09 K.G.
REV: 05-08-12 J.J.

Prevailing Winds

Existing Drainage

CONSTRUCT DIVERSION DITCH

EROSION CONTROL DEVICE

Topsoil Stockpile

C-0.7' El. 81.7'

C-0.5' El. 81.5'

Sta. 4+00

ROBERT L. KAY
REGISTERED
LAND SURVEYOR
STATE OF COLORADO
05-14-02

Approx. Toe of Fill Slope

Construct Berm

NOTE:
Flare Pit is to be located a min. of 100' from the Well Head.

Flare Pit

FLOW

Cut/Fill Transition Line

Existing 2-Track

Existing Fence

Existing 2-Track

El. 78.3'

C-9.3' (Btm. Pit)

F-0.9' El. 80.1'

130'

C-0.5' El. 81.5'

150'

Sta. 2+00

F-0.1' El. 80.9'

Cut/Fill Transition Line

Construct Berm

Sta. 1+00

Total Pit Capacity W/2' of Freeboard = 15,760 Bbls. ±
Total Pit Volume = 4,250 Cu. Yds

CUTTINGS PIT (12' Deep)

1 1/2:1 SLOPE

10' WIDE BENCH/DIKE

200'

El. 81.1'

C-12.1' (Btm. Pit)

10' WIDE BENCH

A

AREA OF MAX. DISTURBANCE

Approx. Top of Cut Slope

C-0.8' El. 81.8'

3

C-1.4' El. 82.4'

Proposed Access Road

Sta. 0+00

2

C-1.6' El. 82.6'

Elev. Ungraded Ground At Loc. Stake = 6981.5'
FINISHED GRADE ELEV. AT LOC. STAKE = 6981.0'

UINTAH ENGINEERING & LAND SURVEYING
85 So. 200 East * Vernal, Utah 84078 * (435) 789-1017

UINTAH ENGINEERING & LAND SURVEYING
85 So. 200 East * Vernal, Utah 84078 * (435) 789-1017