




<<< Fold Here >>>
All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.
Comments
THANK YOU FOR CHOOSING PURE ENERGY SERVICES LOG RAN AS MAIN WIRELINE DEPTH REFERENCE LOG RAN AT 1500 PSI SURFACE

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			STNDRD Standard Cable Head	1.00	1.44	10.00

CCL	22.21		CCL-275tekco (2.75TEKCO) 2 3/4 TEK CCL Earth Mag	1.92	2.75	20.00
			SDSCENT Centralizer for testing	2.73	2.75	20.00
TEMP	16.38					
WVFS1	15.00					
WVFS2	15.00					
WVFS3	15.00		275CTEKSECWTWSLCANS-275RIB (1234) 2 3/4" (R.I.B.) TOOL 3FT, 5FT and 8EA RIB SIGNALS 400 DEG "F" @20K PSI With Sliding Cans For Pressure Ballance	9.31	2.75	102.00
WVFS4	15.00					
WVFS5	15.00					
WVFS6	15.00					
WVFS7	15.00					
WVFS8	15.00					
WVF3FT	14.25					
WVF5FT	13.25					
WVFCAL	9.46					
WVFTEMP	9.46					
WVFSYNC	9.46		SDSCENT Centralizer for testing	2.73	2.75	20.00
			GR-Tek-Co (Tek-Co2) 2 3/4 400deg Scint gamma	4.00	2.75	40.00
GR	3.77					
			SDSCENT Centralizer for testing	2.73	2.75	20.00
Dataset: whiting_razor11-0241h.db: field/well/run1/pass2 Total Length: 24.42 ft Total Weight: 232.00 lb O.D. 2.75 in						

0	Gamma Ray	150	0	3' Amplitude (mV)	100	5' Variable Density Log	Sector Map	0	Average Amplitude	100
	Collar Locator			3' Amplitude x 5	200			0	Minimum Amplitude	100
				(mV)	20			0	Maximum Amplitude	100
				3' Travel Time						
				650 (usec)	150					

