

FORM  
5A  
Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:  
400420873

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: <u>100322</u>	4. Contact Name: <u>JEAN MUSE-REYNOLDS</u>
2. Name of Operator: <u>NOBLE ENERGY INC</u>	Phone: <u>(303) 228-4316</u>
3. Address: <u>1625 BROADWAY STE 2200</u>	Fax: <u>(303) 228-4286</u>
City: <u>DENVER</u> State: <u>CO</u> Zip: <u>80202</u>	

5. API Number <u>05-123-35624-00</u>	6. County: <u>WELD</u>
7. Well Name: <u>ADAMS D</u>	Well Number: <u>30-30D</u>
8. Location: QtrQtr: <u>NENW</u> Section: <u>30</u> Township: <u>3N</u> Range: <u>64W</u> Meridian: <u>6</u>	
9. Field Name: <u>WATTENBERG</u> Field Code: <u>90750</u>	

Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 09/10/2012 End Date: 09/10/2012 Date of First Production this formation: 09/25/2012  
Perforations Top: 7508 Bottom: 7522 No. Holes: 56 Hole size: 0.4

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

PUMPED 244777# OTTAWA SAND DOWNHOLE in 124944gals of 15% HCL/Vistar/GELLED/SLICK/RECYCLED/FRESH WATER  
FLOWBACK VOLUMES REPORTED ON NIOBRARA PANEL  
CODELL IS PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUG

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 2975 Max pressure during treatment (psi): 3952  
Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.34  
Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): 0.86  
Total acid used in treatment (bbl): 12 Number of staged intervals: 7  
Recycled water used in treatment (bbl): 252 Flowback volume recovered (bbl): \_\_\_\_\_  
Fresh water used in treatment (bbl): 2711 Disposition method for flowback: RECYCLE  
Total proppant used (lbs): 244777 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: \_\_\_\_\_

Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date of First Production this formation: 09/25/2012

Perforations Top: 7278 Bottom: 7522 No. Holes: 104 Hole size: 0.4

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

FLOWBACK VOLUMES REPORTED ON NIOBRARA PANEL  
CODELL IS PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUG

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: 09/29/2012 Hours: 24 Bbl oil: 43 Mcf Gas: 166 Bbl H2O: 61

Calculated 24 hour rate: Bbl oil: 43 Mcf Gas: 166 Bbl H2O: 61 GOR: 3860

Test Method: FLOWING Casing PSI: 350 Tubing PSI: 0 Choke Size: 12/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1246 API Gravity Oil: 52

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 09/10/2012 End Date: 09/10/2012 Date of First Production this formation: 09/25/2012  
Perforations Top: 7278 Bottom: 7378 No. Holes: 48 Hole size: 0.4

Provide a brief summary of the formation treatment: Open Hole:

PUMPED 245075# OTTAWA SAND DOWNHOLE in 153938gals of Vistar/GELLED/SLICK/RECYCLED/FRESH WATER  
FLOWBACK VOLUMES REPORTED ON NIOBRARA PANEL  
CODELL IS PRODUCING THROUGH COMPOSITE FLOW-THROUGH PLUG

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3665 Max pressure during treatment (psi): 4444  
Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.34  
Type of gas used in treatment: Min frac gradient (psi/ft): 0.91  
Total acid used in treatment (bbl): 0 Number of staged intervals: 7  
Recycled water used in treatment (bbl): 264 Flowback volume recovered (bbl): 1262  
Fresh water used in treatment (bbl): 3401 Disposition method for flowback: RECYCLE  
Total proppant used (lbs): 245075 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized:

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:  
FLOWBACK VOLUMES REPORTED ON NIOBRARA PANEL.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.  
Signed: \_\_\_\_\_ Print Name: JEAN MUSE-REYNOLDS  
Title: REGULATORY COMPLIANCE Date: \_\_\_\_\_ Email: jmuse@nobleenergyinc.com

**Attachment Check List**

Att Doc Num	Name

Total Attach: 0 Files

**General Comments**

User Group	Comment	Comment Date

Total: 0 comment(s)