

FORM
5A

Rev
06/12

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE ET OE ES

Document Number:

400427929

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322
2. Name of Operator: NOBLE ENERGY INC
3. Address: 1625 BROADWAY STE 2200
City: DENVER State: CO Zip: 80202
4. Contact Name: Kathleen Mills
Phone: (720) 587-2226
Fax: (303) 228-4286

5. API Number 05-123-35674-00
6. County: WELD
7. Well Name: WELLS RANCH AE
Well Number: 18-68-1HN
8. Location: QtrQtr: NWNW Section: 18 Township: 6N Range: 62W Meridian: 6
9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 01/04/2013 End Date: 01/04/2013 Date of First Production this formation: 02/16/2013

Perforations Top: 7167 Bottom: 10984 No. Holes: 0 Hole size:

Provide a brief summary of the formation treatment: Open Hole: ☐

FRAC'D W/3275872 GAL SILVERSTIMM AND SLICK WATER AND 3766697# OTTAWA SAND

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 77997 Max pressure during treatment (psi): 5950

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment: Min frac gradient (psi/ft): 0.74

Total acid used in treatment (bbl): Number of staged intervals: 20

Recycled water used in treatment (bbl): 4088 Flowback volume recovered (bbl): 15775

Fresh water used in treatment (bbl): 73909 Disposition method for flowback: RECYCLE

Total proppant used (lbs): 3766697 Rule 805 green completion techniques were utilized: ☐

Reason why green completion not utilized: PIPELINE

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 02/20/2013 Hours: 24 Bbl oil: 157 Mcf Gas: 292 Bbl H2O: 367

Calculated 24 hour rate: Bbl oil: 157 Mcf Gas: 292 Bbl H2O: 367 GOR: 1860

Test Method: FLOWING Casing PSI: 377 Tubing PSI: 477 Choke Size: 20/64

Gas Disposition: FLARED Gas Type: SHALE Btu Gas: 0 API Gravity Oil: 40

Tubing Size: 2 + 7/8 Tubing Setting Depth: 6893 Tbg setting date: 01/24/2013 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Kathleen Mills

Title: Regulatory Analyst Date: _____ Email: kmills@nobleenergyinc.com
:

Attachment Check List

Att Doc Num	Name

Total Attach: 0 Files

General Comments

User Group **Comment** **Comment Date**

--	--	--

Total: 0 comment(s)