

Ursa Operating Company, LLC

Rockies Region

Speakman A

BAT 33B-24-07-96

Wellbore #1

Plan: Design #1

Standard Planning Report

13 June, 2013



Payzone Directional

Planning Report



Database:	EDM 2003.21 Single User Db	Local Co-ordinate Reference:	Well BAT 33B-24-07-96
Company:	Ursa Operating Company, LLC	TVD Reference:	BAT 33B-24-07-96 @ 5197.9ft (Original Well Elev)
Project:	Rockies Region	MD Reference:	BAT 33B-24-07-96 @ 5197.9ft (Original Well Elev)
Site:	Speakman A	North Reference:	True
Well:	BAT 33B-24-07-96	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Project	Rockies Region		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Central Zone		

Site		Speakman A			
Site Position:		Northing:	484,154.15 m	Latitude:	39° 25' 15.663 N
From:	Lat/Long	Easting:	693,950.13 m	Longitude:	108° 3' 38.016 W
Position Uncertainty:	0.0 ft	Slot Radius:	in	Grid Convergence:	-1.61 °

Well	BAT 33B-24-07-96, SHL LAT: 39.420933287 LONG: -108.060351659					
Well Position	+N/-S	-30.7 ft	Northing:	484,144.29 m	Latitude:	39° 25' 15.360 N
	+E/-W	58.9 ft	Easting:	693,967.81 m	Longitude:	108° 3' 37.266 W
Position Uncertainty		0.0 ft	Wellhead Elevation:	5,197.9 ft	Ground Level:	5,182.5 ft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF200510	6/13/2013	10.08	65.63	52,047

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)
	0.0	0.0	0.0	72.71

Plan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
200.0	0.00	0.00	200.0	0.0	0.0	0.00	0.00	0.00	0.00	
960.8	26.63	72.71	933.7	51.6	165.8	3.50	3.50	0.00	72.71	
3,204.4	26.63	72.71	2,939.3	350.4	1,125.9	0.00	0.00	0.00	0.00	
3,965.1	0.00	0.00	3,673.0	402.0	1,291.6	3.50	-3.50	0.00	180.00	BAT 33B-24-07-96 TC
6,187.1	0.00	0.00	5,895.0	402.0	1,291.6	0.00	0.00	0.00	0.00	BAT 33B-24-07-96 Bf

Payzone Directional Planning Report



Database:	EDM 2003.21 Single User Db	Local Co-ordinate Reference:	Well BAT 33B-24-07-96
Company:	Ursa Operating Company, LLC	TVD Reference:	BAT 33B-24-07-96 @ 5197.9ft (Original Well Elev)
Project:	Rockies Region	MD Reference:	BAT 33B-24-07-96 @ 5197.9ft (Original Well Elev)
Site:	Speakman A	North Reference:	True
Well:	BAT 33B-24-07-96	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
Start Build 3.50									
300.0	3.50	72.71	299.9	0.9	2.9	3.1	3.50	3.50	0.00
400.0	7.00	72.71	399.5	3.6	11.7	12.2	3.50	3.50	0.00
500.0	10.50	72.71	498.3	8.1	26.2	27.4	3.50	3.50	0.00
600.0	14.00	72.71	596.0	14.5	46.4	48.6	3.50	3.50	0.00
700.0	17.50	72.71	692.3	22.5	72.3	75.8	3.50	3.50	0.00
800.0	21.00	72.71	786.7	32.3	103.8	108.7	3.50	3.50	0.00
900.0	24.50	72.71	878.9	43.8	140.7	147.4	3.50	3.50	0.00
960.8	26.63	72.71	933.7	51.6	165.8	173.6	3.50	3.50	0.00
Start 2243.6 hold at 960.8 MD									
1,000.0	26.63	72.71	968.7	56.8	182.6	191.2	0.00	0.00	0.00
1,100.0	26.63	72.71	1,058.1	70.1	225.4	236.0	0.00	0.00	0.00
1,200.0	26.63	72.71	1,147.5	83.5	268.1	280.8	0.00	0.00	0.00
1,300.0	26.63	72.71	1,236.9	96.8	310.9	325.7	0.00	0.00	0.00
1,400.0	26.63	72.71	1,326.3	110.1	353.7	370.5	0.00	0.00	0.00
1,500.0	26.63	72.71	1,415.7	123.4	396.5	415.3	0.00	0.00	0.00
1,600.0	26.63	72.71	1,505.1	136.7	439.3	460.1	0.00	0.00	0.00
1,700.0	26.63	72.71	1,594.5	150.1	482.1	504.9	0.00	0.00	0.00
1,800.0	26.63	72.71	1,683.9	163.4	524.9	549.7	0.00	0.00	0.00
1,900.0	26.63	72.71	1,773.3	176.7	567.7	594.6	0.00	0.00	0.00
2,000.0	26.63	72.71	1,862.7	190.0	610.5	639.4	0.00	0.00	0.00
2,100.0	26.63	72.71	1,952.1	203.3	653.3	684.2	0.00	0.00	0.00
2,200.0	26.63	72.71	2,041.5	216.6	696.1	729.0	0.00	0.00	0.00
2,300.0	26.63	72.71	2,130.9	230.0	738.9	773.8	0.00	0.00	0.00
2,400.0	26.63	72.71	2,220.3	243.3	781.7	818.6	0.00	0.00	0.00
2,500.0	26.63	72.71	2,309.7	256.6	824.5	863.5	0.00	0.00	0.00
2,600.0	26.63	72.71	2,399.1	269.9	867.3	908.3	0.00	0.00	0.00
2,700.0	26.63	72.71	2,488.5	283.2	910.0	953.1	0.00	0.00	0.00
2,800.0	26.63	72.71	2,577.8	296.6	952.8	997.9	0.00	0.00	0.00
2,900.0	26.63	72.71	2,667.2	309.9	995.6	1,042.7	0.00	0.00	0.00
2,931.1	26.63	72.71	2,695.0	314.0	1,008.9	1,056.7	0.00	0.00	0.00
WF									
3,000.0	26.63	72.71	2,756.6	323.2	1,038.4	1,087.6	0.00	0.00	0.00
3,100.0	26.63	72.71	2,846.0	336.5	1,081.2	1,132.4	0.00	0.00	0.00
3,204.4	26.63	72.71	2,939.3	350.4	1,125.9	1,179.1	0.00	0.00	0.00
Start Drop -3.50									
3,300.0	23.28	72.71	3,026.0	362.4	1,164.4	1,219.5	3.50	-3.50	0.00
3,400.0	19.78	72.71	3,119.0	373.3	1,199.4	1,256.2	3.50	-3.50	0.00
3,500.0	16.28	72.71	3,214.1	382.5	1,229.0	1,287.1	3.50	-3.50	0.00
3,600.0	12.78	72.71	3,310.9	390.0	1,252.9	1,312.2	3.50	-3.50	0.00
3,700.0	9.28	72.71	3,409.0	395.6	1,271.2	1,331.3	3.50	-3.50	0.00
3,800.0	5.78	72.71	3,508.2	399.5	1,283.7	1,344.4	3.50	-3.50	0.00
3,900.0	2.28	72.71	3,607.9	401.6	1,290.4	1,351.5	3.50	-3.50	0.00
3,965.1	0.00	0.00	3,673.0	402.0	1,291.6	1,352.8	3.50	-3.50	0.00
Start 2222.0 hold at 3965.1 MD - Top of Gas									
4,000.0	0.00	0.00	3,707.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
4,100.0	0.00	0.00	3,807.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
4,200.0	0.00	0.00	3,907.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00

Payzone Directional

Planning Report



Database:	EDM 2003.21 Single User Db	Local Co-ordinate Reference:	Well BAT 33B-24-07-96
Company:	Ursa Operating Company, LLC	TVD Reference:	BAT 33B-24-07-96 @ 5197.9ft (Original Well Elev)
Project:	Rockies Region	MD Reference:	BAT 33B-24-07-96 @ 5197.9ft (Original Well Elev)
Site:	Speakman A	North Reference:	True
Well:	BAT 33B-24-07-96	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
4,300.0	0.00	0.00	4,007.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
4,400.0	0.00	0.00	4,107.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
4,500.0	0.00	0.00	4,207.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
4,600.0	0.00	0.00	4,307.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
4,700.0	0.00	0.00	4,407.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
4,800.0	0.00	0.00	4,507.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
4,900.0	0.00	0.00	4,607.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,000.0	0.00	0.00	4,707.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,100.0	0.00	0.00	4,807.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,200.0	0.00	0.00	4,907.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,300.0	0.00	0.00	5,007.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,366.1	0.00	0.00	5,074.0	402.0	1,291.6	1,352.8	0.00	0.00	0.00
Cameo									
5,400.0	0.00	0.00	5,107.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,500.0	0.00	0.00	5,207.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,600.0	0.00	0.00	5,307.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,700.0	0.00	0.00	5,407.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,800.0	0.00	0.00	5,507.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
5,887.1	0.00	0.00	5,595.0	402.0	1,291.6	1,352.8	0.00	0.00	0.00
Rollins									
5,900.0	0.00	0.00	5,607.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
6,000.0	0.00	0.00	5,707.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
6,100.0	0.00	0.00	5,807.9	402.0	1,291.6	1,352.8	0.00	0.00	0.00
6,187.1	0.00	0.00	5,895.0	402.0	1,291.6	1,352.8	0.00	0.00	0.00
TD at 6187.1									

Formations

Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)
2,931.1	2,695.0	WF		0.00	
3,965.1	3,673.0	Top of Gas		0.00	
5,366.1	5,074.0	Cameo		0.00	
5,887.1	5,595.0	Rollins		0.00	

Plan Annotations

Measured Depth (ft)	Vertical Depth (ft)	Local Coordinates		Comment
		+N/-S (ft)	+E/-W (ft)	
200.0	200.0	0.0	0.0	Start Build 3.50
960.8	933.7	51.6	165.8	Start 2243.6 hold at 960.8 MD
3,204.4	2,939.3	350.4	1,125.9	Start Drop -3.50
3,965.1	3,673.0	402.0	1,291.6	Start 2222.0 hold at 3965.1 MD
6,187.1	5,895.0	402.0	1,291.6	TD at 6187.1



Well Name: BAT 33B-24-07-96
Surface Location: Speakman A
North American Datum 1983 , US State Plane 1983 , Colorado Central Zone
Ground Elevation: 5182.5
+N/-S +E/-W Northing Easting Latitude Longitude Slot
0.0 0.0 484144.29 693967.81 39° 25' 15.360 N 108° 3' 37.266 W
Original Well Elev BAT 33B-24-07-96 @ 5197.9ft (Original Well Elev)



Azimuths to True North
Magnetic North: 10.08°
Magnetic Field
Strength: 52046.8snT
Dip Angle: 65.63°
Date: 6/13/2013
Model: IGRF200510

Speakman A
BAT 33B-24-07-96
Design #1
16:30, June 13 2013

WELLBORE TARGET DETAILS (MAP CO-ORDINATES AND LAT/LONG)

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape
BAT 33B-24-07-96 TGT	3673.0	402.0	1291.6	484255.68	694364.80	39° 25' 19.333 N	108° 3' 20.806 W	Point
BAT 33B-24-07-96 BHL	5895.0	402.0	1291.6	484255.68	694364.80	39° 25' 19.333 N	108° 3' 20.806 W	Point

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	200.0	0.00	0.00	200.0	0.0	0.0	0.00	0.00	0.0	
3	960.8	26.63	72.71	933.7	51.6	165.8	3.50	72.71	173.6	
4	3204.4	26.63	72.71	2939.3	350.4	1125.9	0.00	0.00	1179.1	
5	3965.1	0.00	0.00	3673.0	402.0	1291.6	3.50	180.00	1352.8	BAT 33B-24-07-96 TGT
6	6187.1	0.00	0.00	5895.0	402.0	1291.6	0.00	0.00	1352.8	BAT 33B-24-07-96 BHL

ANNOTATIONS

TVD	MD	Annotation
200.0	200.0	Start Build 3.50
933.7	960.8	Start 2243.6 hold at 960.8 MD
2939.3	3204.4	Start Drop -3.50
3673.0	3965.1	Start 2222.0 hold at 3965.1 MD
5895.0	6187.1	TD at 6187.1

FORMATION TOP DETAILS

TVDP	MDP	Path	Formation
2695.0	2931.1	WF	WF
3673.0	3965.1		Top of Gas
5074.0	5366.1		Cameo
5595.0	5887.1		Rollins

