

# Well 25AV-06

Original Hole, 6/21/2013 5:04:11 PM

MD (ftKB)	TVD (ftKB)	Incl (°)	DLS	Vertical schematic (actual)	Formations - Final
-5.9	-5.9	0.0	DLS (*M... 0 5		
24.9	24.9	0.1		1-2; Tubing Hanger; 7 1/16; 2,000; 25-26; 0.80	
26.9	26.9	0.1		3-1; CASING HANGER; 4 1/2; 4,000; 25-27; 1.86	
29.2	29.2	0.1		2-1; Hanger; 8 5/8; 8,097; 25-28; 2.50	
1,328.7	1,266.3	30.4		3-2; PUP JT; 4 1/2; 4,000; 27-29; 2.46	
1,372.0	1,303.7	30.4		1-1; Casing Joints; 16; 15,250; 25-85; 60.00	
1,388.1	1,317.6	30.4		2-2; Casing Jt; 8 5/8; 8,097; 28-1,329; 1,301.13	
4,104.0	3,660.0	30.4		2-3; Float Collar; 8 5/8; 8,097; 1,329-1,330; 1.00	
4,361.5	3,882.2	30.4		2-4; Casing Jt (Shoe Jt); 8 5/8; 8,097; 1,330-1,372; 42.37	
4,999.0	4,432.0	30.4		2-5; Down Jet Guide Shoe; 8 5/8; 8,097; 1,372-1,373; 0.69	
5,130.2	4,545.2	30.4		3-3; CASING JT; 4 1/2; 4,000; 29-4,082; 4,052.99	
5,237.2	4,637.4	30.4		1-3; Tubing; 2 3/8; 1.995; 26-5,955; 5,929.31	
5,399.9	4,777.8	30.4		3-4; MARKER JT; 4 1/2; 4,000; 4,082-4,104; 21.73	
5,667.0	5,008.1	30.4		3-5; CASING JT; 4 1/2; 4,000; 4,104-4,319; 214.57	
5,955.1	5,256.6	30.4		3-6; CASING JT; 4 1/2; 4,000; 4,319-4,361; 42.79	
5,979.0	5,277.2	30.4		3-7; CASING JT; 4 1/2; 4,000; 4,361-5,130; 768.70	
5,989.2	5,286.0	30.4		Perforated; 4,804-4,999; 8/8/2009	
5,996.1	5,292.0	30.4		3-8; MARKER JT; 4 1/2; 4,000; 5,130-5,152; 21.73	
6,216.9	5,482.4	30.4		3-9; CASING JT; 4 1/2; 4,000; 5,152-5,237; 85.39	
6,471.1	5,701.7	30.4		Perforated; 5,112-5,400; 8/8/2009	
6,568.9	5,786.0	30.4		3-10; CASING JT; 4 1/2; 4,000; 5,237-5,280; 42.83	
6,687.0	5,887.9	30.4		Perforated; 5,446-5,667; 8/8/2009	
6,688.3	5,889.0	30.4		Perforated; 5,716-5,979; 8/7/2009	
6,727.4	5,922.7	30.4		1-4; X Nipple; 2 3/8; 1.875; 5,955-5,956; 1.18	
6,759.8	5,950.7	30.4		1-5; Tubing; 2 3/8; 1.995; 5,956-5,988; 31.57	
				3-11; CASING JT; 4 1/2; 4,000; 5,280-6,688; 1,408.11	
				1-6; XN Nipple; 2 3/8; 1.791; 5,988-5,989; 1.26	
				1-7; Tubing Pup Joint; 2 3/8; 1.995; 5,989-5,995; 6.10	
				1-8; Bit-sub Housing; 3 5/16; 2,000; 5,995-5,996; 0.80	
				Perforated; 6,010-6,217; 8/7/2009	
				Perforated; 6,274-6,471; 8/6/2009	
				3-12; FLOAT COLLAR; 4 1/2; 4,000; 6,688-6,689; 1.00	
				3-13; CASING JT (SHOE JT); 4 1/2; 4,000; 6,689-6,728; 38.33	
				3-14; DOWN JET GUIDE SHOE; 4 1/2; 4,000; 6,728-6,729; 1.00	