



Calculation Results

Formation Name: Bakken and Three Forks
Formation Depth: 10,000 ft (TVD) Feet

Drilling Parameters

Drilling Fluid Type	Oil Based Mud	
Fluid Density (MW)	10	PPG
Pressure Gradient	0.52	PSI/ft
Equivalent Circulating Density	10.4	PPG

Casing Points

Casing Point 1	9,000	ft (TVD)
Casing Point 2	10,000	ft (TVD)

Mud Weights

Initial Mud Weight	10	PPG
Maximum Allowable Density	10.4	PPG

Kick Data

Kick Intensity	0.4	PPG
Pressure at Control Point	5,200	PSI

Model: Gilbert - adjusted for 10,000 ft (TVD) Bakken

Pump 1

	Liner ID	Rod OD	Stroke	SPM	Pump Rate
	in	in	in		GPM
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000

Pump 2

	Liner ID	Rod OD	Stroke	SPM	Pump Rate
	in	in	in		GPM
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000

Model: Gilbert - adjusted for 10,000 ft (TVD) Bakken

Pump 1

	Liner ID	Rod OD	Stroke	SPM	Pump Rate
	in	in	in		GPM
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000

Pump 2

	Liner ID	Rod OD	Stroke	SPM	Pump Rate
	in	in	in		GPM
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000

Model: Gilbert - adjusted for 10,000 ft (TVD) Bakken

Pump 1

	Liner ID	Rod OD	Stroke	SPM	Pump Rate
	in	in	in		GPM
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000

Pump 2

	Liner ID	Rod OD	Stroke	SPM	Pump Rate
	in	in	in		GPM
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000

Model: Gilbert - adjusted for 10,000 ft (TVD) Bakken

Pump 1

	Liner ID	Rod OD	Stroke	SPM	Pump Rate
	in	in	in		GPM
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000

Pump 2

	Liner ID	Rod OD	Stroke	SPM	Pump Rate
	in	in	in		GPM
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000
Max	6.500	3.500	12.000	120.000	1,000.000
Min	5.000	2.000	8.000	80.000	500.000

Pump Output Calculation Results

Pump Output	0.0700	BBL/stk
Pump Output	2.940	GAL/stk
Pump Output	0.420	BBL/min
Pump Output	17.640	GAL/min