

Schlumberger

Company: CHEVRON U.S.A. INC.
Well: 1 (SEC. 36-T10S-R18E)
Field: WILDCAT
County: UINTAH
State: UTAH

Other Services: DSI/PEX/HNGS/AMS

Permanent Datum: GROUND LEVEL
Elevation: 5,000 ft
Log Measured From: KELLY BUSHING, 16 ft above Permanent Datum
Drilling Measured From: KELLY BUSHING

Date: 10-Jun-08
Run Number: ONE
Depth Driller: 12,000 ft
Schlumberger Depth: 12,000 ft
Bottom Log Interval: 11,998 ft
Top Log Interval: 1,000 ft
Casing Driller Size @ Depth: 9.625 in @ 1,000 ft
Casing Schlumberger: 1,000 ft
Bit Size: 8.5 in

Type Fluid in Hole: WBM
Density: 9.6 lbm/gal
Viscosity: 40 s
Fluid Loss: 8.4 cc
Source of Sample: FLOWLINE
Rm @ Meas Temp: 0.8 @ 70 degF
Rmf @ Meas Temp: 0.6 @ 70 degF
Rmc @ Meas Temp: 1.1 @ 70 degF
Source Rmf / Rmc: MEASURED / CALCULATED
Rm @ BHT: 0.5 @ 180 degF
Time Since Circulation: 12 hr
Time on Bottom: 10-Jun-08 08:00
Maximum Recorded Temperature: 180 degF
Equipment / Base: 11556 / 11556
Recorded By: J. SEBRING
Witnessed By: J. MCCARTHY

Tool Type / Serial No. / Position / Weight / Length
DSI-H / 3913 / 1 / 1,000 lbm / 50 ft
PEX-HRLA-AMS / 3913 / 2 / 1,000 lbm / 50 ft
HNGS / 3913 / 3 / 1,000 lbm / 50 ft

Top Log Interval: 1,000 ft
Bottom Log Interval: 11,998 ft
Logging Speed: 1,800 ft/hr

Tool Standoff: 0.5 in
Tool Standoff: 0.5 in
Tool Standoff: 0.5 in