Tension - Cable
Tension - Head
Speed
Gamma Ray
Gamma Ray
Gamma Ray
Neutron Porosity
Neutron Porosity
Neutron Porosity
Density
Density
Density
Caliper
Caliper
Caliper
Resistivity
Resistivity
Resistivity

Background Reading:	0.0	cps
Calibrator Reading:	85.8	cps
Sensitivity:	1.0000	GAPI/cps

Cement Bond Log Calibration Report

Serial Number:	5.5dig040201	
Tool Model:	Probe275Digital	
Performed:	Mon Jul 08 13:59:53 2013	
Depth:	2762.31	ft
Casing Diameter:	5.5	in

	3' Spacing	5' Spacing	
Signal Zero:	0.25	0	mV
Calibrated Amplitude:	71.921	71.921	mV
Reading at Signal Zero:	0.00175781	0.00598145	V
Reading in Free Pipe:	2.26162	2.15364	V
Gain:	31.7148	33.4881	
Offset:	0.194251	-0.200307	

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			CENT-TITAN (1) SHORT CENTRALIZER	2.17	1.88	0.50
			CHD-None (1)	1.20	1.38	5.00
WVF3	10.88		CBL-Probe275Digital (5.5dig040201) Digital 3' 5' CBL Move voltage to +/- 150 for cal mode	8.75	2.75	92.00
WVF5	9.88					
CCL	5.79		CCL-PROBE (CCL061120) PROBECCL	1.42	2.75	5.00
			GR-PROBE (061120GR) 2 3/4"gamma ray probe	3.04	2.75	10.00
GR	3.06					
			CENT-TITAN (SHORT) SHORT CENTRALIZER	2.17	1.88	0.50

Dataset:	harley#4.db: field/well/run1/pass1
Total Length:	18.74 ft
Total Weight:	113.00 lb
O.D.	2.75 in