
Schlumberger
Platform Express
Three Detector Lithology Density
Compensated Neutron
Array Induction Imager Tool
Gamma Ray
Caliper
Run 1
Run 2
Run 3
Logging Date
Operating Rig Time
Depth Driller
Depth Logger
Bottom Logged Interval
Top Log Interval
Casing Driller
Casing Logger
Bit Size
Type Fluid in Hole
Density
Viscosity
pH
Fluid Loss
Source of Sample
Rm @ Meas Temp
Rmf @ Meas Temp
Rmc @ Meas Temp
Source of Rmf and Rmc
Rm @ BHT
Time Since Circulation
Max Recorded Temp
Equipment Number
Location
Recorded By
Witnessed By
Schlumberger
Anadarko Petroleum Corporation
Chalkley 1-25
Section 25 Township 6N Range 26W
Cimarron County
Oklahoma
Other Services
Remarks
Engineer's Remarks
Run 1 Run 2 Run 3
Run 1 Run 2 Run 3
Run 1 Run 2 Run 3




## Calibration Report

Database File: mastate.db
Dataset Pathname: 2/run1/pass3.1
Dataset Creation: Tue Jun 11 08:45:05 2013

### Gamma Ray Calibration Report

| | | |
|---|---|---|
| Serial Number: | 061120GR | |
| Tool Model: | PROBE | |
| Performed: | Tue Jun 11 07:13:44 2013 | |
| Calibrator Value: | 1.0 | GAPI |
| Background Reading: | 0.0 | cps |
| Calibrator Reading: | 85.8 | cps |
| Sensitivity: | 0.8000 | GAPI/cps |

### Segmented Cement Bond Log Calibration Report

| | | |
|---|---|---|
| Serial Number: | 4.5040904 | |
| Tool Model: | Probe | |
| Calibration Casing Diameter: | 5.500 | in |
| Calibration Depth: | 5215.708 | ft |

Master Calibration, performed Tue Jun 11 07:01:30 2013:

| | Raw (v) | | Calibrated (mv) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | Cal | Zero | Cal | Gain | Offset |
| 3' | 0.014 | 1.514 | 0.250 | 71.921 | 47.795 | -0.417 |
| CAL | 1.762 | 1.732 | | | | |
| 5' | 0.015 | 1.434 | 0.250 | 71.921 | 50.510 | -0.493 |
| SUM | | | | | | |
| S1 | 0.013 | 1.504 | 0.250 | 100.000 | 66.892 | -0.592 |
| S2 | 0.014 | 1.472 | 0.250 | 100.000 | 68.434 | -0.729 |
| S3 | 0.015 | 1.486 | 0.250 | 100.000 | 67.802 | -0.784 |
| S4 | 0.014 | 1.508 | 0.250 | 100.000 | 66.781 | -0.708 |
| S5 | 0.014 | 1.513 | 0.250 | 100.000 | 66.565 | -0.691 |
| S6 | 0.015 | 1.513 | 0.250 | 100.000 | 66.582 | -0.754 |
| S7 | 0.015 | 1.529 | 0.250 | 100.000 | 65.845 | -0.706 |
| S8 | 0.014 | 1.523 | 0.250 | 100.000 | 66.135 | -0.694 |

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969:

| | Raw (v) | | Calibrated (v) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | Cal | Zero | Cal | Gain | Offset |
| CAL | 0.000 | 0.000 | 1.762 | 1.732 | 1.000 | 0.000 |

Air Zero Calibration, performed Tue Jun 11 06:47:28 2013:

| | Raw (v) | Calibrated (v) | Results |
|---|---|---|---|
| | Zero | Zero | Offset |
| 3' | 0.000 | 0.000 | 0.000 |
| 5' | 0.000 | 0.000 | 0.000 |
| SUM | | | |
| S1 | 0.000 | 0.000 | 0.000 |
| S2 | 0.000 | 0.000 | 0.000 |
| S3 | 0.000 | 0.000 | 0.000 |
| S4 | 0.000 | 0.000 | 0.000 |
| S5 | 0.000 | 0.000 | 0.000 |
| S6 | 0.000 | 0.000 | 0.000 |
| S7 | 0.000 | 0.000 | 0.000 |
| S8 | 0.000 | 0.000 | 0.000 |