

FORM
5A

Rev
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400468659

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 16700

2. Name of Operator: CHEVRON USA INC

3. Address: 6001 BOLLINGER CANYON RD

City: SAN RAMON State: CA Zip: 94583

4. Contact Name: Julie Justus

Phone: (970) 257-6042

Fax: (970) 245-6489

5. API Number 05-045-15256-00

7. Well Name: SKR

8. Location: QtrQtr: NENW Section: 25 Township: 5S Range: 98W Meridian: 6

9. Field Name: SKINNER RIDGE Field Code: 77548

6. County: GARFIELD

Well Number: 598-25-AV-16

Completed Interval

FORMATION: WILLIAMS FORK Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 07/28/2013 End Date: 07/29/2013 Date of First Production this formation: 08/06/2009

Perforations Top: 4182 Bottom: 4714 No. Holes: 57 Hole size: 35/100

Provide a brief summary of the formation treatment: Open Hole: ☐

Pumped 374,892 gallons of treated produced water with 218,000 lbs of sand.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 8926 Max pressure during treatment (psi): 6396

Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.43

Type of gas used in treatment: Min frac gradient (psi/ft): 0.75

Total acid used in treatment (bbl): 0 Number of staged intervals: 2

Recycled water used in treatment (bbl): 8926 Flowback volume recovered (bbl): 7295

Fresh water used in treatment (bbl): 0 Disposition method for flowback: RECYCLE

Total proppant used (lbs): 218000 Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 08/12/2013 Hours: 22 Bbl oil: 0 Mcf Gas: 426 Bbl H2O: 616

Calculated 24 hour rate: Bbl oil: 0 Mcf Gas: 465 Bbl H2O: 672 GOR: 0

Test Method: Flowtest Casing PSI: 120 Tubing PSI: 1000 Choke Size: 48

Gas Disposition: FLARED Gas Type: DRY Btu Gas: 1068 API Gravity Oil: 0

Tubing Size: 2 + 7/8 Tubing Setting Depth: 5922 Tbg setting date: 08/07/2013 Packer Depth:

Reason for Non-Production: Not on continuous production: well is being vented/flared/shut-in to unload water head from re-complete.

Date formation Abandoned: Squeeze: ☐ Yes ☒ No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Julie Justus

Title: Regulatory Specialist Date: Email: jjustus@chevron.com

Attachment Check List

Att Doc Num	Name
400468677	WELLBORE DIAGRAM
400474621	COMPLETED INTERVAL REPORT
400474622	COMPLETED INTERVAL REPORT

Total Attach: 3 Files

General Comments

User Group

Comment

Comment Date

--	--	--

Total: 0 comment(s)