

All interpretations, or opinions based on inferences from electrical or other measurements and no warranty as to the accuracy or correctness of any interpretation is made or implied. In consideration of the furnishing of this information, the undersigned agrees that neither Nabors Completion & Production Services Co. nor any of its officers or employees shall be responsible for any loss, cost, damage or expense arising in connection with the use of or reliance on any interpretation. These interpretations are also subject to our general terms and conditions set out in our current price schedule.

Comments

THANK YOU FOR CHOOSING NCPS!!
LOG NOT CORRELATED
MCR BLS & RCR BL & LL @ WHTD

Database File: 20-NOV-15 01:28 JB
Dataset Pathname: Gamma Ray 10 LAS
Presented Along: Measured Depth
Created by: Depth 0 Point: 0.0000 (7.4000)

Gamma Ray (GR) (API) 0 150
Caliper (CALI) (in) 6 16
Deep Resistivity (RILD) (ohm.m) 0.2 2000
Medium Resistivity (RILM) (ohm.m) 0.2 2000
Shallow Resistivity (RILS) (ohm.m) 0.2 2000
Spontaneous Potential (SP) (mV) -160 40
Cable Speed (CS) (ft/min) -5000 5000
Tension (TENS) (lbs) 0 10000
Casing Collar Locator (CCL) -1 1
Depth (MD) (ft) 0 7400
Depth (TVD) (ft) 0 7400

Gamma Ray (GR) (API) 0 150
Caliper (CALI) (in) 6 16
Deep Resistivity (RILD) (ohm.m) 0.2 2000
Medium Resistivity (RILM) (ohm.m) 0.2 2000
Shallow Resistivity (RILS) (ohm.m) 0.2 2000
Spontaneous Potential (SP) (mV) -160 40
Cable Speed (CS) (ft/min) -5000 5000
Tension (TENS) (lbs) 0 10000
Casing Collar Locator (CCL) -1 1
Depth (MD) (ft) 0 7400
Depth (TVD) (ft) 0 7400

Database File: 20-NOV-15 01:28 JB
Dataset Pathname: Gamma Ray 10 LAS
Presented Along: Measured Depth
Created by: Depth 0 Point: 0.0000 (7.4000)

Gamma Ray (GR) (API) 0 150
Caliper (CALI) (in) 6 16
Deep Resistivity (RILD) (ohm.m) 0.2 2000
Medium Resistivity (RILM) (ohm.m) 0.2 2000
Shallow Resistivity (RILS) (ohm.m) 0.2 2000
Spontaneous Potential (SP) (mV) -160 40
Cable Speed (CS) (ft/min) -5000 5000
Tension (TENS) (lbs) 0 10000
Casing Collar Locator (CCL) -1 1
Depth (MD) (ft) 0 7400
Depth (TVD) (ft) 0 7400

Calibration Report

Service Rep: Calibration Report

Tuner: Genie2 Probe2 Pulsar 103015

Run Log 20-NOV-15 22:56

SHOP CALIBRATION

	Counts/Sec	Gain	Offset	Alg	Units
Background	0.0				cps
Calibrator	0.0				cps/Counts
		0.4720			

PRIMARY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	cps%

SECOND (LIKE-BY) VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	cps%

AFTER (LIKE-BY) VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	cps%

Calibrated Bore Log Calibrations Report

Logging Company	NABORS		
Truck Number	Probe2 Pulsar		
Run Number	Run 1 on 20-NOV-15 22:56:01		
Depth Reference	KB		
Casing	7.00 lb	ft	
Casing Diameter	6.276	in	
	X Spacing	Y Spacing	
Sensor Offset	0.0	0.0	in
Calibration Inaddhole	21.1243	21.1243	API
Calibration Inaddhole Pass	21.1243	21.1243	API
	4.8720	4.8720	
Gain	21.1243	21.1243	
Offset	4.8720	4.8720	