Comments

Pioneer volume calculated for 4 1/2" casing.
Hole size 6.125 in.
Thank you for using Pioneer Energy Services!

DENSITY DATA SUSPECT


PIONEER
MAIN PASS
Company: Rockville Exploration & Prod. LLC
Well: Pioneer Fed. 1
Field: Wildcat
County: Nye
State: Nevada
Date: 2024-11-20
Run: 1
Service Order: 0
Depth Datum: KB
Log Measured From: KB
Permanent Datum: Ground Level
Elevation: 4,812 ft
Drilling Measured From: KB
API Number: 32-023-00000
Location: Sec 14, T12S, R58E
Latitude: 37.9412
Longitude: -116.2187
Run Number: 1
Depth Driller: 8,000 ft
Depth Logger: 8,000 ft
Bottom Log Interval: 8,000 ft
Top Log Interval: 0 ft
Casing Driller: 13.375 in @ 1,200 ft
Casing Logger: 13.375 in @ 1,200 ft
Bit Size: 12.25 in
Type Fluid in Hole: Water-based mud
Density: 9.2 ppg
Viscosity: 48 s/qt
PH: 9.5
Fluid Loss: 6.4 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.21 @ 72 °F
Rmf @ Measured Temp: 0.18 @ 72 °F
Rmc @ Measured Temp: 0.27 @ 72 °F
Source of Rmf and Rmc: Measured
Rm @ BHT: 0.12 @ 168 °F
Time Circulation Stopped: 04:30
Time Logger on Bottom: 06:15
Maximum Recorded Temperature: 168 °F
Equipment Number: PIO-LOG-07
Location: Tonopah, NV
Recorded By: M. Ellsworth
Witnessed By: J. Carrasco
Gamma Ray (GR) 0 150 API
Caliper (CAL) 6 16 in
Bit Size 6 16 in
Deep Resistivity (LLD) 0.2 2000 ohm-m
Shallow Resistivity (LLS) 0.2 2000 ohm-m
Neutron Porosity (NPHI) 45 -15 %
Bulk Density (RHOB) 1.95 2.95 g/cm³
Gamma Ray (GR) 0 150 API
Neutron Porosity (NPHI) 45 -15 %
Bulk Density (RHOB) 1.95 2.95 g/cm³