
Schlumberger
Platform Express
Three Detector Lithology Density
Compensated Neutron
Array Induction Imager Tool
Gamma Ray
Caliper
Bit Size
Density Correction
Photoelectric Factor
Neutron Porosity
Bulk Density
Delta Rho
Gamma Ray
Caliper
Bit Size
Deep Resistivity
Medium Resistivity
Shallow Resistivity
Spherically Focused Resistivity
Rt
Rxo
Rm
Rmf
Rmc
Mud Type
Mud Density
Mud Viscosity
Mud Resistivity
Mud Filtrate Resistivity
Mud Cake Resistivity
Source of Sample
Rm @ Measured Temperature
Rmf @ Measured Temperature
Rmc @ Measured Temperature
Rm @ BHT
Rmf @ BHT
Rmc @ BHT
Time Since Circulation
Max Recorded Temperature
Equipment Number
Location
Recorded By
Witnessed By
Run Number
Depth Driller
Depth Logger
Bottom Logged Interval
Top Logged Interval
Casing Driller Size @ Depth
Casing Logger Size @ Depth
Bit Size
Type Fluid in Hole
Density
Viscosity
PH
Fluid Loss



PEAK WIRELINE SERVICES, INC.

REPEAT SECTION

Database File: evan2.db
Dataset Pathname: pass1
Presentation Format: cbldig
Dataset Creation: Thu Sep 26 08:47:19 2013 by Log Std Casedhole 10071
Charted by: Depth in Feet scaled 1:240



Calibration Report

Database File: evan2.db
Dataset Pathname: pass2.1
Dataset Creation: Thu Sep 26 09:38:05 2013

Gamma Ray Calibration Report

Serial Number:	061120GR	
Tool Model:	PROBE	
Performed:	Fri Aug 09 11:38:03 2013	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Cement Bond Log Calibration Report

Serial Number:	5.5dig040201		
Tool Model:	Probe275Digital		
Performed:	Thu Sep 26 08:42:46 2013		
Depth:	3745.9	ft	
Casing Diameter:	5.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	0.25	0	mV
Calibrated Amplitude:	71.921	71.921	mV
Reading at Signal Zero:	0.0105225	0.0152588	V
Reading in Free Pipe:	2.03381	1.96504	V
Gain:	35.423	36.8867	
Offset:	-0.122737	-0.562847	