Company	Swift Energy Operating
Well	Wales 34-12-32H1S
Field	Wildcat
County	La Paloma
State	Colorado
Location	API No. 05-123-34719 1200' FNL & 1200' FWL Sec 12 T32S R67W 6th PM
Elevation	KB 7,083 ft GL 7,058 ft
Permanent Datum	Mean Sea Level
Log Measured From	KB, 25 ft above Permanent Datum
Drilling Measured From	KB
Date	08-Oct-13
Run Number	ONE
Depth Driller	10,253 ft
Depth Logger	10,253 ft
Bottom Logged Interval	10,253 ft
Top Logged Interval	9,900 ft
Casing Driller	9.625 in @ 1,570 ft
Casing Logger	1,570 ft
Bit Size	8.75 in
Type Fluid in Hole	Water Based Mud
Density	9.2 ppg
Viscosity	40 s
Fluid Loss	4.8 cc
Source of Sample	Flowline
Rm @ Measured Temp	0.07 @ 70 °F
Rmf @ Measured Temp	0.06 @ 70 °F
Rmc @ Measured Temp	0.09 @ 70 °F
Source of Rmf and Rmc	Measured
Rm @ BHT	0.04 @ 180 °F
Time Since Circulation	12 hours
Max Recorded Temp	180 °F
Equipment Number	3
Location	Greeley
Recorded By	Jeff Hall
Witnessed By	Jeff Hall

BASIN LOGGING
Basin Logging & Perforating, LLC
Greeley, Colorado

COMPANY SWIFT ENERGY OPERATING
WELL WALES 34-12-32H1S
FIELD WILDCAT
COUNTY LA PALOMA
STATE COLORADO

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except to the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions as set out in our current Price Schedule.

Comments

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			PTS2275	2.83	2.75	
Headsub	10.33					
WSF3	12.50		CBL Digital (Dig2275)	9.17	2.75	100.00
WSF5	11.58					
CCL	7.00		GR-Probe (2767) Probe 2.75 1/8 barrel Rear	4.50	2.75	30.00
GR	5.83					
			PTS2275	2.83	2.75	

Dataset: wales34-12-32#1H.db: fieldheirlum1(pass6)
Total Length: 10.5 ft
Total Weight: 130.00 lb
O.D.: 2.75 in

Database File: wales34-12-32#1H.db
Dataset Pathname: pass6
Presentation Format: CBL
Dataset Creation: Tue 22 Oct 2013 08:04:45 (MST) by Calc: SCH 12012R
Charted by: Depth in Feet scaled 1:240

0	Gamma Ray (GAPI)	200	17376 1200	7713 (usec) 200 200 Variable Density 1200
WSF	Travel Time (usec)	WSF	26.25400	Amplitude (mV) 100
0	CCL	1	0	25 Amplified Amplitude (mV) 25

Calibration Report

Database File: wales34-12-32#1H.db
Dataset Pathname: pass6
Dataset Creation: Wed Sep 11 09:54:45 2013 by Calc: SCH 12012R

Gamma Ray Calibration Report

Serial Number	2767
Test Type	Probe
Performed	Fri Jul 27 11:06:10 2012
Calibrator Value	148.0 GAPI
Background Reading	0.0 cps
Calibrator Reading	150.0 cps
Sensitivity	1.2500 GAPI/cps

Cement Bond Log Calibration Report

Serial Number	Dig2275
Tool Model	Digital
Performed	Wed Sep 11 08:26:10 2013
Depth	44.7083 ft
Casing Diameter	4.5 in
T Spacing	3' Spacing

Digital Zero	0.25	0	mV
Calibrated Amplitude	12.2756	11.2756	mV
Reading at Digital Zero	0.0081268	0.0137451	V
Reading at max Sigs	0.11423	0.09082	V
Gain	23.023	21.5178	
Offset	0.0081271	0.0081268	

Database File: wales34-12-32#1H.db
Dataset Pathname: pass6
Presentation Format: CBL
Dataset Creation: Tue 22 Oct 2013 08:04:45 (MST) by Calc: SCH 12012R
Charted by: Depth in Feet scaled 1:240

0	Gamma Ray (GAPI)	200	17376 1200	7713 (usec) 200 200 Variable Density 1200
WSF	Travel Time (usec)	WSF	26.25400	Amplitude (mV) 100
0	CCL	1	0	25 Amplified Amplitude (mV) 25