

Company: ENCANA OIL & GAS (USA) INC

Well: HMU 6-13A (J6SEB)

Field: MAMM CREEK

County: GARFIELD

State: COLORADO

SLIM CEMENT MAPPING LOG
CBL-VDL
GAMMA RAY-CCL

County:	GARFIELD		
Field:	MAMM CREEK		
Location:	SHL: 1945 FSL & 1908 FEL		
Well:	HMU 6-13A (J6SEB)		
Company:	ENCANA OIL & GAS (USA) INC		
	LOCATION		
	SHL: 1945 FSL & 1908 FEL BHL: 1198 FSL & 745 FWL	Elev.: K.B. 7166.00 ft G.L. 7144.00 ft D.F. 7165.00 ft	
	Permanent Datum: _____ Log Measured From: _____ Drilling Measured From: _____	GROUND LEVEL _____ KELLY BUSHING _____ KELLY BUSHING _____	Elev.: 7144.00 ft _____ 22.00 ft above Perm. Datum
	API Serial No. _____ 05-045-21941-000C		Section 6 Township 8S Range 92W

Logging Date	25-Nov-2013		
Run Number	1		
Depth Driller	9010 ft		
Schlumberger Depth	8929 ft		
Bottom Log Interval	8920 ft		
Top Log Interval	70 ft		
Casing Fluid Type	FRESH WATER		
Salinity			
Density	8.4 lbm/gal		
Fluid Level	70 ft		
BIT/CASING/TUBING STRING			
Bit Size	7.875 in		
From	6312 ft		
To	9010 ft		
Casing/Tubing Size	4.500 in		
Weight	11.6 lbm/ft		
Grade	S-80		
From	22 ft		
To	8990 ft		
Maximum Recorded Temperatures	249 degF		
Logger On Bottom	25-Nov-2013	21:45	
Unit Number	391	GRAND JUNCTION	
Recorded By	KIRSTIE BUNTING		
Witnessed By	JIM DYKEMAN		

	Oil Density	Run 1	Run 2	Run 3
	Water Salinity			
	Gas Gravity			
PVT DATA	Bo			
	Bw			
	1/Bg			
	Bubble Point Pressure			
	Bubble Point Temperature			
	Solution GOR			
	Maximum Deviation			
	CEMENTING DATA			
	Primary/Squeeze	Primary		
	Casing String No			
	Lead Cement Type			
	Volume			
	Density			
	Water Loss			
	Additives			
	Tail Cement Type			
	Volume			
	Density			
	Water Loss			
	Additives			
	Expected Cement Top			
Logging Date				
Run Number				
Depth Driller				
Schlumberger Depth				
Bottom Log Interval				
Top Log Interval				
Casing Fluid Type				
Salinity				
Density				
Fluid Level				
BIT/CASING/TUBING STRING				
Bit Size				
From				
To				
Casing/Tubing Size				
Weight				
Grade				
From				
To				
Maximum Recorded Temperatures				
Logger On Bottom				
Unit Number				
Recorded By				
Witnessed By				

DEPTH SUMMARY LISTING

Date Created: 14-AUG-2013 11:54:57

Depth System Equipment

Depth Measuring Device		Tension Device		Logging Cable	
Type:	IDW-JB	Type:	CMTD-B/A	Type:	1-25ZT
Serial Number:	6349	Serial Number:	3421	Serial Number:	112136
Calibration Date:	7-31-2013	Calibration Date:	14-AUG-201	Length:	19000 FT
Calibrator Serial Number:		Calibrator Serial Number:	174878		
Calibration Cable Type:	1-25ZT	Number of Calibration Points:	10	Conveyance Method:	Wireline
Wheel Correction 1:	-5	Calibration RMS:	3	Rig Type:	LAND
Wheel Correction 2:	-4	Calibration Peak Error:	8		

Depth Control Parameters

Log Sequence:	First Log In the Well
Rig Up Length At Surface:	0.00 FT
Rig Up Length At Bottom:	0.00 FT
Rig Up Length Correction:	0.00 FT
Stretch Correction:	
Tool Zero Check At Surface:	

Depth Control Remarks

1. ALL SCHLUMBERGER DEPTH CONTROL PROCEDURES USED
2. IDW USED AS PRIMARY DEPTH REFERENCE
3. SPWT DRUM COUNTER USED AS SECONDARY DEPTH REFERENCE
- 4.
- 5.
- 6.

DISCLAIMER













THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.


OTHER SERVICES1	OTHER SERVICES2
OS1: RESERVOIR SATURATION	OS1:
OS2: LOG	OS2:
OS3: SIGMA MODE	OS3:
OS4:	OS4:
OS5:	OS5:
REMARKS: RUN NUMBER 1	REMARKS: RUN NUMBER 2
FIRST RUN IN HOLE CORRLEATED TO DOWN LOG	
TOOL RAN AS PER TOOL SKETCH	
ENTRANCE: 21:00	
TIME ON BOTTOM: 21:45	
EXIT: 00:00	

MAXIMUM RECORDED TEMPERATURE: 249 DEGF	
MAXIMUM RECORDED PRESSURE: 3702 PSIA	
SHORT JOINTS: 6833 FT & 7825 FT	
MAIN PASS LOGGED UNDER ZERO SURFACE PRESSURE	
EXPECTED CBL AMPLITUDE IN FREE PIPE IS 80MV	
CREW: KBUNTING, WAZIZ, KJOHNS, KBOZARTH	
THANK YOU FOR CHOOSING E&P WIRELINE, A SCHLUMBERGER COMPANY	

RUN 1 SERVICE ORDER #: PROGRAM VERSION: FLUID LEVEL:			RUN 2 SERVICE ORDER #: PROGRAM VERSION: FLUID LEVEL:		
LOGGED INTERVAL	START	STOP	LOGGED INTERVAL	START	STOP

	EQUIPMENT	DESCRIPTION	
RUN 1			RUN 2

SURFACE EQUIPMENT			
WITM-A			
PSC_16MHZ			
DOWNHOLE EQUIPMENT			
MH-22			53.4
MH-22			
Detail MT			
AH-38	TelStatus		51.8
	CTEM		
PSPT			51.5
PSC-A			
PSPT-B			
PSTC-A			
PBMS-B 928	GR		47.8
CQG_F_Mano			
RTD_Thermometer			
GR	Well_Temp		44.8
CCL	CQG Manom		44.5
PBMS	CCL		44.0
	PBMS PSTC		43.3
RST-C			43.3
RSCH-A			
RSC-E 374			
RSS-A 350			
RSXH-A			
RSX-E 220			
	RSC-A Far		34.2
	RSC-A PNG		
	RSC-A Nea		
	RSX-A PNG		33.7




Schlumberger


MAIN PASS CBL VDL


MAXIS Field Log


Company: ENCANA OIL & GAS (USA) INCWell: HMU 6-13A (J6SEB)


Input DLIS Files						
DEFAULT	Splice_SCMT_RST_PSP_053CUP	FN:1	PRODUCER	26-Nov-2013 00:39	8936.0 FT	9.5 FT
Output DLIS Files						
DEFAULT	SCMT_RST_PSP_054PUP	FN:51	PRODUCER	26-Nov-2013 00:41	8939.0 FT	-39.5 FT
OP System Version: 19C0-187						
SCMT-CB	SRPC-5214-H2-2012-OP1		RST-C	SRPC-5214-H2-2012-OP1		
PSPT	SRPC-5214-H2-2012-OP1					

































































































































OP System Version: 19C0-187

SCMT-CB	SRPC-5214-H2-2012-OP1!	RST-C	SRPC-5214-H2-2012-OP1!
PSPT	SRPC-5214-H2-2012-OP1!		

<<<SCMT Cement Evaluation Information Summary>>>

Sonde Serial Number	SCMS-CB 8303		
Current Casing Size	4.50000 IN		
Casing Weight	11.6000 LB/F		
Expected CBL Amplitude in Free Pipe Section	80 MV	Minimum Sonic Amplitude	0.579149 MV (100% Cement)
			1.55185 MV (80% Cement)
		MAP Minimum Sonic Amplitude	4.32284 MV (100% Cement)
			8.10244 MV (80% Cement)
Master Calibration (Normalization)	Before Calibration (Adjustment)		
Date of Master Calibration	19-NOV-2013		
CBL Correction Factor	0.0743678	CBL Adjustment Factor (CBAF)	1.0
MAP 1 Correction Factor	0.127925	MAP Adjustment Factor (MPAF)	1.0
MAP 2 Correction Factor	0.120622		
MAP 3 Correction Factor	0.153607		
MAP 4 Correction Factor	0.159414		
MAP 5 Correction Factor	0.164508		
MAP 6 Correction Factor	0.182220		
MAP 7 Correction Factor	0.190086		
MAP 8 Correction Factor	0.182177		

Parameters

DLIS Name	Description	Value	
SCMT-CB: Slim Cement Mapping Tool, 1-11/16 OD			
BILI	Bond Index Level for Zone Isolation	0.8	
CB3D	SCMT CBL 3 ft Peak Detection Mode	PEAK	
CB3G	SCMT CBL 3 ft Peak Detection T0_Delay and Noise Gate	224.559	US
CB3T	SCMT CBL 3 ft Fixed Threshold Level	20	MV
CB5D	SCMT CBL 5 ft Peak Detection Mode	PEAK	
CB5G	SCMT CBL 5 ft Peak Detection T0_Delay and Noise Gate	338.559	US
CB5T	SCMT CBL 5 ft Fixed Threshold Level	20	MV
CBLG	CBL Gate Width	45	US
CBRA	CBL LQC Reference Amplitude in Free Pipe	80	MV
CMCF	CBL Cement Type Compensation Factor	1	
CMTC	SCMT Slow Channel Multiplexer Mode	SCAN	
CMTM	SCMT Operating Mode	LOG	
CSCS	SCMT Slow Channel Index	VCC	
CTHI	Casing Thickness	0.255617	IN
DTF	Delta-T Fluid	189	US/F
FATT	Acoustic Attenuation due to Fluid	0	DB/F
FCF	CBL Fluid Compensation Factor	0.924277	
GOBO	Good Bond	1.55185	MV
MAPD	SCMT MAP Peak Detection Mode	PEAK	
MAPG	SCMT MAP Peak Detection T0_Delay and Noise Gate	167.559	US
MAPT	SCMT MAP Fixed Threshold Level	30	MV
MATT	Maximum Attenuation	16.5449	DB/F
MCCF	MAP Cement Type Compensation Factor	1	
MCI	Minimum Cemented Interval for Isolation	1.25	FT
MMSA	MAP Minimum Sonic Amplitude	4.32284	MV
MSA	Minimum Sonic Amplitude	0.579149	MV
PEDE	Peak Detection On/Off Switch in Playback	OFF	
VDLG	VDL Manual Gain	5	
ZCMT	Acoustic Impedance of Cement	6.8	MRAY
System and Miscellaneous			
CSIZ	Current Casing Size	4.500	IN
CWEI	Casing Weight	11.60	LB/F
DFD	Drilling Fluid Density	8.40	LB/G
DO	Depth Offset for Playback	3.0	FT
PP	Playback Processing	RECOMPUTE	
TD	Total Depth	8929	FT

Input DLIS Files

DEFAULT Splice_SCMT_RST_PSP_053CUP FN:1 PRODUCER 26-Nov-2013 00:39 8936.0 FT 9.5 FT

Output DLIS Files

DEFAULT SCMT_RST_PSP_054PUP FN:51 PRODUCER 26-Nov-2013 00:41

Schlumberger

REPEAT ANALYSIS CBL VDL

MAXIS Field Log

Company: ENCANA OIL & GAS (USA) INC Well: HMU 6-13A (J6SEB)

Input DLIS Files

DEFAULT SCMT_RST_PSP_045LUP FN:43 PRODUCER 25-Nov-2013 21:31 6953.5 FT 6646.5 FT
 DEFAULT SCMT_RST_PSP_054PUP FN:51 PRODUCER 26-Nov-2013 00:41 8939.0 FT -39.5 FT

Output DLIS Files


DEFAULT SCMT_RST_PSP_055PUP FN:52 PRODUCER 26-Nov-2013 00:47 6956.5 FT 6597.5 FT


OP System Version: 19C0-187



SCMT-CB SRPC-5214-H2-2012-OP1 RST-C SRPC-5214-H2-2012-OP1
 PSPT SRPC-5214-H2-2012-OP1

PIP SUMMARY

Time Mark Every 60 S







PIP SUMMARY

Time Mark Every 60 S
Format: CBL_VDL_REP Vertical Scale: 5" per 100' Graphics File Created: 26-Nov-2013 00:47

OP System Version: 19C0-187

SCMT-CB PSPT	SRPC-5214-H2-2012-OP1 SRPC-5214-H2-2012-OP1	RST-C	SRPC-5214-H2-2012-OP1
-----------------	--	-------	-----------------------

<<<SCMT Cement Evaluation Information Summary>>>

Sonde Serial Number	SCMS-CB 8303		
Current Casing Size	4.50000 IN		
Casing Weight	11.6000 LB/F		
Expected CBL Amplitude in Free Pipe Section	80 MV	Minimum Sonic Amplitude	0.579149 MV (100% Cement) 1.55185 MV (80% Cement)
		MAP Minimum Sonic Amplitude	4.32284 MV (100% Cement) 8.10244 MV (80% Cement)
Master Calibration (Normalization)	Before Calibration (Adjustment)		
Date of Master Calibration	19-NOV-2013		
CBL Correction Factor	0.0743678	CBL Adjustment Factor (CBAF)	1.0
MAP 1 Correction Factor	0.127925	MAP Adjustment Factor (MPAF)	1.0
MAP 2 Correction Factor	0.120622		
MAP 3 Correction Factor	0.153607		

MAP 3 Correction Factor	0.159414
MAP 4 Correction Factor	0.164508
MAP 5 Correction Factor	0.182220
MAP 6 Correction Factor	0.190086
MAP 7 Correction Factor	0.182177

Parameters

DLIS Name	Description	Value	
SCMT-CB: Slim Cement Mapping Tool, 1-11/16 OD			
BILI	Bond Index Level for Zone Isolation	0.8	
CB3D	SCMT CBL 3 ft Peak Detection Mode	PEAK	
CB3G	SCMT CBL 3 ft Peak Detection T0_Delay and Noise Gate	224.559	US
CB3T	SCMT CBL 3 ft Fixed Threshold Level	20	MV
CB5D	SCMT CBL 5 ft Peak Detection Mode	PEAK	
CB5G	SCMT CBL 5 ft Peak Detection T0_Delay and Noise Gate	338.559	US
CB5T	SCMT CBL 5 ft Fixed Threshold Level	20	MV
CBLG	CBL Gate Width	45	US
CBRA	CBL LQC Reference Amplitude in Free Pipe	80	MV
CMCF	CBL Cement Type Compensation Factor	1	
CMTC	SCMT Slow Channel Multiplexer Mode	SCAN	
CMTM	SCMT Operating Mode	LOG	
CSCS	SCMT Slow Channel Index	VCC	
CTHI	Casing Thickness	0.255617	IN
DTF	Delta-T Fluid	189	US/F
FATT	Acoustic Attenuation due to Fluid	0	DB/F
FCF	CBL Fluid Compensation Factor	0.924277	
GOBO	Good Bond	1.55185	MV
MAPD	SCMT MAP Peak Detection Mode	PEAK	
MAPG	SCMT MAP Peak Detection T0_Delay and Noise Gate	167.559	US
MAPT	SCMT MAP Fixed Threshold Level	30	MV
MATT	Maximum Attenuation	16.5449	DB/F
MCCF	MAP Cement Type Compensation Factor	1	
MCI	Minimum Cemented Interval for Isolation	1.25	FT
MMSA	MAP Minimum Sonic Amplitude	4.32284	MV
MSA	Minimum Sonic Amplitude	0.579149	MV
PEDE	Peak Detection On/Off Switch in Playback	OFF	
VDLG	VDL Manual Gain	5	
ZCMT	Acoustic Impedance of Cement	6.8	MRAY
System and Miscellaneous			
CSIZ	Current Casing Size	4.500	IN
CWEI	Casing Weight	11.60	LB/F
DFD	Drilling Fluid Density	8.40	LB/G
DO	Depth Offset for Playback	3.0	FT
DORL	Depth Offset for Repeat Analysis	0.0	FT
PP	Playback Processing	RECOMPUTE	
TD	Total Depth	8929	FT

Input DLIS Files

DEFAULT	SCMT_RST_PSP_045LUP	FN:43	PRODUCER	25-Nov-2013 21:31	6953.5 FT	6646.5 FT
DEFAULT	SCMT_RST_PSP_054PUP	FN:51	PRODUCER	26-Nov-2013 00:41	8939.0 FT	-39.5 FT

Output DLIS Files


DEFAULT	SCMT_RST_PSP_055PUP	FN:52	PRODUCER	26-Nov-2013 00:47
---------	---------------------	-------	----------	-------------------

Schlumberger

TEMPERATURE PLOT

MAXIS Field Log

Index: 8939.0 – -39.5 FT



17879 Points Plotted

26-NOV-2013 0:46

Schlumberger

PBMS COEFFICIENTS

MAXIS Field Log

Client: ENCANA OIL & GAS (USA) INC
Field: MAMM CREEK
Well: HMU 6-13A (J6SEB)
Run date: 25-Nov-2013

Tool: PSP
Sub Type: PBMS
Sensor: GR

PBMS Gamma Ray
Sonde Serial NB RESISTORS FOR GR SENSOR N.33223,TOOL PBMS–BA0928. SENSOR S/N:
Sensor Serial NB 33223
Calib Date ddmmyy 090800
Matrix Size 12
Coeff CRC CFE2

GR HV Rt

	Rt**0	Rt**1
Rt**0	+.182000000000e+04	+.332000000000e+04

Client:	ENCANA OIL & GAS (USA) INC	Tool:	PSP
Field:	MAMM CREEK	Sub Type:	PBMS
Well:	HMU 6–13A (J6SEB)	Sensor:	WellTemp RTD
Run date:	25–Nov–2013		

PBMS RTD Well Thermometer
Sonde Serial NB COEFFICIENTS FOR RTD THERMOMETER PBMS–B.928 S/N:
Sensor Serial NB 928
Calib Date ddmmyy 280612
Matrix Size 16
Coeff CRC A24E

WTemp Coeff

	Tt**0	Tt**1	Tt**2
Tt**0	–.391987973189E+03	+.191346892512E+03	–.440920753451E+02
	Tt**3	Tt**4	Tt**5
Tt**0	+.957191300908E+01	–.711421725686E+00	0.0

Client: ENCANA OIL & GAS (USA) INC

Field: MAMM CREEK

Well: HMU 6-13A (J6SEB)

Run date: 25-Nov-2013

Tool:

Sub Type:

Sensor:

PSP

PBMS

CQG

PBMS Quartz Gauge type F

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

Matrix Size

Coeff CRC

COEFFICIENTS FOR CQG PBMS-B.928 S/N:

928

280612

66

9DC3

Pres Coeff

	Fb**0	Fb**1	Fb**2
Fc**0	+714463802232E+04	+183434658655E-01	-.156620073569E-06
Fc**1	-.100638308957E+01	-.119899563644E-04	-.912155899025E-10
Fc**2	+936268101283E-06	+423898071451E-10	+958076371919E-15
Fc**3	+185123362373E-11	+203107925433E-15	0.0
Fc**4	0.0	0.0	0.0
Fc**5	0.0	0.0	0.0

	Fb**3	Fb**4	Fb**5
Fc**0	-.746577997611E-10	-.588773826860E-15	-.622250441458E-19
Fc**1	-.120636521092E-15	+400325894750E-19	0.0
Fc**2	0.0	0.0	0.0
Fc**3	0.0	0.0	0.0
Fc**4	0.0	0.0	0.0
Fc**5	0.0	0.0	0.0

PBMS Quartz Gauge type F

Sonde Serial NB

Sensor Serial NB

Calib Date ddmmyy

Matrix Size

Coeff CRC

:

928

280612

66

283B

Temp Coeff

Fc**0	Fc**1	Fc**2

Fb**0	+.117016867873E+03	-.284359629614E-03	+.604391180345E-08
Fb**1	-.598309140812E-02	+.182731130848E-07	+.160166486172E-12
Fb**2	-.307621454576E-07	+.300601550309E-12	+.311233548560E-17
Fb**3	-.419658736767E-12	+.117473708647E-16	0.0
Fb**4	0.0	0.0	0.0
Fb**5	0.0	0.0	0.0

	Fc**3	Fc**4	Fc**5
Fb**0	+.114322792679E-12	+.153807711176E-17	-.736714260866E-21
Fb**1	-.528037875456E-18	-.220337637519E-21	0.0
Fb**2	0.0	0.0	0.0
Fb**3	0.0	0.0	0.0
Fb**4	0.0	0.0	0.0
Fb**5	0.0	0.0	0.0

PBMS Quartz Gauge type F

Sonde Serial NB :
 Sensor Serial NB 928
 Calib Date ddmmyy 280612
 Matrix Size 16
 Coeff CRC 093F

Clock Freq Coeff

	(Fb'-Fc')**0	(Fb'-Fc')**1	(Fb'-Fc')**2
(Fb'-Fc')**0	+.310874009898E+05	+.288920923041E-02	+.697940727038E-06
	(Fb'-Fc')**3	(Fb'-Fc')**4	(Fb'-Fc')**5
(Fb'-Fc')**0	-.657432344763E-10	-.412920638782E-15	+.213369826099E-20

PBMS Quartz Gauge type F

Sonde Serial NB :
 Sensor Serial NB 928
 Calib Date ddmmyy 280612
 Matrix Size 16
 Coeff CRC 8419

Clock Temp Coeff

	(Fb'-Fc')**0	(Fb'-Fc')**1	(Fb'-Fc')**2
(Fb'-Fc')**0	+.115369519827E+03	-.565338877075E-02	-.333717531829E-07
	(Fb'-Fc')**3	(Fb'-Fc')**4	(Fb'-Fc')**5
(Fb'-Fc')**0	-.124387135327E-12	+.713102327208E-16	-.316084316842E-20



MASTER CALIBRATION

MAXIS Field Log

Slim Cement Mapping Tool, 1-11/16 OD / Equipment Identification

Primary Equipment:

Slim Cement Mapping Xmitter Electronics	SCMX – CA	
Slim Cement Mapping Sonde	SCMS – CB	8303
Slim Cement Mapping Cartridge	SCMC – CA	8120

Auxiliary Equipment:

Slim Electronics Cartridge Housing	SECH – CA
------------------------------------	-----------

Slim Cement Mapping Tool, 1-11/16 OD Master Calibration

SCMT CBL and MAP Amplitude Normalization in SFT-155/-255

Phase	MAP 1 Amplitude Plus MV	Value	Phase	MAP 2 Amplitude Plus MV	Value
Master		938.0	Master		994.8
	500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)			500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)	
Phase	MAP 3 Amplitude Plus MV	Value	Phase	MAP 4 Amplitude Plus MV	Value
Master		781.2	Master		752.8
	500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)			500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)	
Phase	MAP 5 Amplitude Plus MV	Value	Phase	MAP 6 Amplitude Plus MV	Value
Master		729.4	Master		658.5
	500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)			500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)	
Phase	MAP 7 Amplitude Plus MV	Value	Phase	MAP 8 Amplitude Plus MV	Value
Master		631.3	Master		658.7
	500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)			500.0 (Minimum) 1075 (Nominal) 1650 (Maximum)	
Phase	CBL Amplitude Plus MV	Value			
Master		1291			
	1000 (Minimum) 1350 (Nominal) 1700 (Maximum)				

Master: 19-Nov-2013 13:46

Company: **ENCANA OIL & GAS (USA) INC**

Well: **HMU 6-13A (J6SEB)**

Field: **MAMM CREEK**



County: **GARFIELD**
State: **COLORADO**

SLIM CEMENT MAPPING LOG
CBL-VDL
GAMMA RAY-CCL