



## FIELD TICKET & TREATMENT REPORT CEMENT

Walt + Dinker

264430

## CEMENT

JOB TYPE <u>Surface</u>	HOLE SIZE <u>12 1/4"</u>	HOLE DEPTH <u>352</u>	CASING SIZE & WEIGHT <u>8 5/8 24#</u>
CASING DEPTH <u>352</u>	DRILL PIPE _____	TUBING _____	OTHER _____
SLURRY WEIGHT <u>14.8</u>	SLURRY VOL <u>1.36</u>	WATER gal/sk _____	CEMENT LEFT in CASING <u>20."</u>
DISPLACEMENT <u>212615</u>	DISPLACEMENT PSI _____	MIX PSI _____	RATE _____

REMARKS: Safety meeting and rig up on Martin Drilling rig #20, circulate casing mix 265 SWS, ~~then~~ Class A common cement with 3% calcium 265 gel. Shutdown released plug pump 265 lbs water. Shut in cement at 1" act. Circulate 1" down to 50' mix 50 SWS common cement with 3% Calcium 265 gel cement to surface.

Thanks M. test crew

Ravin 3737		7.65	SALES TAX	477.73
AUTHORIZATION <u>Greg Carden</u>		ESTIMATED TOTAL		10140.41
TITLE <u>Toolpusher</u>		DATE		11-27-13

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.