

Project: Weld County, CO
Site: Sec. 26-T10N-R58W
Well: Razor #26K-2306B
Wellbore: Sidetrack 1
Plan: Rev D0

Whiting Oil and Gas Corporation



SECTION DETAILS											
Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Target	
1	9466.00	89.88	359.14	5701.32	4377.22	-226.62	0.00	0.00	4377.22		
2	9530.00	89.88	359.14	5701.45	4441.21	-227.59	0.00	0.00	4441.21		
3	9630.00	89.36	356.19	5702.12	4541.12	-231.66	3.00	260.00	4541.12		
4	9754.29	91.84	356.22	5700.81	4665.12	-239.89	2.00	0.86	4665.12		
5	10090.08	91.84	356.22	5690.00	5000.00	-262.00	0.00	0.00	5000.00	Razor 26K-2306B STWP1 New	
6	10198.16	90.50	357.92	5687.79	5107.91	-267.52	2.00	128.46	5107.91	Razor 26K-2306B STWP2 New	
7	11090.87	90.50	357.92	5680.00	6000.00	-300.00	0.00	0.00	6000.00		
8	11223.58	89.98	0.52	5679.44	6132.68	-301.81	2.00	101.20	6132.68	Razor 26K-2306B STWP3 New	
	93228.87	89.98	0.52	5680.00	8137.89	-283.66	0.00	0.00	8137.89		

Plan: Rev D0 (Razor #26K-2306B/Sidetrack 1)

Created By: Troy L. Stoute Date: 11:40, January 21 2014

Checked: _____ Date: _____

Reviewed: _____ Date: _____

Approved: _____ Date: _____

T

M

Azimuths to True North
Magnetic Field
Magnetic North: 8.07°

Strength: 53096.5snT
Dip Angle: 67.43°
Date: 12/18/2013
Model: BGGM2013

