

**State of Colorado**  
**Oil and Gas Conservation Commission**

1120 Lincoln Street, Suite 801, Denver, Colorado 80205 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
Document Number: <u>400547397</u>			
Date Received: <u>01/29/2014</u>			

**SUNDRY NOTICE**

Submit a signed original. This form is to be used for general, technical and environmental sundry information. For proposed or completed operations, describe in full in Comments or provide as an attachment. Identify Well by API Number; identify Oil and Gas Location by Location ID Number; identify other Facility by Facility ID Number.

OGCC Operator Number: 47120 Contact Name Cheryl Light  
 Name of Operator: KERR-MCGEE OIL & GAS ONSHORE LP Phone: (720) 929-6461  
 Address: P O BOX 173779 Fax: (720) 929-7461  
 City: DENVER State: CO Zip: 80217-3779 Email: cheryl.light@anadarko.com

Complete the Attachment  
Checklist

OP OGCC

API Number : 05- 123 08230 00 OGCC Facility ID Number: 240442  
 Well/Facility Name: CLC GAS UNIT Well/Facility Number: 1  
 Location QtrQtr: NESW Section: 18 Township: 2N Range: 66W Meridian: 6  
 County: WELD Field Name: WATTENBERG  
 Federal, Indian or State Lease Number: \_\_\_\_\_

Survey Plat		
Directional Survey		
Srvc Eqpmt Diagram		
Technical Info Page		
Other		

**CHANGE OF LOCATION OR AS BUILT GPS REPORT**

- Change of Location \*     As-Built GPS Location Report     As-Built GPS Location Report with Survey

\* Well location change requires new plat. A substantive surface location change may require new Form 2A.

**SURFACE LOCATION GPS DATA** Data must be provided for Change of Surface Location and As Built Reports.

Latitude \_\_\_\_\_ PDOP Reading \_\_\_\_\_ Date of Measurement \_\_\_\_\_  
 Longitude \_\_\_\_\_ GPS Instrument Operator's Name \_\_\_\_\_

**LOCATION CHANGE (all measurements in Feet)**

Well will be: \_\_\_\_\_ (Vertical, Directional, Horizontal)

Change of **Surface** Footage **From** Exterior Section Lines:

FNL/FSL		FEL/FWL	
1650	FSL	1750	FWL

Change of **Surface** Footage **To** Exterior Section Lines:

--	--	--	--

Current **Surface** Location **From** QtrQtr NESW Sec 18

Twp 2N Range 66W Meridian 6

New **Surface** Location **To** QtrQtr \_\_\_\_\_ Sec \_\_\_\_\_

Twp \_\_\_\_\_ Range \_\_\_\_\_ Meridian \_\_\_\_\_

Change of **Top of Productive Zone** Footage **From** Exterior Section Lines:

--	--	--	--

Change of **Top of Productive Zone** Footage **To** Exterior Section Lines:

--	--	--	--

\*\*

Current **Top of Productive Zone** Location **From** Sec \_\_\_\_\_

Twp \_\_\_\_\_ Range \_\_\_\_\_

New **Top of Productive Zone** Location **To** Sec \_\_\_\_\_

Twp \_\_\_\_\_ Range \_\_\_\_\_

Change of **Bottomhole** Footage **From** Exterior Section Lines:

--	--	--	--

Change of **Bottomhole** Footage **To** Exterior Section Lines:

--	--	--	--

\*\*

Current **Bottomhole** Location Sec \_\_\_\_\_ Twp \_\_\_\_\_ Range \_\_\_\_\_

\*\* attach deviated drilling plan

New **Bottomhole** Location Sec \_\_\_\_\_ Twp \_\_\_\_\_ Range \_\_\_\_\_

Is location in High Density Area? \_\_\_\_\_

Distance, in feet, to nearest building \_\_\_\_\_, public road: \_\_\_\_\_, above ground utility: \_\_\_\_\_, railroad: \_\_\_\_\_,  
 property line: \_\_\_\_\_, lease line: \_\_\_\_\_, well in same formation: \_\_\_\_\_

Ground Elevation \_\_\_\_\_ feet Surface owner consultation date \_\_\_\_\_



Comments:

**ENGINEERING AND ENVIRONMENTAL WORK**

NOTICE OF CONTINUED TEMPORARILY ABANDONED STATUS

Indicate why the well is temporarily abandoned and describe future plans for utilization in the COMMENTS box below or provide as an attachment, as required by Rule 319.b.(3).

Date well temporarily abandoned \_\_\_\_\_ Has Production Equipment been removed from site? \_\_\_\_\_

Mechanical Integrity Test (MIT) required if shut in longer than 2 years. Date of last MIT \_\_\_\_\_

SPUD DATE: \_\_\_\_\_

**TECHNICAL ENGINEERING AND ENVIRONMENTAL WORK**

Details of work must be described in full in the COMMENTS below or provided as an attachment.

NOTICE OF INTENT Approximate Start Date 02/14/2014

REPORT OF WORK DONE Date Work Completed \_\_\_\_\_

<input type="checkbox"/> Intent to Recomplete (Form 2 also required)	<input type="checkbox"/> Request to Vent or Flare	<input type="checkbox"/> E&P Waste Mangement Plan
<input type="checkbox"/> Change Drilling Plan	<input checked="" type="checkbox"/> Repair Well	<input type="checkbox"/> Beneficial Reuse of E&P Waste
<input type="checkbox"/> Gross Interval Change	<input type="checkbox"/> Rule 502 variance requested. Must provide detailed info regarding request.	
<input type="checkbox"/> Other _____	<input type="checkbox"/> Status Update/Change of Remediation Plans for Spills and Releases	

COMMENTS:

REMEDIAL CEMENT

**CASING AND CEMENTING CHANGES**

Casing Type	Size	Of	/	Hole	Size	Of	/	Casing	Wt/Ft	Csg/LinTop	Setting Depth	Sacks of Cement	Cement Bottom	Cement Top

**H2S REPORTING**

Data Fields in this section are intended to document Sample and Location Data associated with the collection of a Gas Sample that is submitted for Laboratory Analysis.

Gas Analysis Report must be attached.

H2S Concentration: \_\_\_\_\_ in ppm (parts per million) Date of Measurement or Sample Collection \_\_\_\_\_

Description of Sample Point:

Absolute Open Flow Potential \_\_\_\_\_ in CFPD (cubic feet per day)

Description of Release Potential and Duration (If flow is not open to the atmosphere, identify the duration in which the container or pipeline would likely be opened for servicing operations.):

Distance to nearest occupied residence, school, church, park, school bus stop, place of business, or other areas where the public could reasonably be expected to frequent: \_\_\_\_\_

Distance to nearest Federal, State, County, or municipal road or highway owned and principally maintained for public use: \_\_\_\_\_

COMMENTS:

<b><u>Best Management Practices</u></b>		
<b><u>No</u></b>	<b><u>BMP/COA Type</u></b>	<b><u>Description</u></b>

Operator Comments:

1 NOTE: GYRO RAN 10/18/11.  
 2 Level location for base beam rig.  
 3 Call Foreman or Field Coordinator before rig up to catch plunger, isolate production equipment, and ask if replacement parts/equipment are requested. Operations need to hook up the Bradenhead pressure and bleed off the pressure before the rig gets on location.  
 4 Check and report surface casing pressure. If surface casing is not accessible at ground level, re-plumb so valve is at ground level.  
 5 Spot a minimum of 5 jts 2-3/8", 4.7#, J-55 EUE TBG for replacement.  
 6 MIRU slickline. Fish production equipment as necessary and tag fill. Note tagged depth in OpenWells. RDMO Slickline.  
 7 MIRU WO rig, flat tanks and rig pumps. Kill well, as necessary, with biocide treated fresh water. ND WH. NU BOP.  
 8 Unseat landing joint and lay down.  
 9 MIRU EMI services. TOOH with 2-3/8" TBG. EMI on TOOH. LD joints with wall loss or penetrations > 35%. Replace joints as necessary. \*\*Keep yellow & blue band tubing. Note joint number and depth of tubing leak(s) on PRODUCTION EQUIPMENT FAILURE REPORT IN OPEN WELLS.  
 10 PU casing scraper for 4-1/2", 10.5/11.6# casing and TIH to 7150' KB. Circulate all debris from wellbore with clean water. POOH and stand back tubing and LD scraper.  
 11 MIRU WL. RIH with CCL and CIBP. Correlate depth to Brandex CBL/GR dated 8/2/94. Set CIBP at 7050'. POOH.  
 12 Pressure test casing/CIBP to 1000 psi for 15 mins. If pressure test passes, proceed.  
 13 ND BOPs, ND existing tubing head. NU new 5000 psi rated wellhead but do not install adapter flange. NU BOPs.  
 14 RIH with CCL and perf guns. Correlate depth to CBL. PUH and shoot squeeze holes as per the following: 6950'-6951', 3 spf, 0.38" EHD, 23 gm charge. POOH and LD guns.  
 15 PU and TIH retrievable packer for 4-1/2", 10.5/11.6# casing. Set packer at 6850'. Establish injection/circulation before setting CICR. Note rate, pressure, volume pumped. Release packer and TOOH while standing back tubing and laying down packer.  
 16 RIH and set CICR at 6850'. RDMO WL.  
 17 PU stinger and RIH on 2-3/8" tbg. Sting into retainer at 6850'.  
 18 RU cementer. Prepare & pump 126 sks 50/50 Poz 'G' + 20% silica flour + 3% gel + 0.1% SMS + 0.4% fluid-loss additive, mixed at 13.5 ppg and 1.71 cu ft/sk, into squeeze holes at 6950'. Displace cement 1/2 bbl short of CICR. Sting out of CICR, place remaining cement on top of CICR. Reverse out. Design is for coverage from 6950 to 6500 in 9.5" hole (caliper log), including 20% excess.  
 19 TOOH and stand back tbg. LD stinger. WOC overnight at minimum.  
 20 MIRU WL. PU and RIH with CCL/CBL/GR. Correlate to depth to CBL. Run CBL from 6800' to SURFACE. Deliver logs to Evans for review. Once cleared by Engineering, proceed with next step.  
 21 TIH with 3-7/8" bit on 2-3/8" TBG. Drill through cement and CICR down to CIBP at 7050'. Pressure test squeeze perforations to 1000 psi for 15 mins. If pressure test passes, proceed.  
 22 Continue to drill out to PBDT of 7908'.  
 23 TOOH while standing back tubing and LD bit.  
 24 MIRU hydrotester.  
 25 PU & RIH with 2-3/8" NC, 2-3/8" XN profile nipple, 25 joints 2-3/8" TBG, Arrowset AS-1X packer (10k psi rated), and 2-3/8" TBG. Hydrotest tubing to 6000 psi while RIH. Set packer at 6600'.  
 26 Load backside with biocide treated water and pressure test packer to 1000 psi for 15 min.  
 27 ND BOP. NU WH. Ensure all valves on TBG head are rated to 5000 psi and ensure TBG head has a new R-46 ring gasket installed.  
 28 Hydrotest TBG head and master valve to 5000 psi. If pressure test fails, call Evans office for alternate procedures.  
 29 RDMO hydrotester. RDMO WO rig.  
 30 Return well to production team.  
 31 END OF SAFETY PREP STEPS. BELOW ARE STEPS FOR UN-PREPPING THE WELL.  
 32 When notification is sent to un-prep well, MIRU WO rig.  
 33 Control well with biocide treated water.  
 34 ND WH. NU BOP.  
 35 Release Arrowset AS-1X packer and POOH with 2-3/8" TBG, Arrowset packer, XN profile nipple, and NC while standing back TBG and laying down packer.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Cheryl Light  
 Title: Sr. Regulatory Analyst Email: DJRegulatory@anadarko.com Date: 1/29/2014

Based on the information provided herein, this Sundry Notice (Form 4) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: SCHLAGENHAUF, MARK Date: 1/30/2014

**CONDITIONS OF APPROVAL, IF ANY:**

**COA Type**

**Description**

	1) The additional cement referenced shall be placed as indicated and comply with Rule 317.i. The placed cement shall be verified with a CBL and documented with a Form 5 Drilling Completion Report. 2) Please submit gyro data with Form 5 Drilling Completion Report.
--	--

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
-------------------	----------------	---------------------

--	--	--

Total: 0 comment(s)

### Attachment Check List

<u>Att Doc Num</u>	<u>Name</u>
--------------------	-------------

400547397	FORM 4 SUBMITTED
400547399	OTHER

Total Attach: 2 Files