



Ursa Operating Company, LLC

Rockies Region

Speakman A

BAT 14D-24-07-96

Wellbore #1

Plan: Design #3

Standard Planning Report

23 January, 2014



Database:	MasterDB	Local Co-ordinate Reference:	Well BAT 14D-24-07-96
Company:	Ursa Operating Company, LLC	TVD Reference:	BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)
Project:	Rockies Region	MD Reference:	BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)
Site:	Speakman A	North Reference:	True
Well:	BAT 14D-24-07-96	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #3		

Project	Rockies Region		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Central Zone		

Site		Speakman A			
Site Position:		Northing:	1,588,429.06 usft	Latitude:	39° 25' 15.663 N
From:	Lat/Long	Easting:	2,276,734.73 usft	Longitude:	108° 3' 38.016 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	-1.61 °

Well	BAT 14D-24-07-96, SHL LAT: 39.4205938 LONG: -108.0600565					
Well Position	+N/-S	-154.4 usft	Northing:	1,588,270.76 usft	Latitude:	39° 25' 14.138 N
	+E/-W	142.3 usft	Easting:	2,276,872.58 usft	Longitude:	108° 3' 36.203 W
Position Uncertainty		0.0 usft	Wellhead Elevation:	5,197.9 usft	Ground Level:	5,182.5 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF200510	6/15/2013	10.08	65.63	52,046

Design	Design #3			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	212.99

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
200.0	0.00	0.00	200.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,420.0	42.70	212.99	1,310.2	-364.0	-236.3	3.50	3.50	0.00	212.99	
2,936.7	42.70	212.99	2,424.8	-1,226.7	-796.4	0.00	0.00	0.00	0.00	
4,156.8	0.00	0.00	3,535.0	-1,590.7	-1,032.7	3.50	-3.50	0.00	180.00	BAT 14D-24-07-96 TC
6,349.8	0.00	0.00	5,728.0	-1,590.7	-1,032.7	0.00	0.00	0.00	0.00	BAT 14D-24-07-96 BT

Database:	MasterDB	Local Co-ordinate Reference:	Well BAT 14D-24-07-96
Company:	Ursa Operating Company, LLC	TVD Reference:	BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)
Project:	Rockies Region	MD Reference:	BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)
Site:	Speakman A	North Reference:	True
Well:	BAT 14D-24-07-96	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #3		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
Start Build 3.50									
300.0	3.50	212.99	299.9	-2.6	-1.7	3.1	3.50	3.50	0.00
400.0	7.00	212.99	399.5	-10.2	-6.6	12.2	3.50	3.50	0.00
500.0	10.50	212.99	498.3	-23.0	-14.9	27.4	3.50	3.50	0.00
600.0	14.00	212.99	596.0	-40.8	-26.5	48.6	3.50	3.50	0.00
700.0	17.50	212.99	692.3	-63.6	-41.3	75.8	3.50	3.50	0.00
800.0	21.00	212.99	786.7	-91.2	-59.2	108.7	3.50	3.50	0.00
900.0	24.50	212.99	878.9	-123.6	-80.3	147.4	3.50	3.50	0.00
1,000.0	28.00	212.99	968.5	-160.7	-104.3	191.6	3.50	3.50	0.00
1,100.0	31.50	212.99	1,055.3	-202.3	-131.4	241.2	3.50	3.50	0.00
1,200.0	35.00	212.99	1,139.0	-248.3	-161.2	296.1	3.50	3.50	0.00
1,300.0	38.50	212.99	1,219.1	-298.5	-193.8	355.9	3.50	3.50	0.00
1,400.0	42.00	212.99	1,295.4	-352.7	-229.0	420.5	3.50	3.50	0.00
1,420.0	42.70	212.99	1,310.2	-364.0	-236.3	434.0	3.50	3.50	0.00
Start 1516.7 hold at 1420.0 MD									
1,500.0	42.70	212.99	1,369.0	-409.5	-265.8	488.2	0.00	0.00	0.00
1,600.0	42.70	212.99	1,442.4	-466.4	-302.8	556.0	0.00	0.00	0.00
1,700.0	42.70	212.99	1,515.9	-523.3	-339.7	623.8	0.00	0.00	0.00
1,800.0	42.70	212.99	1,589.4	-580.1	-376.6	691.7	0.00	0.00	0.00
1,900.0	42.70	212.99	1,662.9	-637.0	-413.5	759.5	0.00	0.00	0.00
2,000.0	42.70	212.99	1,736.4	-693.9	-450.5	827.3	0.00	0.00	0.00
2,100.0	42.70	212.99	1,809.9	-750.8	-487.4	895.1	0.00	0.00	0.00
2,200.0	42.70	212.99	1,883.4	-807.7	-524.3	962.9	0.00	0.00	0.00
2,300.0	42.70	212.99	1,956.9	-864.6	-561.2	1,030.7	0.00	0.00	0.00
2,400.0	42.70	212.99	2,030.4	-921.4	-598.2	1,098.6	0.00	0.00	0.00
2,500.0	42.70	212.99	2,103.9	-978.3	-635.1	1,166.4	0.00	0.00	0.00
2,600.0	42.70	212.99	2,177.3	-1,035.2	-672.0	1,234.2	0.00	0.00	0.00
2,700.0	42.70	212.99	2,250.8	-1,092.1	-708.9	1,302.0	0.00	0.00	0.00
2,800.0	42.70	212.99	2,324.3	-1,149.0	-745.9	1,369.8	0.00	0.00	0.00
2,900.0	42.70	212.99	2,397.8	-1,205.8	-782.8	1,437.7	0.00	0.00	0.00
2,936.7	42.70	212.99	2,424.8	-1,226.7	-796.4	1,462.6	0.00	0.00	0.00
Start Drop -3.50									
3,000.0	40.49	212.99	2,472.1	-1,262.0	-819.2	1,504.6	3.50	-3.50	0.00
3,072.1	37.96	212.99	2,528.0	-1,300.2	-844.1	1,550.2	3.50	-3.50	0.00
WF									
3,100.0	36.99	212.99	2,550.1	-1,314.4	-853.3	1,567.1	3.50	-3.50	0.00
3,200.0	33.49	212.99	2,631.8	-1,362.8	-884.7	1,624.8	3.50	-3.50	0.00
3,300.0	29.99	212.99	2,716.8	-1,406.9	-913.3	1,677.4	3.50	-3.50	0.00
3,400.0	26.49	212.99	2,804.9	-1,446.6	-939.1	1,724.7	3.50	-3.50	0.00
3,500.0	22.99	212.99	2,895.7	-1,481.7	-961.9	1,766.6	3.50	-3.50	0.00
3,600.0	19.49	212.99	2,988.9	-1,512.1	-981.6	1,802.8	3.50	-3.50	0.00
3,700.0	15.99	212.99	3,084.1	-1,537.6	-998.2	1,833.2	3.50	-3.50	0.00
3,800.0	12.49	212.99	3,181.0	-1,558.3	-1,011.6	1,857.8	3.50	-3.50	0.00
3,900.0	8.99	212.99	3,279.3	-1,573.9	-1,021.7	1,876.4	3.50	-3.50	0.00
4,000.0	5.49	212.99	3,378.5	-1,584.5	-1,028.6	1,889.0	3.50	-3.50	0.00
4,100.0	1.99	212.99	3,478.2	-1,589.9	-1,032.1	1,895.6	3.50	-3.50	0.00
4,156.8	0.00	0.00	3,535.0	-1,590.7	-1,032.7	1,896.5	3.50	-3.50	0.00
Start 2193.0 hold at 4156.8 MD - Top of Gas - BAT 14D-24-07-96 TGT									

Database:	MasterDB	Local Co-ordinate Reference:	Well BAT 14D-24-07-96
Company:	Ursa Operating Company, LLC	TVD Reference:	BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)
Project:	Rockies Region	MD Reference:	BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)
Site:	Speakman A	North Reference:	True
Well:	BAT 14D-24-07-96	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #3		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,200.0	0.00	0.00	3,578.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
4,300.0	0.00	0.00	3,678.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
4,400.0	0.00	0.00	3,778.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
4,500.0	0.00	0.00	3,878.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
4,600.0	0.00	0.00	3,978.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
4,700.0	0.00	0.00	4,078.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
4,800.0	0.00	0.00	4,178.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
4,900.0	0.00	0.00	4,278.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,000.0	0.00	0.00	4,378.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,100.0	0.00	0.00	4,478.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,200.0	0.00	0.00	4,578.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,300.0	0.00	0.00	4,678.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,400.0	0.00	0.00	4,778.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,500.0	0.00	0.00	4,878.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,528.8	0.00	0.00	4,907.0	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
Cameo									
5,600.0	0.00	0.00	4,978.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,700.0	0.00	0.00	5,078.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,800.0	0.00	0.00	5,178.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
5,900.0	0.00	0.00	5,278.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
6,000.0	0.00	0.00	5,378.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
6,049.8	0.00	0.00	5,428.0	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
Rollins									
6,100.0	0.00	0.00	5,478.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
6,200.0	0.00	0.00	5,578.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
6,300.0	0.00	0.00	5,678.2	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
6,349.8	0.00	0.00	5,728.0	-1,590.7	-1,032.7	1,896.5	0.00	0.00	0.00
TD at 6349.8 - BAT 14D-24-07-96 BHL									

Design Targets									
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
BAT 14D-24-07-96 TGT	0.00	0.00	3,535.0	-1,590.7	-1,032.7	1,586,709.74	2,275,795.50	39° 24' 58.415 N	108° 3' 49.362 W
- hit/miss target									
- plan hits target center									
- Rectangle (sides W100.0 H40.0 D2,193.0)									
BAT 14D-24-07-96 BHL	0.00	0.00	5,728.0	-1,590.7	-1,032.7	1,586,709.74	2,275,795.50	39° 24' 58.415 N	108° 3' 49.362 W
- hit/miss target									
- plan hits target center									
- Rectangle (sides W100.0 H40.0 D0.0)									

Database:	MasterDB	Local Co-ordinate Reference:	Well BAT 14D-24-07-96
Company:	Ursa Operating Company, LLC	TVD Reference:	BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)
Project:	Rockies Region	MD Reference:	BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)
Site:	Speakman A	North Reference:	True
Well:	BAT 14D-24-07-96	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #3		

Formations					
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
3,072.1	2,528.0	WF		0.00	
4,156.8	3,535.0	Top of Gas		0.00	
5,528.8	4,907.0	Cameo		0.00	
6,049.8	5,428.0	Rollins		0.00	

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
200.0	200.0	0.0	0.0	Start Build 3.50
1,420.0	1,310.2	-364.0	-236.3	Start 1516.7 hold at 1420.0 MD
2,936.7	2,424.8	-1,226.7	-796.4	Start Drop -3.50
4,156.8	3,535.0	-1,590.7	-1,032.7	Start 2193.0 hold at 4156.8 MD
6,349.8	5,728.0	-1,590.7	-1,032.7	TD at 6349.8



Well Name: BAT 14D-24-07-96
Surface Location: Speakman A
North American Datum 1983, US State Plane 1983, Colorado Central Zone
Ground Elevation: 5182.5
+N/-S +E/-W Northing Easting Latitude Longitude Slot
0.0 0.0 1588270.76 2276872.58 39° 25' 14.138 N 108° 3' 36.203 W
Original Well Elev BAT 14D-24-07-96 @ 5197.9usft (Original Well Elev)



Azimuths to True North
Magnetic North: 10.08°
Magnetic Field
Strength: 52046.1nT
Dip Angle: 65.63°
Date: 6/15/2013
Model: IGRF200510

Speakman A
BAT 14D-24-07-96
Design #3
12:04, January 23 2014

WELLBORE TARGET DETAILS (MAP CO-ORDINATES AND LAT/LONG)

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Shape
BAT 14D-24-07-96	3535.0	-1590.7	-1032.7	1586709.74	2275795.50	39° 24' 58.415 N	108° 3' 49.362 W	Rectangle (Sides: L40.0 W100.0)
BAT 14D-24-07-96	5728.0	-1590.7	-1032.7	1586709.74	2275795.50	39° 24' 58.415 N	108° 3' 49.362 W	Rectangle (Sides: L40.0 W100.0)

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSec	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	200.0	0.00	0.00	200.0	0.0	0.0	0.00	0.00	0.0	
3	1420.0	42.70	212.99	1310.2	-364.0	-236.3	3.50	212.99	434.0	
4	2936.7	42.70	212.99	2424.8	-1226.7	-796.4	0.00	0.00	1462.6	
5	4156.8	0.00	0.00	3535.0	-1590.7	-1032.7	3.50	180.00	1896.5	BAT 14D-24-07-96 TGT
6	6349.8	0.00	0.00	5728.0	-1590.7	-1032.7	0.00	0.00	1896.5	BAT 14D-24-07-96 BHL

ANNOTATIONS

TVD	MD	Annotation
200.0	200.0	Start Build 3.50
1310.2	1420.0	Start 1516.7 hold at 1420.0 MD
2424.8	2936.7	Start Drop -3.50
3535.0	4156.8	Start 2193.0 hold at 4156.8 MD
5728.0	6349.8	TD at 6349.8

FORMATION TOP DETAILS

TVDPath	MDPath	Formation	DipAngle	DipDir
2528.0	3072.1	WF	0.00	
3535.0	4156.8	Top of Gas	0.00	
4907.0	5528.8	Cameo	0.00	
5428.0	6049.8	Rollins	0.00	

