DISCLAIMER
All the information, data and conclusions contained or referred to in this document or other correspondence with our company are to be considered the opinions of our company based on information and data received or obtained by our company as well as our company's interpretation of such data and information. All of such information, data, conclusions and opinions are given without any warranty, express or implied, as to their accuracy, and no liability or responsibility for any such information, data, conclusions and opinions (or any omission to make the same available) will be incurred by our company or its agents.

Armstrong Oil & Gas Inc.
Cadotte Lake 4-27-109-24W6
Cadotte Lake Drilling Rig 25
Triple Combo Log - Run 1 Surface
API #: 42-123-20108-00

Armstrong Oil & Gas Inc.
Cadotte Lake 4-27-109-24W6
Cadotte Lake Drilling Rig 25
Triple Combo Log - Run 1 Surface
API #: 42-123-20108-00

Company: Armstrong Oil & Gas Inc.
Well: Cadotte Lake 4-27-109-24W6
Drilling Rig: Cadotte Lake Drilling Rig 25
Triple Combo Log - Run 1 Surface
API #: 42-123-20108-00
Location: 4-27-109-24W6
Province: Alberta
Country: Canada
Field: Cadotte Lake
Service Company: Schlumberger
Run: 1
Date: Sept 14-15 '19
Time: 23:59 Sept 14 to 00:30 Sept 15
Depth Driller: 2,700 m
Depth Logger: 2,700 m
Bottom Log Interval: 2,700 m
Top Log Interval: 1,800 m
Casing Driller: 1,800 m @ 1,800 m
Casing Logger: 1,800 m
Bit Size: 311.2 mm
Type Fluid in Hole: Water Based Mud
Density: 1.10 g/cm³
Viscosity: 50 s
Resistivity: 0.2 ohm-m @ 20 °C
Source of Sample: Flowline
Rm @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rmf @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rmc @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rm @ BHT: 0.2 ohm-m @ 20 °C
Time Circulation Stopped: 23:59 Sept 14
Time Logger on Bottom: 00:30 Sept 15
Maximum Recorded Temperature: 20 °C
Equipment Number: 1
Location: Cadotte Lake
Recorded By: Jeff Lee
Witnessed By: Jeff Lee

Company: Armstrong Oil & Gas Inc.
Well: Cadotte Lake 4-27-109-24W6
Drilling Rig: Cadotte Lake Drilling Rig 25
Triple Combo Log - Run 1 Surface
API #: 42-123-20108-00
Location: 4-27-109-24W6
Province: Alberta
Country: Canada
Field: Cadotte Lake
Service Company: Schlumberger
Run: 1
Date: Sept 14-15 '19
Time: 23:59 Sept 14 to 00:30 Sept 15
Depth Driller: 2,700 m
Depth Logger: 2,700 m
Bottom Log Interval: 2,700 m
Top Log Interval: 1,800 m
Casing Driller: 1,800 m @ 1,800 m
Casing Logger: 1,800 m
Bit Size: 311.2 mm
Type Fluid in Hole: Water Based Mud
Density: 1.10 g/cm³
Viscosity: 50 s
Resistivity: 0.2 ohm-m @ 20 °C
Source of Sample: Flowline
Rm @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rmf @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rmc @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rm @ BHT: 0.2 ohm-m @ 20 °C
Time Circulation Stopped: 23:59 Sept 14
Time Logger on Bottom: 00:30 Sept 15
Maximum Recorded Temperature: 20 °C
Equipment Number: 1
Location: Cadotte Lake
Recorded By: Jeff Lee
Witnessed By: Jeff Lee

Company: Armstrong Oil & Gas Inc.
Well: Cadotte Lake 4-27-109-24W6
Drilling Rig: Cadotte Lake Drilling Rig 25
Triple Combo Log - Run 1 Surface
API #: 42-123-20108-00
Location: 4-27-109-24W6
Province: Alberta
Country: Canada
Field: Cadotte Lake
Service Company: Schlumberger
Run: 1
Date: Sept 14-15 '19
Time: 23:59 Sept 14 to 00:30 Sept 15
Depth Driller: 2,700 m
Depth Logger: 2,700 m
Bottom Log Interval: 2,700 m
Top Log Interval: 1,800 m
Casing Driller: 1,800 m @ 1,800 m
Casing Logger: 1,800 m
Bit Size: 311.2 mm
Type Fluid in Hole: Water Based Mud
Density: 1.10 g/cm³
Viscosity: 50 s
Resistivity: 0.2 ohm-m @ 20 °C
Source of Sample: Flowline
Rm @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rmf @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rmc @ Meas. Temp: 0.2 ohm-m @ 20 °C
Rm @ BHT: 0.2 ohm-m @ 20 °C
Time Circulation Stopped: 23:59 Sept 14
Time Logger on Bottom: 00:30 Sept 15
Maximum Recorded Temperature: 20 °C
Equipment Number: 1
Location: Cadotte Lake
Recorded By: Jeff Lee
Witnessed By: Jeff Lee

Gamma Ray (GAPI) 0 150
Caliper (in) 6 16
Density Porosity (pu) 45 -15
Neutron Porosity (pu) 45 -15
Deep Resistivity (Ohm-m) .2 2000
Medium Resistivity (Ohm-m) .2 2000
Shallow Resistivity (Ohm-m) .2 2000
Bit Size (in) 12

Gamma Ray (GAPI) 0 150
Caliper (in) 6 16
Density Porosity (pu) 45 -15
Neutron Porosity (pu) 45 -15
Deep Resistivity (Ohm-m) .2 2000
Medium Resistivity (Ohm-m) .2 2000
Shallow Resistivity (Ohm-m) .2 2000
Bit Size (in) 12

Gamma Ray (GAPI) 0 150
Caliper (in) 6 16
Density Porosity (pu) 45 -15
Neutron Porosity (pu) 45 -15
Deep Resistivity (Ohm-m) .2 2000
Medium Resistivity (Ohm-m) .2 2000
Shallow Resistivity (Ohm-m) .2 2000
Bit Size (in) 12

1:200 (5"/100')

1:200 (5"/100')

1:200 (5"/100')

Base Fish Creek Sandstone
Base Fish Creek Sandstone
Base Fish Creek Sandstone