

WELLBORE DIAGRAM: After P&A Operations



Company: Hyndrex Resources
Lease: Ampet/Amoco
Location: SWSE, Sec: 9, T2S, R64W

Well No.: 9-34
County: Adams

API: 05-001-08885
Field: Toque
State: Colorado

WELLHEAD:

Surface Casing

Size: 9-5/8"
Wght: 32.0#
Type:
Depth: 222
Csg ID:
Csg Drift:
TOC: Surface
Hole Size: 13-3/4"

150 sxs of cement with LCM from 300' to 0'
To cover surface casing shoe at 222'

Production Casing

Size: 4-1/2"
Wght: 11.600
Type:
Depth: 8,030
Csg ID:
Csg Drift:
TOC: 7,195
Hole Size: 7-7/8"

40 sxs of cement at 450'

40 sxs of cement at 1,100'

40 sxs of cement at 1,600'

PERFORATIONS:

STAGE 1: 7,867 - 7,873
STAGE 2: 7,922 - 7,930

50 sxs from 50' below casing stub to 100' above
Cut casing at freepoint (below 1,700')

Niobrara top: 7,100'

40 sxs of cement at 7,158' to cover Niobrara top
(If CBL shows TOC below Nio top, perf and squeeze)

10 sxs of cement on top of CIBP
CIBP at 7,810' (50' above topmost perforation)

Stage 1
PBTD: 7,910
Stage 2
TD: 8,032

Updated: 2/6/2014
By: Aron Rascon

