
Well Name: 16/7-A-21 AH
Well Bore: 16/7-A-21 AH
Log Run No.: 1 Run 1 Run 2
Log Run Date: 20-Jun-2015
Log Run Time: 00:00 - 24:00
Drilling Fluid: Water Based
Drilling Fluid Type: Water Based
Drilling Fluid Density: 1.03 - 1.04 SG
Drilling Fluid Viscosity: 30 - 40 s
Drilling Fluid pH: 9 - 10
Drilling Fluid Chlorides: 30 - 40 g/l
Max Temp: 90 °C
Max Deviation: 90.1 °
Max Dogleg: 3.5 °/30m
Min Hole Size: 8.5 in
Max Hole Size: 8.5 in
Max Mud Weight: 1.04 SG
Max Flow Rate: 3000 l/min
Max Pump Pressure: 350 bar
Max Rotary Speed: 180 rpm
Max Rotary Torque: 30 kNm
Max Weight on Bit: 20 kN
Max Rate of Penetration: 100 m/hr
Max Gamma Ray: 150 API
Max Resistivity: 2000 ohmm
Max Neutron Porosity: 0.6 v/v
Max Density: 3 g/cm3
Max Caliper: 10 in
Max Annular Pressure: 350 bar
Max Equivalent Circulating Density: 1.04 SG
Max Pump