

Calibration Report

Database File: SHELL-MAIN-PROP.db
Calibration Method: Multi Point Calibration

Calibration Log

Tool Number: 32.00
Tool Type: Dual Laterolog
Firmware: Rev. 4.01 19-JUL-21 16:02

CALIBRATE Data: 1.1 cal1
Calibration Points: 1.1 cal2
Operator: 1.1 cal3
Remarks: 1.1000 cal4 hole

Temperature Corrected Resistivity Calibration Report

Serial Number: 32.00
Tool Type: Dual Laterolog
Calibration Curve Number: 1
Calibration Points: 4

Master Calibration, performed Tue Dec 17 15:44:42 2013

Pass 1.0 Calibration Data Results

Gain Offset Gain Offset Gain Offset

A 0.000 1.750 10.000 -10.000 10.000 -10.000
M 0.000 1.750 0.000 10.000 -10.000 0.000
AO 0.000 1.750 1.000 10.000 -10.000 1.000
A1 0.000 1.750 0.000 100.000 -100.000 0.000
M1 0.000 1.750 1.000 100.000 -100.000 1.000
A2 0.000 1.750 0.000 1000.000 -1000.000 0.000
M2 0.000 1.750 1.000 1000.000 -1000.000 1.000
A3 0.000 1.750 0.000 10000.000 -10000.000 0.000
M3 0.000 1.750 1.000 10000.000 -10000.000 0.000

Matrix Resource Calibration Tue Dec 17 15:44:42 1996

Pass 1.0 Calibration Data Results

Gain Offset Gain Offset Gain Offset

CAL 0.000 0.000 0.000 1.375 1.000 0.000

Air Gain Calibration performed Thu Jan 23 14:44 2014

Pass 1.0 Calibration Data Results

Gain Offset Gain Offset

A 0.000 0.000 0.000
M 0.000 0.000 0.000
AO 0.000 0.000 0.000
A1 0.000 0.000 0.000
M1 0.000 0.000 0.000
A2 0.000 0.000 0.000
M2 0.000 0.000 0.000
A3 0.000 0.000 0.000
M3 0.000 0.000 0.000

Temperature Calibration Report

Tool Number: 32.00
Tool Type: Dual Laterolog
Firmware: Rev. 4.01 19-JUL-21 16:02

Reading

Low Reference: 20.00 degC 68.00 degF
High Reference: 100.00 degC 212.00 degF
Offset: 0.00
Slope: 1.00