

Operating Rig: Rig 64 - DHD-X - 2,000 hp
Drilling Contractor: Helmerich & Payne (FlexRig) Spud Date: 8/17/2018 07:00

Lateral Well Plan

Lateral Well Plan for Well 1H of Pad 1 in Section 6 of T153N-R97W of the 5th PM

Surface Location: 1,000' FNL & 1,000' FWL
Bottom Hole Location: 1,000' FSL & 1,000' FWL
Elevation: GL: 1,947' & RKB: 1,972'
Directions to Rig: Williston, ND

Target Zone: Middle Bakken
Target Top: 10,000' TVD
Target Bottom: 10,020' TVD
Dip: 90°
Azimuth: 180°

Casing Program
9 5/8" Surface: 2,000' MD
7" Intermediate: 10,000' MD
4 1/2" Liner: 20,000' MD

Mud Program
Surface: Fresh Water
Intermediate: Invert
Lateral: Brine

Formation Tops
Pierre: 1,972' TVD
Greenhorn: 5,472' TVD
Mowry: 5,872' TVD
Dakota: 6,272' TVD
Swift: 6,672' TVD
Rierdon: 7,072' TVD
Dunham Salt: 7,472' TVD
Spearfish: 7,872' TVD
Pine Salt: 8,272' TVD
Opeche: 8,472' TVD
Minnelusa: 8,672' TVD
Kibbey Lime: 9,072' TVD
Charles: 9,272' TVD
Base Last Salt: 9,672' TVD
Ratcliffe: 9,872' TVD
Mission Canyon: 10,072' TVD
Lodgepole: 10,472' TVD
False Bakken: 10,872' TVD
Upper Bakken: 10,882' TVD
Middle Bakken: 10,900' TVD
Lower Bakken: 10,920' TVD
Pronghorn: 10,940' TVD
Three Forks: 10,960' TVD

Drilling Plan
Surface: 2,000' MD, 2,000' TVD
Intermediate: 10,000' MD, 10,000' TVD
Lateral: 20,000' MD, 10,020' TVD
Total Drilling Days: 20
Total Completion Days: 10
Total Well Days: 30

Bit Program
Surface: 13.5" PDC
Intermediate: 8.75" PDC
Lateral: 6" PDC

Directional Plan
Build Rate: 12°/100'
Lateral Length: 10,000'
Total Vertical Depth: 10,020' TVD
Total Measured Depth: 20,000' MD

Prepared by: Nathan Gilbertson, Lead Directional Driller
Date: 8/17/2018