PIONEER
Pioneer Energy Services

Radial Cement Bond Log With VDL / CCL / GR And Cement Map

Company Anadarko Petroleum Corporation
Well NRC 4N-8HZ
Field Wattenberg
County Weld State Colorado

Location: API # : 05-123-38412
SHL: 350'FSL & 660'FWL
SEC 8 TWP 1N RGE 67W

Other Services
JB/GR
Caliper
Set Plug

Permanent Datum	Ground Level	Elevation 5049'	Elevation
Log Measured From	Kelly Bushing	25' A.P.D.	K.B. 5074' D.F. 5073' G.L. 5049'
Drilling Measured From	Kelly Bushing		

Company Anadarko Petroleum Corporation
Well NRC 4N-8HZ
Field Wattenberg
County Weld
State Colorado

Date	23-Mar-2014
Run Number	Two
Depth Driller	12,553'
Depth Logger	7611'
Bottom Logged Interval	7609'
Top Log Interval	Surface
Open Hole Size	8.75"
Type Fluid	Water
Density / Viscosity	8.34
Max. Recorded Temp.	See Caliper Log
Estimated Cement Top	56'
Time Well Ready	14:00
Time Logger on Bottom	14:30
Equipment Number	96
Location	Ft. Morgan
Recorded By	Bruce Miller
Witnessed By	Mr. Edgar Chavez

Borehole Record				Tubing Record		
Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size	Wgt/Ft	Top	Bottom
Surface String	9.625"	36#	Surface	1263'
Prot. String				
Production String	7.0"	26#	Surface	7900'
Liner	4.5"	11.6#	6816'	12,543'
See Remarks				

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank You For Using Pioneer Energy Services

Liner Top Was Found At 6818' On Log.

K.O.P. @ 6889'



Sensor	Offset (ft)	Description	Len (ft)	OD (in)	Wt (lb)
		PTS275	2.83	2.75	
WVF3FT WVFCAL WVFS1 WVFS2 WVFS3 WVFS4 WVFS5 WVFS6 WVFS7 WVFS8 WVF5FT	11.86 11.86 11.86 11.86 11.86 11.86 11.86 11.86 11.86 11.86 10.78	RBT-Probe (Base) Probe Radii Bond Tool with Digital Telemetry	8.92	2.75	90.00
		PTS275	2.83	2.75	
CCL TEMP GR	3.84 3.14 2.30	GCT-GRCCLTEMP (130608) Probe GCT	4.69	2.75	100.00

Dataset: anadarko_nrc_4n-8hz_jbgr_logs.db: field/well/run2/pass1
Total Length: 19.27 ft
Total Weight: 190.00 lb
O.D. 2.75 in

PIONEER
Pioneer Energy Services

Main Pass

Logged With 2500 PSI Applied At Surface

Database File: anadarko_nrc_4n-8hz_jbgr_logs.db
Dataset Pathname: run2/pass1
Presentation Format: scbl02
Dataset Creation: Sun Mar 23 14:29:25 2014 by Log SCH 120430
Charted by: Depth in Feet scaled 1:240


3600
3700


3800
3900


4000
4100
4200


4300
4400


4500
4600


4700
4800


4900
5000


5100
5200


5300
5400


5500
5600


5700
5800


5900
6000
6100


6200
6300


6400
6500


6600
6700


AMPx5
AMP
6800
7.0" 26# Casing
Liner Top
6900


7000
7100


7200
7300


7400
7500



Calibration Report

Database File:	anadarko_nrc_4n-8hz_jbgr_logs.db
Dataset Pathname:	run2/pass1
Dataset Creation:	Sun Mar 23 14:29:25 2014 by Log SCH 120430

Gamma Ray Calibration Report

Serial Number:	130608	
Tool Model:	GRCCLTEMP	
Performed:	Sun Jun 13 14:33:21 1993	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Temperature Calibration Report

Serial Number:	130608	
Tool Model:	GRCCLTEMP	
Performed:	Thu Aug 15 08:56:46 2013	
	Reference	Reading
Low Reference:	100.00 degF	6509.65degF
High Reference:	350.00 degF	27350.70degF
Gain:	0.01	
Offset:	21.91	
Delta Spacing	1	

Segmented Cement Bond Log Calibration Report

Serial Number:	Base	
Tool Model:	Probe	
Calibration Casing Diameter:	7.000	in
Calibration Depth:	918.155	ft

Master Calibration, performed Sun Mar 23 14:38:45 2014:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.030	0.780	2.000	62.165	80.211	-0.398
CAL	0.963	0.984				
5'	0.024	0.791	2.000	62.165	78.413	0.112
SUM						
S1	0.019	0.735	5.000	95.000	125.559	2.664
S2	0.030	0.784	5.000	95.000	119.280	1.476
S3	0.042	0.819	5.000	95.000	115.899	0.123
S4	0.042	0.822	5.000	95.000	115.355	0.125
S5	0.031	0.787	5.000	95.000	118.901	1.367
S6	0.025	0.758	5.000	95.000	122.694	1.978
S7	0.025	0.721	5.000	95.000	129.286	1.812
S8	0.025	0.726	5.000	95.000	128.377	1.813

Internal Reference Calibration, performed Wed Aug 21 12:08:58 2013:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.963	0.984	1.000	0.000

Air Zero Calibration, performed Sun Mar 23 11:47:36 2014:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

PIONEER
Pioneer Energy Services

Company	Anadarko Petroleum Corporation
Well	NRC 4N-8HZ
Field	Wattenberg
County	Weld
State	Colorado