

FORM

2

Rev
08/13

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
Phone: (303) 894-2100 Fax: (303) 894-2109

Document Number:

400579888

APPLICATION FOR PERMIT TO:

☒ Drill
 ☐ Deepen
 ☐ Re-enter
 ☐ Recomplete and Operate

Date Received:

04/29/2014

TYPE OF WELL OIL ☐ GAS ☐ COALBED ☐ OTHER CO2Refilling ☐ZONE TYPE SINGLE ZONE ☒ MULTIPLE ZONES ☐ COMMINGLE ZONES ☐Sidetrack ☐

Well Name: Goodman Point (GP)

Well Number: 27

Name of Operator: KINDER MORGAN CO2 CO LP

COGCC Operator Number: 46685

Address: 17801 HWY 491

City: CORTEZ

State: CO

Zip: 81321

Contact Name: Paul Belanger

Phone: (970)882-2464

Fax: (970)882-5521

Email: Paul_Belanger@kindermorgan.com

RECLAMATION FINANCIAL ASSURANCE

Plugging and Abandonment Bond Surety ID: 20110027

WELL LOCATION INFORMATION

QtrQtr: SWSE Sec: 18 Twp: 36N Rng: 17W Meridian: N

Latitude: 37.373670

Longitude: -108.761870

Footage at Surface: 935 feet FNL/FSL FSL 2105 feet FEL/FWL FEL

Field Name: MCELMO

Field Number: 53674

Ground Elevation: 7080

County: MONTEZUMA

GPS Data:

Date of Measurement: 03/13/2014 PDOP Reading: 5.9 Instrument Operator's Name: Gerald G Huddleston

If well is ☐ Directional ☒ Horizontal (highly deviated) submit deviated drilling plan.
 Footage at Top of Prod Zone: FNL/FSL FSL 2105 FEL 2225 FNL 1096 FWL
 Sec: 18 Twp: 36N Rng: 17W Sec: 18 Twp: 36N Rng: 17W

LOCATION SURFACE & MINERALS & RIGHT TO CONSTRUCT

Surface Ownership: ☒ Fee ☐ State ☐ Federal ☐ IndianThe Surface Owner is: ☐ is the mineral owner beneath the location.

(check all that apply)

☐ is committed to an Oil and Gas Lease.☐ has signed the Oil and Gas Lease.☐ is the applicant.The Mineral Owner beneath this Oil and Gas Location is: ☒ Fee ☐ State ☐ Federal ☐ Indian

The Minerals beneath this Oil and Gas Location will be developed by this Well: Yes

The right to construct the Oil and Gas Location is granted by: Bond

Surface damage assurance if no agreement is in place: Blanket

Surface Surety ID: 20080051

LEASE INFORMATION

Using standard QtrQtr, Sec, Twp, Rng format, describe one entire mineral lease that will be produced by this well (Describe lease beneath surface location if produced. Attach separate description page or map if necessary.)

section 18 36N17W: W1/2NE1/4, E1/2NW1/4, W1/2SE1/4, LOT4, SESW. Section 28 37N17W: N1/2NW1/4; lots 1, 2, 3 NESW (161.82 ac) - see attached leases

Total Acres in Described Lease: 563 Described Mineral Lease is: ☒ Fee ☐ State ☐ Federal ☐ Indian

Federal or State Lease # _____

Distance from Completed Portion of Wellbore to Nearest Lease Line of described lease: 0 Feet

CULTURAL DISTANCE INFORMATION

Distance to nearest:

Building: 4653 Feet

Building Unit: 4653 Feet

High Occupancy Building Unit: 5280 Feet

Designated Outside Activity Area: 5280 Feet

Public Road: 4341 Feet

Above Ground Utility: 3175 Feet

Railroad: 5280 Feet

Property Line: 840 Feet

INSTRUCTIONS:

- All measurements shall be provided from center of the Proposed Well to nearest of each cultural feature as described in Rule 303.a.(5).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit, High Occupancy Building Unit, and Designated Outside Activity Area - as defined in 100-Series Rules.

DESIGNATED SETBACK LOCATION INFORMATION

Check all that apply. This location is within a: ☐ Buffer Zone ☐ Exception Zone ☐ Urban Mitigation Area

- Buffer Zone – as described in Rule 604.a.(2), within 1,000' of a Building Unit
- Exception Zone - as described in Rule 604.a.(1), within 500' of a Building Unit.
- Urban Mitigation Area - as defined in 100-Series Rules.

Pre-application Notifications (required if location is within 1,000 feet of a building unit):

Date of Rule 305.a.(1) Urban Mitigation Area Notification to Local Government: _____

Date of Rule 305.a.(2) Buffer Zone Notification to Building Unit Owners: _____

SPACING and UNIT INFORMATION

Distance from Completed Portion of Wellbore to Nearest Wellbore Permitted or Completed in the same formation: 2700 Feet

Distance from Completed Portion of Wellbore to Nearest Unit Boundary 5280 Feet (Enter 5280 for distance greater than 1 mile.)

Federal or State Unit Name (if appl): MCELMO Unit Number: 47653X

SPACING & FORMATIONS COMMENTS

OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
------------------------	----------------	-------------------------	-------------------------------	--------------------------------------

LEADVILLE	LDVLL			
-----------	-------	--	--	--

DRILLING PROGRAM

Proposed Total Measured Depth: 10868 Feet

Distance to nearest permitted or existing wellbore penetrating objective formation: 2700 Feet (Including plugged wells)

Will a closed-loop drilling system be used? Yes

Is H₂S gas reasonably expected to be encountered during drilling operations at concentrations greater than

or equal to 100 ppm? No (If Yes, attach an H2S Drilling Operations Plan)

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? No

BOP Equipment Type: ☒ Annular Preventor ☒ Double Ram ☒ Rotating Head ☐ None

GROUNDWATER BASELINE SAMPLING AND MONITORING AND WATER WELL SAMPLING

Water well sampling required per Rule 609

DRILLING WASTE MANAGEMENT PROGRAM

Drilling Fluids Disposal: OFFSITE Drilling Fluids Disposal Methods: Recycle/reuse

Cuttings Disposal: OFFSITE Cuttings Disposal Method: Commercial Disposal

Other Disposal Description:

Fluids: Recycle as much as possible; any excess will go to licensed UIC disposal facility. Cuttings are dewatered in a closed loop system and disposed of at a permitted E&P commercial solid waste facility.

Beneficial reuse or land application plan submitted?

Reuse Facility ID: or Document Number:

CASING PROGRAM

Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
CONDUCTOR	20	16	55	0	80	100	80	0
SURF	12+1/4	9+5/8	36	0	2920	1200	2920	0
1ST	8+3/4	7	29&32	0	7803	1900	7803	0
OPEN HOLE	4+3/4		0	7803				7803

☐ Conductor Casing is NOT planned

DESIGNATED SETBACK LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 604.a.(1)A. Exception Zone (within 500' of Building Unit)
- ☐ Rule 604.b.(1)A. Exception Location (existing or approved Oil & Gas Location now within a Designated Setback as a result of Rule 604.a.)
- ☐ Rule 604.b.(1)B. Exception Location (existing or approved Oil & Gas Location is within a Designated Setback due to Building Unit construction after Location approval)
- ☐ Rule 604.b.(2) Exception Location (SUA or site-specific development plan executed on or before August 1, 2013)
- ☐ Rule 604.b.(3) Exception Location (Building Units constructed after August 1, 2013 within setback per an SUA or site-specific development plan)

GREATER WATTENBERG AREA LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 318A.a. Exception Location (GWA Windows).
- ☐ Rule 318A.c. Exception Location (GWA Twinning).

RULE 502.b VARIANCE REQUEST

- ☐ Rule 502.b. Variance Request from COGCC Rule or Spacing Order Number

OTHER LOCATION EXCEPTIONS

Check all that apply:

- ☐ Rule 318.c. Exception Location from Rule or Spacing Order Number _____
- ☐ Rule 603.a.(2) Exception Location (Property Line Setback).

ALL exceptions and variances require attached Request Letter(s). Refer to applicable rule for additional required attachments (e.g. waivers, certifications, SUAs).

OPERATOR COMMENTS AND SUBMITTAL

Comments

This is an APD for the horizontal portion following the drilling and logging of a vertical pilot wellbore; see docnum 400579470. No H2S or salt sections expected in this horizontal wellbore in that those formations having H2S or salt will have already been drilled and cased off.
There are no water wells located within a .5 mile radius of the GP-27 Limit of Disturbance.
A Form 4 will be filed accordingly. No fracking is being planned.
There are no wells within 1500' and no fracking of this well is being planned

This application is in a Comprehensive Drilling Plan _____ CDP #: _____

Location ID: _____

Is this application being submitted with an Oil and Gas Location Assessment application? _____ Yes

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Paul Belanger

Title: Regulatory contractor Date: 4/29/2014 Email: Paul_Belanger@kindermorgan.

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: _____ Director of COGCC Date: _____

Expiration Date: _____

API NUMBER

05

Conditions Of Approval

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

COA Type

Description

Best Management Practices

No BMP/COA Type

Description

1	Planning	A Kinder Morgan Fire Mitigation Plan is currently on file with the Montezuma County Planning Office. Any material not in use that might constitute a fire hazard will be removed a minimum of 25 feet from the wellhead, tanks and separator. Any electrical installations inside the bermed area will comply with API RP 500 classifications and comply with the current national electrical code as adopted by the State of Colorado.
---	----------	---

2	Traffic control	<p>A Road Use Plan, which addresses traffic concerns specific to the GP-27, is currently on file with Montezuma County. The Road Use Plan was produced after consulting with the county Road and Bridge Supervisor.</p> <p>All access roads are fully compliant with local county road standards. Access roads are composed of compacted gravel. In an effort to mitigate dust, magnesium-chloride applications to the road surface are performed at the request of Montezuma County.</p>
3	General Housekeeping	<p>Erosion control barriers, namely fiber wattles, will be placed at the edge of disturbance where necessary. Care will be taken to avoid disturbance outside of the project area unless it is deemed necessary for equipment stability and fire safety.</p> <p>During the construction, drilling, and completion phases, on-site trash dumpsters are emptied regularly by the local waste management company.</p> <p>Steel ranch fencing will be placed around the well head after the well is drilled. Once the well is tied in, the fencing will be removed. The proposed well location will be drilled using a closed loop system and will therefore not use open pits.</p> <p>During drilling and completion operations, safety officers are present on location to ensure that livestock, wildlife, and unauthorized personnel do not enter the location. Following completion, the only items present on the well pad are the well head and aboveground pipeline junction. Additionally, there is no active grazing near the proposed location.</p>
4	Storm Water/Erosion Control	<p>Diversion ditches will be implemented to divert run-on and run-off around the well pad. Compacted earthen berms will also be utilized to control stormwater run-on and runoff.</p> <p>Tackifier will be added to the stored topsoil piles and all slopes to prevent erosion. Stockpiled soils will have slopes not greater than 3:1.</p> <p>Stormwater BMPs will be maintained/amended by Kinder Morgan as site conditions change throughout the construction and reclamation process.</p>
5	Material Handling and Spill Prevention	<p>The use of a closed-loop drilling system will reduce the amount of waste produced and water used during drilling operations. Solid cuttings will be disposed of at a solid waste facility.</p> <p>Water that can no longer be reused or recycled will be disposed of in a Class I disposal well.</p> <p>Sufficiently impervious containment devices will be constructed around any condensate and produced water tanks. The containment devices will be sufficiently impervious to contain any spilled or released material. All containment devices will be inspected at regular intervals and maintained in good condition.</p> <p>Tanks are designed to meet all API 650 guidelines.</p>
6	Dust control	<p>In an effort to mitigate dust, magnesium-chloride applications to the road surface are performed at the request of Montezuma County.</p>
7	Construction	<p>All equipment will be stored within the right-of-way (ROW) area of disturbance. Top soil will be removed to create a level pad for drilling and access road.</p> <p>Vegetation that does not need to be removed will be avoided during construction and removed vegetation will be cut near ground level, leaving the root system intact except where permanent facilities, roads, or ROWs, and wellpads require the complete removal of vegetation.</p>
8	Noise mitigation	<p>During normal operations, the well will remain within COGCC regulations for noise. However, during the construction phase of the project, this standard may be exceeded occasionally.</p>
9	Emissions mitigation	<p>Non-flammable CO₂ will be produced from the Leadville formation and thus green completion per rule 805 (3) does not apply.</p> <p>All CO₂ wells are equipped with a CO₂ leak detection monitor during drilling.</p>

10	Drilling/Completion Operations	<p>Blowout preventer equipment (BOPE) complies with COGCC equipment regulations.</p> <p>Mineral Management certification or Director approved training for blowout prevention has been conducted for at least one person at the well site during drilling operations.</p> <p>Kinder Morgan conducts a BOPE test and files a 24 hour notice (Form 42) at the initial rig-up time, after each casing emplacement, and/or every 30 days.</p> <p>KM standard operating protocol includes a check list for well-site clearance activities when a well is transferred from the Drilling Department to the Operations Department.</p> <p>Adequate blowout prevention equipment is used on all well servicing operations.</p> <p>Backup stabbing valves are used on well servicing operations during reverse circulation and are pressure tested before each well servicing operation using both low-pressure air and high-pressure fluid.</p> <p>No pits are present at the well site.</p>
11	Interim Reclamation	Surface roughening, surface contouring, seeding, and weed control will be employed to facilitate vegetation reestablishment. Tackifier will be added to reclaimed areas.
12	Final Reclamation	All disturbed areas that are not necessary for operational procedures will be restored to at least 80 percent of pre-disturbance vegetative cover.

Total: 12 comment(s)

Attachment Check List

<u>Att Doc Num</u>	<u>Name</u>
400579888	FORM 2 SUBMITTED
400596935	OffsetWellEvaluations Data
400596990	DEVIATED DRILLING PLAN
400596992	DRILLING PLAN
400597001	DIRECTIONAL DATA
400598677	OIL & GAS LEASE
400598678	OIL & GAS LEASE
400605036	PLAT
400605499	OIL & GAS LEASE

Total Attach: 9 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Operator requested form back to draft to make revisions.	5/8/2014 7:23:05 AM
Permit	Is there a lease that covers the NESW and Lot 2? How can distance to lease line be 75 when the lateral is crossing the lease line?	5/6/2014 1:09:27 PM
Permit	Passed completeness.	5/5/2014 9:10:09 AM
Permit	Return to draft: Plugging and Abandonment Bond Surety ID is blank. "None" is checked for BOP type although there are selections made for BOP type.	5/2/2014 2:18:28 PM

Total: 4 comment(s)