

FORM
5A

Rev
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400605971

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 16700
2. Name of Operator: CHEVRON USA INC
3. Address: 6001 BOLLINGER CANYON RD
City: SAN RAMON State: CA Zip: 94583
4. Contact Name: Julie Justus
Phone: (970) 257-6042
Fax: (970) 245-6489
Email: jjustus@chevron.com

5. API Number 05-045-15259-00
6. County: GARFIELD
7. Well Name: SKR
Well Number: 598-25-AV-17
8. Location: QtrQtr: NENW Section: 25 Township: 5S Range: 98W Meridian: 6
9. Field Name: SKINNER RIDGE Field Code: 77548

Completed Interval

FORMATION: WILLIAMS FORK - CAMEO Status: PRODUCING Treatment Type: FRACTURE STIMULATION
Treatment Date: 06/25/2009 End Date: 07/06/2009 Date of First Production this formation: 10/23/2009
Perforations Top: 4938 Bottom: 6159 No. Holes: 171 Hole size: 35/100
Provide a brief summary of the formation treatment: Open Hole: ☐
525,000 gals slurry pumped with 353,742 lbs sand
This formation is commingled with another formation: ☐ Yes ☒ No
Total fluid used in treatment (bbl): 12500 Max pressure during treatment (psi): 5771
Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.43
Type of gas used in treatment: Min frac gradient (psi/ft): 0.75
Total acid used in treatment (bbl): 0 Number of staged intervals: 6
Recycled water used in treatment (bbl): 12500 Flowback volume recovered (bbl):
Fresh water used in treatment (bbl): 0 Disposition method for flowback: RECYCLE
Total proppant used (lbs): 353742 Rule 805 green completion techniques were utilized: ☒
Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 10/25/2009 Hours: 24 Bbl oil: 0 Mcf Gas: 1317 Bbl H2O: 643
Calculated 24 hour rate: Bbl oil: 0 Mcf Gas: 1317 Bbl H2O: 643 GOR:
Test Method: Flowing Casing PSI: 980 Tubing PSI: 510 Choke Size: 32/64
Gas Disposition: FLARED Gas Type: DRY Btu Gas: 1086 API Gravity Oil:
Tubing Size: 2 + 3/8 Tubing Setting Depth: 5757 Tbg setting date: 10/22/2009 Packer Depth:
Reason for Non-Production: NA
Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt
** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

I am filing this Form 5A to correct Monthly Production Report error: "Need Form 5A" for WFCM

Original 5A submitted (Doc #1948207) listed WMFK as producing interval, which included WFCM completion as a common hydrocarbon source, but did not specifically name WFCM.

This Form 5A is intended to correct/replace original Form 5A filed in 2009 (Attached)

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Julie Justus

Title: Regulatory Specialist Date: _____ Email: jjustus@chevron.com
:

Attachment Check List

Att Doc Num **Name**

--	--

Total Attach: 0 Files

General Comments

User Group **Comment** **Comment Date**

--	--	--

Total: 0 comment(s)