COMPANY, ETC. BRIGHT C.OP.
WELL O.J.MILLER 24-24
FIELD WATTENBERG
County WELD
State COLORADO
File

COMPANY BRIGHT & SCHENCK OIL CO.
WELL O.J. MILLER 24-24
FIELD WATTENBERG
COUNTY WELD STATE COLORADO
Other Services

Permanent Datum: G.L. Elev. 4920
Log Measured From: K.B. 12 Ft. Above Perm. Datum
Drilling Measured From: K.B.

Date 7-26-74
Run No. ONE
Type Log GAMMA RAY-ACOUSTIC CEMENT BOND
Depth-Driller 7,560
Depth-Logger 7,556
Bottom Logged Interval 7,556
Top Logged Interval 5,500
Type Fluid in Hole WATER
Salinity, PPM Cl
Density LB/GAL
Level FULL
Max. Rec. Temp. Deg. F 140
Estimated Cement Top 5,500
Time Since Circulation 3 HRS.
Time on Bottom 0600 7-26-74
Unit Number 1420
Recorded By R. HOLLAND
Witnessed By MR. BRIGHT

CASING RECORD
SIZE 4½" WEIGHT 11.6 LB/FT GRADE K-55 FROM SURF. TO 7,560
SIZE 7" WEIGHT 20 LB/FT GRADE K-55 FROM SURF. TO 5,500
SIZE WEIGHT GRADE FROM TO
SIZE WEIGHT GRADE FROM TO

BORE HOLE RECORD
BIT NO. 1 SIZE 6¼" FROM SURF. TO 7,560
BIT NO. SIZE FROM TO

TUBING RECORD
SIZE 2⅜" WEIGHT 4.7 LB/FT GRADE J-55 FROM SURF. TO 7,500

Rig Name & No. UNIT #1
Source of Sample
Rm @ Meas. Temp.
Rmf @ Meas. Temp.
Rmc @ Meas. Temp.
Source of Rmf & Rmc
Rm @ BHT
Time Circ. (Hrs.)
Max. Rec. Temp. Deg. F
Equip. Location

Recorded By R. HOLLAND
Witnessed By MR. BRIGHT

ACOUSTIC CEMENT BOND - GAMMA RAY LOG

O.W.P.

EQUIPMENT DATA

Truck Serial No.	1	Model No. 1420	Dia. 3.375"
Gamma Ray Detector Type	BGO MT.	Length	
Distance T-R Bond Rec.	5'-0"		

Transmitter Frequency 20KC
Receiver to Transmitter Spacing 5 METER
Fluid Density Full

LOGGING DATA

GAMMA RAY

Run No.	Depth From	Depth To	Speed FT/MIN	TC Sec.	Span	Zero	Scale	Gain
1	7,556	5,000	30	1	5.0		2 DIVISIONS	1.9

AMPLITUDE

Zero	Scale	Gain	Delay	Scale
	2 DIVISIONS	1.9	515	5 MV/DIV

V. Time Scale 2.5

CEMENTING DATA:

CEMENT BOND LOG RAN AFTER PRESSURE TESTING WELL TO 5,000#.

GAMMA RAY
API UNITS
TRANSIT TIME
MICROSECONDS
200 | 100

CASING COLLAR LOG

AMPLITUDE
CEMENT BONDING INCREASES
0 | 20
0 | 100

VARIABLE DENSITY or SEISMIC SPECTRUM
TIME
MICROSECONDS
0 | 100
1.0 | 11.0

CASING COLLAR

006100
006200
006300
006400
006500
006600
006700
006800
006900
007000

CASING COLLAR

TOTAL TIME

RADIATION INTENSITY INCREASES
GAMMA RAY
MICROSECONDS
TRANSIT TIME
DEPTH

FREE CASING
ACOUSTIC ZERO
CEMENT BONDING INCREASES
CEMENT BOND

MICROSECONDS
VDL or SEISMIC

REPEAT SECTION

REPEAT SECTION

Company	LYN ENERGY CORPORATION	Drillers T.D.	7,560
Well	O.J. MILLER 24-24	Log R.D.	7,556
Field	WATTENBERG	Log T.D.	7,553
County	WELD	Elevations:	
State	COLORADO	K.B. 4925	D.F. 4924 G.L. 4913