
Schlumberger
Platform Express
Three Detector Lithology
Density Neutron
Array Induction Imager
Array Sonic
Gamma Ray
Caliper
Bit Size
Mud Type: Water Based Mud
Density: 10.0 lbm/gal
Resistivity: 0.04 ohmm @ 75 degF
Source of Sample: Flowline
RM @ BHT: 0.03 @ 150 degF
Time Since Circulation: 24 hrs
Max Rec Temp: 150 degF
Equipment: SEA-1
Location: Offshore Area
Rig: Semi-Submersible
Witness: Operator Rep
Service Order: 1234567
Run: One
Depth Datum: Rotary Table
Elevation: 0 ft
Permanent Datum: Mean Sea Level
Log Measured From: Rotary Table
Drilling Measured From: Rotary Table
Logging Date: 15-Mar-2024
Run Number: One
Depth Driller: 12,500 ft
Schlumberger Depth: 12,498 ft
Bottom Logged Interval: 12,496 ft
Top Logged Interval: 1,200 ft
Casing Driller Size @ Depth: 13 3/8 in @ 1,200 ft
Casing Schlumberger: 1,198 ft
Bit Size: 12 1/4 in
Type Fluid in Hole: Water Based Mud
Density / Viscosity: 10.0 lbm/gal / 45 s
PH / Fluid Loss: 9.5 / 4.2 cm3
Source of Sample: Flowline
Rm @ Measured Temp: 0.03 @ 150 degF
Rmf @ Measured Temp: 0.02 @ 150 degF
Rmc @ Measured Temp: 0.05 @ 150 degF
Source Rmf / Rmc: Measured / Measured
Rm


Effective Length
Effective Length
Effective Length