

| HSR-Wise 16-15  |               |        |              |                       | Existing Cement |
|-----------------|---------------|--------|--------------|-----------------------|-----------------|
|                 |               |        |              |                       | New Cement      |
|                 |               | API:   | 05-123-17026 |                       | SX              |
| Existing        |               | WINS:  | 76878        |                       | SH              |
|                 |               |        |              | Planned               | NB              |
|                 |               |        |              | Welded Cap            | CD              |
| TOC             | 10            | 20 SX  |              |                       | JS              |
|                 |               |        |              | 80 CIBP               | Fox Hills       |
|                 |               |        |              |                       | Mud             |
|                 |               |        |              | 400 TOC in 8-5/8"     |                 |
| btm sfcsg & BOC | 607           | 330 SX |              |                       |                 |
| FH mrkr         |               | 1,079  |              | 1,180 cut csg         |                 |
|                 |               |        |              | 1,280 stub plug       |                 |
|                 |               |        |              |                       |                 |
|                 |               |        |              | 4,020 TOC in 4-1/2"   |                 |
|                 |               |        |              | 4,120 top perfs       |                 |
|                 |               |        |              | 4,150 CICR            |                 |
| SX top          | 4,319         | 200 SX |              | 4,520 BOC & btm perfs |                 |
| SH btm          | 4,598         |        |              |                       |                 |
|                 |               |        |              |                       |                 |
| SH btm          | 5,037         |        |              |                       |                 |
|                 |               |        |              |                       |                 |
| TOC             | 6,237         | 20 SX  |              | 6,560 TOC in 4-1/2"   |                 |
| CIBP            | 6,870         |        |              | 6,870 BOC in 4-1/2"   |                 |
| CIBP            | 6,951         |        |              |                       |                 |
|                 |               |        |              |                       |                 |
| NB top          | 7,059         |        |              |                       |                 |
| NB Perfs        | 7,060 - 7,201 |        |              |                       |                 |
| NB btm          |               |        |              |                       |                 |
| CD top          |               |        |              |                       |                 |
| CD Perfs        | 7,346 - 7,360 |        |              |                       |                 |
| CD btm          |               |        |              |                       |                 |
| btm pdcn csg    | 7,484         |        |              |                       |                 |
| BOC             | 7,505         |        |              |                       |                 |
| Surface Csg:    | 8-5/8"        |        |              |                       |                 |
| Production Csg: | 4-1/2"        |        |              |                       |                 |