

# CEMENT JOB REPORT



<b>CUSTOMER</b> WHITING PETROLEUM CORP			<b>DATE</b> 25-JUN-14		<b>F.R. #</b> 10011078057		<b>SERV. SUPV.</b> Anthony J Staples					
<b>LEASE &amp; WELL NAME</b> RAZOR #26L-3504B - API 05123379880000			<b>LOCATION</b> 26-10N-58W				<b>COUNTY-PARISH-BLOCK</b> Weld Colorado					
<b>DISTRICT</b> Brighton			<b>DRILLING CONTRACTOR RIG #</b>				<b>TYPE OF JOB</b> Surface					
<b>SIZE &amp; TYPE OF PLUGS</b>		<b>LIST-CSG-HARDWARE</b>		<b>MECHANICAL BARRIERS</b>		<b>MD</b>	<b>TVD</b>	<b>HANGER TYPES</b>		<b>MD</b>	<b>TVD</b>	
Cement Plug, Rubber, Top 9-5/8 in		Centralizer, with Pins, 9-5/8 in										
		Float Shoe 9-5/8 - 8rd										
		Float Collar, Auto Fill, 9-5/8 - 8rd										
<b>MATERIALS FURNISHED BY BJ</b>				<b>LAB REPORT NO.</b>				<b>PHYSICAL SLURRY PROPERTIES</b>				
								<b>SACKS OF CEMENT</b>	<b>SLURRY WGT PPG</b>	<b>SLURRY YLD FT<sup>3</sup></b>	<b>WATER GPS</b>	<b>PUMP TIME HR:MIN</b>
Fresh Water				0				8.34	0	0	00:00	15
Type III + Adds				719				14.5	1.40	6.81	01:30	179.50
Mud				0				8.8	0	0	00:00	112.87
Available Mix Water 400 Bbl.				Available Displ. Fluid 400 Bbl.				<b>TOTAL</b>		307.37		116.54
<b>HOLE</b>			<b>TBG-CSG-D.P.</b>						<b>COLLAR DEPTHS</b>			
<b>SIZE</b>	<b>% EXCESS</b>	<b>DEPTH</b>	<b>ID</b>	<b>OD</b>	<b>WGT.</b>	<b>TYPE</b>	<b>MD</b>	<b>TVD</b>	<b>GRADE</b>	<b>SHOE</b>	<b>FLOAT</b>	<b>STAGE</b>
13.5	35	1550	8.921	9.625	36	CSG	1534	1534	J-55	1534	1488	0
<b>LAST CASING</b>			<b>PKR-CMT RET-BR PL-LINER</b>			<b>PERF. DEPTH</b>			<b>TOP CONN</b>		<b>WELL FLUID</b>	
<b>ID</b>	<b>OD</b>	<b>WGT</b>	<b>TYPE</b>	<b>MD</b>	<b>TVD</b>	<b>BRAND &amp; TYPE</b>	<b>DEPTH</b>	<b>TOP</b>	<b>BTM</b>	<b>SIZE</b>	<b>THREAD</b>	<b>WGT.</b>
						No Packer				9.625	8RD	8.8
<b>DISPL. VOLUME</b>		<b>DISPL. FLUID</b>		<b>CAL. PSI</b>	<b>CAL. MAX PSI</b>	<b>OP. MAX</b>	<b>MAX TBG PSI</b>		<b>MAX CSG PSI</b>		<b>MIX WATER</b>	
<b>VOLUME</b>	<b>UOM</b>	<b>TYPE</b>	<b>WGT.</b>	<b>BUMP PLUG</b>	<b>TO REV.</b>	<b>SQ. PSI</b>	<b>RATED</b>	<b>Operator</b>	<b>RATED</b>	<b>Operator</b>		
115	BBLS	Mud	8.8	440	0	0	0	0	2816	2000	frac Tank	
<b>Circulation Prior to Job</b>												
Circulated Well: Rig <input checked="" type="checkbox"/> BJ <input type="checkbox"/>						Circulation Time: 1			Circulation Rate: 4 BPM			
Mud Density In: 8.6 LBS/GAL Mud Density Out: 8.6 LBS/GAL						PV & YP Mud In: 0			PV & YP Mud Out: 0			
Gas Present: NO <input checked="" type="checkbox"/> YES <input type="checkbox"/> Units:						Solids Present at End of Circulation: NO <input checked="" type="checkbox"/> YES <input type="checkbox"/>						
<b>Displacement And Mud Removal</b>												
Displaced By: Rig <input type="checkbox"/> BJ <input checked="" type="checkbox"/>						Amount Bled Back After Job: .5 BBLS						
Returns During Job: <input type="checkbox"/> NONE <input type="checkbox"/> PARTIAL <input checked="" type="checkbox"/> FULL						Method Used to Verify Returns: Visual						
Cement Returns at Surface: <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO						Were Returns Planned at Surface: <input type="checkbox"/> NO <input checked="" type="checkbox"/> YES						
Pipe Movement: <input type="checkbox"/> ROTATION <input type="checkbox"/> RECIPROICATION <input checked="" type="checkbox"/> NONE <input type="checkbox"/> UNABLE DUE TO STUCK PIPE												
Centralizers: <input type="checkbox"/> NO <input checked="" type="checkbox"/> YES						Quantity: 15		Type: <input type="checkbox"/> BOW <input type="checkbox"/> RIGID				
Job Pumped Through: <input type="checkbox"/> CHOKE MANIFOLD <input type="checkbox"/> SQUEEZE MANIFOLD <input checked="" type="checkbox"/> MANIFOLD <input type="checkbox"/> NO MANIFOLD												
<b>Plugs</b>												
Number of Attempts by BJ: 0 Competition: 0						Wiper Balls Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES Quantity:						
Plug Catcher Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES						Parabow Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES						
Was There a Bottom: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES						Top of Plug: 0 FT			Bottom of Plug: 0 FT			
<b>Squeezes (Update Original Treatment Report for Primary Job)</b>												
BLOCK SQUEEZE <input type="checkbox"/> SHOE SQUEEZE <input type="checkbox"/> TOP OF LINER SQUEEZE <input type="checkbox"/> PLANNED <input type="checkbox"/> UNPLANNED <input type="checkbox"/>												
Liner Packer: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES						Bond Log: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES		PSI Applied: 0 Fluid Weight: 0 LBS/GAL				
<b>Casing Test (Update Original Treatment Report for Primary Job)</b>												
Casing Test Pressure: 1250 PSI With 8.6 LBS/GAL Mud						Time Held: 00 Hours 15 Minutes						
<b>EXPLANATION: TROUBLE SETTING TOOL, RUNNING CSG, ETC. PRIOR TO CEMENTING: none</b>												
<b>PRESSURE/RATE DETAIL</b>						<b>EXPLANATION</b>						

# CEMENT JOB REPORT



## Shoe Test (Update Original Treatment Report for Primary Job)

Depth Drilled out of Shoe: 0 FT Target EMW: 0 LBS/GAL Actual EMW: 0 LBS/GAL  
 Number of Times Tests Conducted: 0 Mud Weight When Test was Conducted: 0 LBS/GAL

Problems Before Job (I.E. Running Casing, Circulating Well, ETC)  
 None

Problems During Job (I.E. Lost Returns, Equipment Failure, Bulk Delivery, Foaming, ETC)  
 None

Problems After Job (I.E. Gas at Surface, Float Equipment Failed, ETC)  
 None

PRESSURE/RATE DETAIL						EXPLANATION	
TIME HR:MIN.	PRESSURE - PSI		RATE BPM	Bbl. FLUID PUMPED	FLUID TYPE	SAFETY MEETING: BJ CREW <input checked="" type="checkbox"/> CO. REP. <input checked="" type="checkbox"/>	
	PIPE	ANNULUS				TEST LINES	2948 PSI
						CIRCULATING WELL - RIG	<input checked="" type="checkbox"/> BJ <input type="checkbox"/>
17:28	0	0	0	0	N/A	Arrive on Location ( 120 Miles Finishing Up Casing )	
17:30	0	0	0	0	N/A	Spot Trucks	
17:41	0	0	0	0	N/A	Pre-Rig Safety Meeting	
18:55	0	0	0	0	N/A	Pre-Job Safety Meeting	
19:17	25	0	.8	2	H2O	Load Lines	
19:20	2948	0	0	0	H2O	Pressure Test	
19:23	151	0	4.6	15	H2O	Fresh Water Spacer	
19:30	105	0	3.6	171	CMT	Batch, Weigh, and Pump 14.5# Type III Cement + .08 lbs/sks Static Free + 1% CaCl + .25 lbs/sks Cello Flake	
20:29	0	0	0	0	N/A	Shut Down to Drop Plug	
20:37	0	0	0	0	H2O	Plug Away	
20:37	712	0	5.6	85	MUD	Displace	
21:52	670	0	4.8	15	MUD	Rate Change	
21:58	610	0	2.5	15	H2O	Rate Change	
21:05	1250	0	0	0	H2O	Bumped Plug	
21:05	1250	0	0	0	H2O	Started Casing test at 1250 psi Per Customer	
21:20	0	0	0	0	N/A	Bled Off Pressure ( .5 Bbls Back)	

BUMPED PLUG	PSI TO BUMP PLUG	TEST FLOAT EQUIP.	BBL.CMT RETURNS/ REVERSED	TOTAL BBL. PUMPED	PSI LEFT ON CSG	SPOT TOP OUT CEMENT	Service Supervisor Signature:
<input checked="" type="checkbox"/> Y <input type="checkbox"/> N	705	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N	46	301	0	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N	

