

EXCELL SERVICES LLC
LUNDGREN 22 08-5N-46W

100-4020
YUMA
AARON CARRASCO
8/20/2014

DESCRIPTION OF JOB EVENTS

[illegible]

Notes:

TD@ (511) FT

SET @ (506) FT

7 INCH CASING = 20 LBS/FT

140 FT SHOE

CEMENT TYPE = 50/50 POZ 3% CCA = MIXED & PUMPED (240 sks)

15.2 LBS/GAL= 1.07 YIELD = 4.20 GAL/SKS

DISPLACED= (18.8) BBL


BRIS TO PIT = (20)

X

Work Preformed	
----------------	--

Just 284

X 8-20-14



Bison Oil Well Cementing
Two Cement Long String

Customer
Well Name

Agustus Energy Resources
JUNDGREN FARMS 22-08-5N-46W

Date 8/23/2014
INVOICE # 13158
LOCATION Yuma
FOREMAN Aaron Carrasco
Treatment Report Page 2

DESCRIPTION OF JOB EVENTS

Fety Meeting	6:56am	Displace 1			Displace 2			Displace 3			Displace 4			Displace 5		
	2am	BBLS	Time	PSI	BBLS	Time	PSI	BBLS	Time	PSI	BBLS	Time	PSI	BBLS	Time	PSI
RCULATE	6:59am	0	7:48am	50	0			0			0			0		
op Plug		10	7:51am	190	10			10			10			10		
7:48am		20	7:53am	330	20			20			20			20		
		30	7:56am	480	30			30			30			30		
		45.4	8:05am	1010	40			40			40			40		
M & P		50			50			50			50			50		
Time	Sacks	60			60			60			60			60		
7:12am	237	70			70			70			70			70		
		80			80			80			80			80		
		90			90			90			90			90		
		100			100			100			100			100		
		110			110			110			110			110		
		120			120			120			120			120		
ad mixed bbls	68	130			130			130			130			130		
ad % Excess	161%	140			140			140			140			140		
ad Sacks	237	150			150			150			150			150		
Notes:																
il mixed bbls	11.2	Ran (66)TS, 4.5", 10.5#, MEAS W/ SHOE (2893), SET @ (2899), PBTD @ (2853), RIG TD @ (2916)														
il % Excess	0%	CMT W/ (237) SX LEAD, 50/50 POZ, 12% GEL, 2% CACL, YLD 2.21, 12PPG														
il Sacks	75	CMT W/ (75) SX TAIL, 50/50 POZ, 3% CACL, 25% FLO-CEL, YLD 1.33, 13.8PPG														
		CIRC (0) BBLS TO PIT														
ital Sacks	312															
ater Temp	67 f															
l Returns	0															