NABORS COMPLETION & PRODUCTION SERVICES CO.

DUAL INDUCTION LOG

Company MULL DRILLING COMPANY, INC.
Well SCHERLER #1-10
Field
County KIOWA
State COLORADO

Company MULL DRILLING COMPANY, INC.
Well SCHERLER #1-10
Field
County KIOWA State COLORADO
Location: API # : 05-061-06893-00
849' FNL & 952' FEL
SEC 10 TWP 17S RGE 45W

Other Services: CDL/CNL/PE MEL/SON

Permanent Datum GROUND LEVEL Elevation 4148
Log Measured From KELLY BUSHING 11' A.G.L.
Drilling Measured From KELLY BUSHING

Elevation
K.B. 4159
D.F. 4157
G.L. 4148

Date	8/28/14		
Run Number	ONE		
Depth Driller	5450		
Depth Logger	5457		
Bottom Logged Interval	5455		
Top Log Interval	00		
Casing Driller	341		
Casing Logger	340		
Bit Size	7.875		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 1800 PPM	
Density / Viscosity	9.3/60		
pH / Fluid Loss	9.5/7.2		
Source of Sample	FLOWLINE		
Rm @ Meas. Temp	1.10 @ 87F		
Rmf @ Meas. Temp	.82 @ 87F		
Rmc @ Meas. Temp	1.32 @ 87F		
Source of Rmf / Rmc	MEASURED		
Rm @ BHT	.74 @ 129F		
Time Circulation Stopped	2 HOURS		
Time Logger on Bottom			
Maximum Recorded Temperature	129F		
Equipment Number	4010		
Location	HAYS, KS.		
Recorded By	JASON CAPPELLUCCI		
Witnessed By	PHIL ASKEY		

<<< Fold Here >>>

Comments

NABORS COMPLETION & PRODUCTION SERVICES
785-628-6395
THANK YOU FOR YOUR BUSINESS
BRANDON, CO. - 10 NORTH - WEST INTO

NABORS COMPLETION & PRODUCTION SERVICES CO.

MAIN SECTION

SERVICES CO.

Database File: 25860pe.db
Dataset Pathname: pass3.3
Presentation Format: _dil2
Dataset Creation: Thu Aug 28 06:10:47 2014 by Calc Open-Cased 090629
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray (GAPI)	150
-100	SP (mV)	100

0	RLL3 (Ohm-m)	50
0	RILD (Ohm-m)	50
1000	CILD (mmho/m)	0
50	RILD X10 (Ohm-m)	500
50	RLL3 X10 (Ohm-m)	500




450
500
550
600
650
700
750
800
850
900
950


1000
1050
1100
1150
1200
1250
1300
1350
1400
1450
1500


1550
1600
1650
1700
1750
1800
1850
1900
1950
2000
2050


2100
2150
2200
2250
2300
2350
2400
2450
2500
2550
2600


2650
2700
2750
2800
2850
2900
2950
3000
3050
3100
3150


3200
3250
3300
3350
3400
3450
3500
3550
3600
3650
3700


3750
3800
3850
3900
3950
4000
4050
4100
4150
4200
4250


4300
4350
4400
4450
4500
4550
4600
4650
4700
4750
4800


4850
4900
4950
5000
5050
5100
5150
5200
5250
5300
5350



0	Gamma Ray (GAPI)	150
-100	SP (mV)	100

0	RLL3 (Ohm-m)	50
0	RILD (Ohm-m)	50
1000	CILD (mmho/m)	0
50	RILD X10 (Ohm-m)	500
50	RLL3 X10 (Ohm-m)	500

NABORS
COMPLETION & PRODUCTION SERVICES CO.

ANHYDRITE

Database File: 25860pe.db
Dataset Pathname: pass3.2
Presentation Format: _dil
Dataset Creation: Thu Aug 28 05:33:03 2014 by Calc Open-Cased 090629
Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000



0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000

NABORS
COMPLETION & PRODUCTION SERVICES CO.

MAIN SECTION

Database File: 25860pe.db
Dataset Pathname: pass3.1
Presentation Format: _dil
Dataset Creation: Thu Aug 28 05:23:19 2014 by Calc Open-Cased 090629
Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




3750
3800
3850
3900


3950
4000
4050
4100
4150


4200
4250
4300
4350


4400
4450
4500
4550
4600


4650
4700
4750
4800


4850
4900
4950
5000


5050
5100
5150
5200
5250



0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000

NABORS
COMPLETION & PRODUCTION SERVICES CO.

REPEAT SECTION

Database File:	25860pe.db
Dataset Pathname:	pass2.1
Presentation Format:	_dil
Dataset Creation:	Thu Aug 28 05:11:33 2014 by Calc Open-Cased 090629
Charted by:	Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000





Calibration Report

Database File: 25860pe.db
Dataset Pathname: pass2.1
Dataset Creation: Thu Aug 28 05:11:33 2014 by Calc Open-Cased 090629

Dual Induction Calibration Report

Serial-Model:	PROBE8-DILG
Surface Cal Performed:	Sun Aug 17 08:09:53 2014
Downhole Cal Performed:	Mon Jul 28 11:08:27 2008
After Survey Verification Performed:	Mon Jul 28 11:08:27 2008

Surface Calibration

	Readings			References			Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	0.015	0.648	V	0.000	400.000	mmho/m	620.000	-2.000
Medium	0.029	0.796	V	0.000	464.000	mmho/m	590.000	-16.000
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.017	0.657	V	0.000	400.000	mmho/m	625.153	-10.619
Medium	0.016	0.757	V	0.000	464.000	mmho/m	625.992	-9.739

Downhole Calibration

	Readings			References			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	2.011	405.777	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	7.590	503.393	mmho/m	1.000	0.000
LL3		7.500	V		1500.000	Ohm-m		
		0.000	V		20.000	Ohm-m		

-7.200	V		3800.000	mmho-m	

After Survey Verification

	Readings			Targets			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		
		0.000	Ohm-m		0.000	Ohm-m		
		1.000	mmho-m		1.000	mmho-m		

Litho Density Calibration Report

Serial: 002 Model: PRB

Master Calibration — Performed Wed Feb 26 14:40:29 2014

	Background	Magnesium	Aluminum	Sandstone	
Window 1	844.3	7247.0	2284.1	7908.3	cps
Window 2	800.5	6081.1	1985.0	6521.4	cps
Window 3	688.8	3783.7	1363.3	3972.6	cps
Window 4	191.6	192.1	191.7	191.4	cps
Long Space	0.0	5280.6	1184.5	5720.9	cps
Short Space	1.1	1287.1	882.6	1385.1	cps
Rho		1.7100	2.5900	1.3800	g/cc
Pe		0.0000	2.5700	1.5500	

Rib Angle	: 45.8	Rib Slope	: 1.030	Density/Spine Ratio	: 0.571
Spine Angle	: 75.8	Spine Slope	: 3.962	Spine Intercept	: -19.8

Before Survey Verification — Performed Wed Dec 31 18:00:00 1969

Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps
Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

After Survey Verification — Performed Wed Dec 31 18:00:00 1969

Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps
Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

Compensated Neutron Calibration Report

Serial Number: 6I
Tool Model: G

CALIBRATION

Detector	Readings		Target		Normalization
Short Space	1.00	cps	1.00	cps	1.0000
Long Space	1.00	cps	1.00	cps	1.0000

PRE-SURVEY VERIFICATION

	Detector	Readings		Measured		Target	
1)	Short Space		cps				
	Long Space		cps		pu		pu
2)	Short Space		cps				
	Long Space		cps		pu		
3)	Short Space		cps				
	Long Space		cps		pu		

POST-SURVEY VERIFICATION

	Detector	Readings		Measured		Target	
1)	Short Space		cps				
	Long Space		cps		pu		pu
2)	Short Space		cps				
	Long Space		cps		pu		pu
3)	Short Space		cps				
	Long Space		cps		pu		pu

Gamma Ray Calibration Report

Serial Number:	GR6	
Tool Model:	OPEN	
Performed:	Sun Aug 17 15:23:09 2014	
Calibrator Value:	150.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	276.0	cps
Sensitivity:	0.7000	GAPI/cps