

Contents

Tools Run using Tender Energy Services
Tender Energy Services
Measuring Mineral Fusion at Depth via Pressure Ship Record

Client
Well
Location
Field
Rig
Date
Time
Depth
Pressure
Temperature
Density
Viscosity
Flow Rate
Gamma Ray
Resistivity
Porosity
Permeability
Saturation
Lithology
Formation
Casing
Cement
Perforations
Completion
Production
Reservoir
Fluid
Gas
Oil
Water
Sand
Shale
Limestone
Dolomite
Anhydrite
Salt
Coal
Basement
Overburden
Interval
Zone
Marker
Log
Run
Pass
Curve
Scale
Header
Footer
Page
Total Pages
Operator
Service Company
Engineer
Supervisor
Witness
Customer
Contractor
Subcontractor
Vendor
Supplier
Manufacturer
Model
Serial Number
Calibration
Verification
Quality Control
Quality Assurance
Health
Safety
Environment
Security
Emergency
Evacuation
Muster
Drill
Incident
Accident
Near Miss
Hazard
Risk
Mitigation
Permit
Authorization
Approval
Rejection
Revision
Version
Date
Time
Depth
Pressure
Temperature
Density
Viscosity
Flow Rate
Gamma Ray
Resistivity
Porosity
Permeability
Saturation
Lithology
Formation
Casing
Cement
Perforations
Completion
Production
Reservoir
Fluid
Gas
Oil
Water
Sand
Shale
Limestone
Dolomite
Anhydrite
Salt
Coal
Basement
Overburden
Interval
Zone
Marker
Log
Run
Pass
Curve
Scale
Header
Footer
Page
Total Pages
Operator
Service Company
Engineer
Supervisor
Witness
Customer
Contractor
Subcontractor
Vendor
Supplier
Manufacturer
Model
Serial Number
Calibration
Verification
Quality Control
Quality Assurance
Health
Safety
Environment
Security
Emergency
Evacuation
Muster
Drill
Incident
Accident
Near Miss
Hazard
Risk
Mitigation
Permit
Authorization
Approval
Rejection
Revision
Version





Calibration Report

Database File: 13456.db
Dataset Pathname: pass4
Dataset Creation: Fri Feb 07 02:54:31 2014 by Log 0

Gamma Ray Calibration Report

Serial Number:	111205	
Tool Model:	probe 2.75	
Performed:	Wed Feb 05 11:09:02 2014	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	Base	
Tool Model:	Probe	
Calibration Casing Diameter:	4.500	in
Calibration Depth:	300.590	ft

Master Calibration, performed Fri Feb 07 02:29:22 2014:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.012	0.924	0.000	62.200	68.231	-0.835
CAL	0.012	1.008				
5'	0.012	0.970	0.000	62.200	64.944	-0.787
SUM						
S1	0.012	1.028	0.000	100.000	98.495	-1.222
S2	0.012	0.941	0.000	100.000	107.611	-1.291
S3	0.012	0.845	0.000	100.000	120.108	-1.459
S4	0.012	0.807	0.000	100.000	125.754	-1.532
S5	0.012	0.822	0.000	100.000	123.442	-1.498
S6	0.012	0.879	0.000	100.000	115.346	-1.404
S7	0.012	0.989	0.000	100.000	102.418	-1.241
S8	0.012	1.030	0.000	100.000	98.230	-1.191

Internal Reference Calibration, performed Wed Feb 05 12:39:32 2014:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.012	1.008	1.000	0.000

Air Zero Calibration, performed Wed Feb 05 12:23:21 2014:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000