Company: K. P. KAUFFMAN COMPANY
Well: CARY ANN-ENG UNIT # 41
Field: SPINDLE
County: WELD
State: COLORADO

JW WIRELINE SURVEY

CEMENT BOND
GAMMA RAY
COLLAR CORRELATION LOG

Company: K. P. KAUFFMAN COMPANY
Well: CARY ANN-ENG UNIT # 41
Field: SPINDLE
County: WELD
State: COLORADO

Permanent Datum: GROUND LEVEL
Elevation: 4,731 Ft.
Log Measured From: KB 10 Ft. Above Permanent Datum
Drilling Measured From: KB

| | | |
|---|---|---|
| Date | 12-Dec-07 | |
| Run Number | ONE | |
| Depth Driller | 7,140 Ft. | |
| Depth Logger | 7,140 Ft. | |
| Bottom Logged Interval | 7,140 Ft. | |
| Top Logged Interval | SURFACE | |
| Type Fluid in Hole | WATER | |
| Salinity, PPM Cl | | |
| Density | 8.4 LB/GAL | |
| Level | FULL | |
| Max Rec. Temp. Deg. F | 120 | |
| Equipment Number | 3 | |
| Location | 1-5N-65W | |
| Recorded By | JAMES | |
| Witnessed By | MR. KAUFFMAN | |

| Run | Bit | From | To | Size | Wt. | Grade | From | To |
|---|---|---|---|---|---|---|---|---|
| ONE | | SURFACE | 7,140 Ft. | 4.5 | 11.6 | | SURFACE | 7,140 Ft. |

| Run | Tool | Type | Serial No. | O.D. | Max. Rec. Temp. | Equipment No. | Location |
|---|---|---|---|---|---|---|---|
| ONE | CBL | | | 3.625 | | | |
| | GR | | | 3.625 | | | |
| | CCL | | | 3.625 | | | |

Fluid Data

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

LOG CORRELATED TO GROUND LEVEL

THANK YOU FOR CHOOSING J-W WIRELINE

Database File: cary walking unit # 1_LL6.db
Dataset Pathname: pass1
Dataset Creation: Fri Dec 14 08:27:27 2007
Dataset Creator: Thu Dec 20 12:00:27 2010 by Log Std Casualhole 08121
Charted by: Depth in Feet scaled 1:240

Collar Locator
50 Gamma Ray (CoAPI) 150
200 TT-PT (usec) 160

0 Amplified Amplitude (mV) 30,000
0 T Amplitude (mV) 500
Variable Density 1200




Collar Locator
50 Gamma Ray (CoAPI) 150
200 TT-PT (usec) 160

0 Amplified Amplitude (mV) 30,000
0 T Amplitude (mV) 500
Variable Density 1200