


Schlumberger
Gamma Ray (GAPI)
Caliper (in)
Resistivity (ohmm)
Density (g/cm3)
Neutron Porosity (v/v)
Sonic (us/ft)
Interpretation
Lithology
Porosity
Saturation
Permeability
Pay Flag
Depth (m)

Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	Base	
Tool Model:	Probe	
Calibration Casing Diameter:	7.000	in
Calibration Depth:	125.428	ft

Master Calibration, performed Fri Jul 11 07:03:42 2014:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.012	0.861	0.000	62.200	68.765	-0.142
CAL	0.012	1.015				
5'	0.012	0.934	0.000	62.200	69.986	-0.412
SUM						
S1	0.005	0.969	0.000	100.000	81.899	-0.839
S2	0.012	0.953	0.000	100.000	83.330	-0.963
S3	0.012	0.843	0.000	100.000	83.316	-0.950
S4	0.012	0.764	0.000	100.000	81.695	-0.990
S5	0.012	0.747	0.000	100.000	83.110	-0.998
S6	0.012	0.760	0.000	100.000	82.923	-0.792
S7	0.012	0.821	0.000	100.000	82.231	-0.858
S8	0.012	0.887	0.000	100.000	81.498	-0.569

Internal Reference Calibration, performed Tue Nov 21 12:42:07 2006:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.012	1.015	1.000	0.000

Air Zero Calibration, performed Thu Apr 24 09:23:40 2008:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000