
Schlumberger
Platform Express
Three Detector Lithology
Array Induction Imager Tool
Hostile Accelerator Porosity Sonde
Natural Gamma Ray Tool
Mud Type: WBM
Density: 9.2 lbm/gal
Viscosity: 40 s
Chlorides: 1000 ppm
Fluid Loss: 4 cm3
Source: Rmf Rmc
Rm @ BHT 0.1 @ 70 degF
Rmf @ BHT 0.1 @ 70 degF
Rmc @ BHT 0.1 @ 70 degF
Max Recorded Temperature
Circulation Stopped
Logger On Bottom
Unit Number
Location
Recorded By
Witnessed By
Run Number
Service Order
Permanent Datum
Elevation
Log Measured From
Drilling Measured From
Elevation
Kelly Bushing
Derrick Floor
Ground Level



PIONEER
Pioneer Energy Services

MAIN PASS 0 PSI

PIONEER
Pioneer Energy Services

REPEAT PASS 0 PSI

Database File: anadarko premium tuhms tuhms b1b8.db
Dataset Pathname: pass5
Dataset Creation: Thu Sep 25 08:41:55 2014 by Log 7.0 81
Charted by: Depth in Feet scaled 1:240

9 Collar Locator -1 LTEN 0 Amplitude Amplitude (mV) 10 200 Variable Density 1200
0 Gamma Ray (GAPI) 200 0 (ft ZDNS) 0 Amplitude (mV) 100

PIONEER
Pioneer Energy Services

REPEAT PASS 0 PSI

Database File: anadarko premium tuhms tuhms b1b8.db
Dataset Pathname: pass8
Dataset Creation: Thu Sep 25 10:04:32 2014 by Log 7.0 81

Calibration Report

Gamma Ray Calibration Report

Serial Number:	51013
Tool Model:	probe 2.75
Performed:	Thu Feb 23 11:03:07 2012
Calibrator Value:	1400.0 GAPI
Background Reading:	26.8 cps
Calibrator Reading:	1120.0 cps
Sensitivity:	0.9000 GAPI/cps

Temperature Calibration Report

Serial Number:	51013
Tool Model:	probe 2.75
Performed:	Sun Jun 13 13:33:21 1993

Reference	Reading	
Low Reference:	0.00 degF	0.00 cps
High Reference:	1.00 degF	1.00 cps
Gain:	1.00	
Offset:	0.00	
Delta Spacing:		

Cement Bond Log Calibration Report

Serial Number:	950215
Tool Model:	Probe
Performed:	Thu Sep 25 09:28:43 2014

Depth:	223.0	ft
Casing Diameter:	4.5	in

	T Spacing	R Spacing	
Signal Zero:	1	0	mV
Calibrated Amplitude:	83	83	mV
Reading at Signal Zero:	0.0125244	0.0127690	V
Reading in Free Pipe:	1.12451	1.33548	V
Gain:	39.748	61.1321	
Offset:	0.0150434	-0.780580	