Copyright © 2014 Schlumberger. All rights reserved.
This work contains the confidential and proprietary trade secrets of Schlumberger and may not be copied or stored in any form or by any means, electronic or mechanical, including photocopying and recording, or by any information storage or retrieval system, except with the express written permission of Schlumberger. Any copy of this work authorized by Schlumberger must reproduce this boilerplate notice in full. The recipient is also subject to the terms and conditions of the applicable Schlumberger agreement.

Mnemonic
Description
Value
Units
Mnemonic
Description
Value
Units

Remote access pressure while flowing ?? ? psig
Flow rate at choke ?? ? bbl/d
Tubing pressure at surface Flowing Pressure ?? ? psig
Wellhead temperature ?? ? degF

Schlumberger

Remote access pressure while flowing ?? ? psig
Flow rate at choke ?? ? bbl/d
Tubing pressure at surface Flowing Pressure ?? ? psig
Wellhead temperature ?? ? degF

Well: 15/9-F-11 T2
Survey: Survey #1
Survey Type: Definitive Survey
Survey Date: 2014.07.06
Tool Type: MWD+IFR1+MS
Start MD: 0.00 m
End MD: 4,172.00 m
Company: Statoil
Declination: 0.00 deg
Grid Convergence: 0.00 deg
Total Correction: 0.00 deg
Grid Type: True
Local Coordinates Referenced To: Well Head
Vertical Section Azimuth: 0.00 deg
Vertical Section Origin: 0.00 m, 0.00 m
Magnetic Model: BGGM2014
Magnetic Declination: 0.00 deg
Dip: 0.00 deg
Magnetic Field Strength: 0.00 nT
Magnetic Declination Date: 2014.07.06

Survey Calculation Method: Minimum Curvature
Vertical Section Azimuth: 0.00 deg
Vertical Section Origin: 0.00 m, 0.00 m
Horizontal Reference Pt: Well Head
Vertical Reference Pt: Rig Floor
Rig on Slot: 15/9-F-11 T2
Rig Name: Transocean Leader
Rig Floor Elevation: 0.00 m
Ground Level Elevation: 0.00 m
Magnetic Declination: 0.00 deg
Grid Convergence: 0.00 deg
Total Correction: 0.00 deg
Local Coordinates Referenced To: Well Head
Grid Type: True
Comments: Definitive Survey

Survey	Depth (m)	Inclination	Azimuth	True Vertical Depth	+N/-S (m)	+E/-W (m)	DLS (deg/30m)
				0.00	0.00	0.00	
	0.00	0.00		0.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	100.00	0.00		100.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	200.00	0.00		200.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	300.00	0.00		300.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	400.00	0.00		400.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	500.00	0.00		500.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	600.00	0.00		600.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	700.00	0.00		700.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	800.00	0.00		800.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	900.00	0.00		900.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,000.00	0.00		1,000.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,100.00	0.00		1,100.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,200.00	0.00		1,200.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,300.00	0.00		1,300.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,400.00	0.00		1,400.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,500.00	0.00		1,500.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,600.00	0.00		1,600.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,700.00	0.00		1,700.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,800.00	0.00		1,800.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	1,900.00	0.00		1,900.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,000.00	0.00		2,000.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,100.00	0.00		2,100.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,200.00	0.00		2,200.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,300.00	0.00		2,300.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,400.00	0.00		2,400.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,500.00	0.00		2,500.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,600.00	0.00		2,600.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,700.00	0.00		2,700.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,800.00	0.00		2,800.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	2,900.00	0.00		2,900.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,000.00	0.00		3,000.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,100.00	0.00		3,100.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,200.00	0.00		3,200.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,300.00	0.00		3,300.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,400.00	0.00		3,400.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,500.00	0.00		3,500.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,600.00	0.00		3,600.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,700.00	0.00		3,700.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,800.00	0.00		3,800.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	3,900.00	0.00		3,900.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	4,000.00	0.00		4,000.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	4,100.00	0.00		4,100.00	0.00	0.00	0.00
				0.00	0.00	0.00	
	4,172.00	0.00		4,172.00	0.00	0.00	0.00

Schlumberger
Private
Survey Calculation Method: Minimum Curvature
Vertical Section Azimuth: 0.00 deg
Vertical Section Origin: 0.00 m, 0.00 m
Horizontal Reference Pt: Well Head
Vertical Reference Pt: Rig Floor
Rig on Slot: 15/9-F-11 T2
Rig Name: Transocean Leader
Rig Floor Elevation: 0.00 m
Ground Level Elevation: 0.00 m
Magnetic Declination: 0.00 deg
Grid Convergence: 0.00 deg
Total Correction: 0.00 deg
Local Coordinates Referenced To: Well Head
Grid Type: True
Comments: Definitive Survey

Well: 15/9-F-11 T2
Survey: Survey #1
Survey Type: Definitive Survey
Survey Date: 2014.07.06
Tool Type: MWD+IFR1+MS
Start MD: 0.00 m
End MD: 4,172.00 m
Company: Statoil
Declination: 0.00 deg
Grid Convergence: 0.00 deg
Total Correction: 0.00 deg
Grid Type: True
Local Coordinates Referenced To: Well Head
Vertical Section Azimuth: 0.00 deg
Vertical Section Origin: 0.00 m, 0.00 m
Magnetic Model: BGGM2014
Magnetic Declination: 0.00 deg
Dip: 0.00 deg
Magnetic Field Strength: 0.00 nT
Magnetic Declination Date: 2014.07.06

Survey Calculation Method: Minimum Curvature
Vertical Section Azimuth: 0.00 deg
Vertical Section Origin: 0.00 m, 0.00 m
Horizontal Reference Pt: Well Head
Vertical Reference Pt: Rig Floor
Rig on Slot: 15/9-F-11 T2
Rig Name: Transocean Leader
Rig Floor Elevation: 0.00 m
Ground Level Elevation: 0.00 m
Magnetic Declination: 0.00 deg
Grid Convergence: 0.00 deg
Total Correction: 0.00 deg
Local Coordinates Referenced To: Well Head
Grid Type: True
Comments: Definitive Survey

Well: 15/9-F-11 T2
Survey: Survey #1
Survey Type: Definitive Survey
Survey Date: 2014.07.06
Tool Type: MWD+IFR1+MS
Start MD: 0.00 m
End MD: 4,172.00 m
Company: Statoil
Declination: 0.00 deg
Grid Convergence: 0.00 deg
Total Correction: 0.00 deg
Grid Type: True
Local Coordinates Referenced To: Well Head
Vertical Section Azimuth: 0.00 deg
Vertical Section Origin: 0.00 m, 0.00 m
Magnetic Model: BGGM2014
Magnetic Declination: 0.00 deg
Dip: 0.00 deg
Magnetic Field Strength: 0.00 nT
Magnetic Declination Date: 2014.07.06

Survey Calculation Method: Minimum Curvature
Vertical Section Azimuth: 0.00 deg
Vertical Section Origin: 0.00 m, 0.00 m
Horizontal Reference Pt: Well Head
Vertical Reference Pt: Rig Floor
Rig on Slot: 15/9-F-11 T2
Rig Name: Transocean Leader
Rig Floor Elevation: 0.00 m
Ground Level Elevation: 0.00 m
Magnetic Declination: 0.00 deg
Grid Convergence: 0.00 deg
Total Correction: 0.00 deg
Local Coordinates Referenced To: Well Head
Grid Type: True
Comments: Definitive Survey



Calibration Report

Database File C:\Interim\Data\Augusta Energy Resources,LLC_Franson #2-33 #NATM_20120123\1_20140101
Dataset Pathname Run 1
Dataset Creation Mon Oct 13 15:33:55 2014 by Log Data Caswell 110582

Dual Induction Calibration Report

Serial Model 1010-PSI
Surface Test Performed

	Readings			References			
Loop	Air	Loop		Air	Loop	m	b
Deep	0.000	1.000		0.000	1.000 mmho/m	0.500	23.000
Medium	0.000	1.000		0.000	1.000 mmho/m	0.460	27.000

Compensated Density Calibration Report

Serial Model PTI-PSI
Weekly Calibration Performed Wed Aug 20 14:19:31 2014

Master Calibration

	Density		Far Detector	Near Detector
Magnesium	1.700 g/cc		6320.65	9557.33 cps
Aluminum	2.680 g/cc		1748.13	5405.96 cps
	Size		Reading	
Small Ring	in			
Medium Ring	in			
Large Ring	in			

Compensated Neutron Calibration Report

Serial Number	853
Tool Model	PSI

CALIBRATION

Detector	Readings	Target	Normalization
Short Space	1.00 cps	1.00 cps	1.0000
Long Space	1.00 cps	1.00 cps	1.0000

PRE-SURVEY VERIFICATION

	Detector	Readings	Measured	Target
1)	Short Space	cps		
	Long Space	cps	pu	pu
2)	Short Space	cps		
	Long Space	cps	pu	
3)	Short Space	cps		
	Long Space	cps	pu	

POST-SURVEY VERIFICATION

	Detector	Readings	Measured	Target
1)	Short Space	cps		
	Long Space	cps	pu	pu
2)	Short Space	cps		
	Long Space	cps	pu	pu
3)	Short Space	cps		
	Long Space	cps	pu	pu

Gamma Ray Calibration Report

Serial Number	43
Tool Model	PSI
Performed	Tue Oct 18 17:42:20 2011
Calibrator Value	275.61 GAPI
Background Reading	52.0 cps
Calibrator Reading	340.0 cps
Sensitivity	0.6000 GAPI/cps

Log Variables

Database C:\Interim\Data\Augusta Energy Resources,LLC_Franson #2-33 #NATM_
Dataset Run 1 Pathname
Presented Along Bottom

SSTOR	MPORSL	FLUIDDEN	MATRIXDEN	DTSHIFT	SHDENFRM	SNDENFRM
Ok	Limestone	1	2.71	0	nonsalty 0	nonsalty 0

CASEOD	PERFS	TDEPTH	BOTTOMP	BOREID
in 4	ft 0	ft 0	degF 0	in 7.875