
Schlumberger
Array Induction Imager Tool
Gamma Ray
Caliper
Bit Size
Deep Induction
Medium Induction
Shallow Induction
Spherically Focused Resistivity
Rt
Rxo
Rm
Rmf
Rmc
Delta Rho
Neutron Porosity
Photoelectric Factor
Density Porosity
Density Correction
Pe
Rhob
Drho
Gamma Ray (API)
Caliper (in)
Bit Size (in)
Deep Resistivity (ohmm)
Medium Resistivity (ohmm)
Shallow Resistivity (ohmm)
Spherically Focused Resistivity (ohmm)
Neutron Porosity (dec)
Density Porosity (dec)
Photoelectric Factor (b/e)
Density (g/cm3)
Density Correction (g/cm3)
Delta Rho
Rt
Rxo
Rm
Rmf
Rmc
Pe
Rhob
Drho
Neutron Porosity
Density Porosity
Gamma Ray
Caliper
Bit Size
Deep Induction
Medium Induction
Shallow Induction
Spherically Focused Resistivity
Rt
Rxo
Rm
Rmf
Rmc
Delta Rho
Neutron Porosity
Photoelectric Factor
Density Porosity
Density Correction
Pe
Rhob
Drho
Gamma Ray (API)
Caliper (in)
Bit Size (in)
Deep Resistivity (ohmm)
Medium Resistivity (ohmm)
Shallow Resistivity (ohmm)
Spherically Focused Resistivity (ohmm)
Neutron Porosity (dec)
Density Porosity (dec)
Photoelectric Factor (b/e)
Density (g/cm3)
Density Correction (g/cm3)
Delta Rho




Calibration Report

Database File: cbl noble muirhead 1-4.db
Dataset Pathname: pass1
Listened Location: Tue Aug 26 07:44:07 2014 by Log SICM-120430

Gamma Ray Calibration Report

Type / Serial: Probe2TGdg / 110785

SHOP CALIBRATION — Fri Nov 08 09:38:36 2013

| | Counts/Sec | Gain | Offset | Jig | Units |
|---|---|---|---|---|---|
| Background | 0.0 | | | | cps |
| Calibrator | 1.0 | | | | cps |
| | | 0.4400 | | | GAPI/cps |

PRIMARY VERIFICATION

| | | | | |
|---|---|---|---|---|
| Background | 0.0 | | | cps |
| Calibrator | 0.0 | | | cps |
| Difference | | | 0.0 | GAPI |

BEFORE SURVEY VERIFICATION

| | | | | |
|---|---|---|---|---|
| Background | 0.0 | | | cps |
| Calibrator | 0.0 | | | cps |
| Difference | | | 0.0 | GAPI |

AFTER SURVEY VERIFICATION

| | | | | |
|---|---|---|---|---|
| Background | 0.0 | | | cps |
| Calibrator | 0.0 | | | cps |
| Difference | | | 0.0 | GAPI |

Cement Bond Log Calibration Report

| | |
|---|---|
| Serial Number: | 110802 |
| Tool Model: | Probe2TDqtbel |
| Performed: | Tue Aug 26 07:33:11 2014 |
| Depth: | 929.467 ft |
| Casing Diameter: | 4.5 in |

| | 3' Spacing | 5' Spacing | |
|---|---|---|---|
| Signal Zero: | 0.7 | 0 | mV |
| Calibrated Amplitude: | 61.1061 | 61.1061 | mV |
| Reading at Signal Zero: | -0.0073613 | -0.0070172 | V |
| Reading in Free Pipe: | 2.49475 | 2.2658 | V |
| Gain: | 32.1915 | 36.7449 | |
| Offset: | 0.886264 | 0.205951 | |