

Company: Omimex Petroleum Inc

Well: Fiddler Peak Ranch 4-3-5-45

Field: Ballyneal

County: Yuma State: Colorado

Platform Express

Array Induction

with Linear Correlation

County: Yuma

Field: Ballyneal

Location: NWNW Sec3 T5N R45W

Well: Fiddler Peak Ranch 4-3-5-45

Company: Omimex Petroleum Inc

Location:

NWNW Sec3 T5N R45W  
SHL: 433' FNL, 603' FWL

Elev.: K.B. 3798.00 ft  
G.L. 3792.00 ft  
D.F. 3797.00 ft

Permanent Datum:  
Log Measured From:  
Drilling Measured From:

Ground Level  
Kelly Bushing  
Kelly Bushing

Elev.: 6.00 ft  
above Perm.Datum

API Serial No.  
05-125-12124

Section: 3

Township: 5N

Range: 45W

Logging Date	15-Nov-2014				
Run Number	ONE				
Depth Driller	2725.00 ft				
Schlumberger Depth	2726.00 ft				
Bottom Log Interval	2726.00 ft				
Top Log Interval	494.00 ft				
Casing Driller Size @ Depth	7 in @ 493.00 ft				
Casing Schlumberger	494 ft				
Bit Size	6.25 in				
Type Fluid In Hole	Water				
MUD	Density	8.8 lbm/gal	29 s		
	Fluid Loss	3.2 cm3	8		
	Source of Sample				
	RM @ Meas Temp	0.23 ohm.m @ 86 degF			
RMF @ Meas Temp	0.16 ohm.m @ 86 degF				
RMC @ Meas Temp	0.31 ohm.m @ 86 degF				
Source RMF	RMC	Calculated	Calculated		
RM @ BHT	RMF @ BHT	0.19 @ 103	0.14 @ 103		
Max Recorded Temperatures			103 degF		
Circulation Stopped	Time	15-Nov-2014 11:45:00			
Logger on Bottom	Time	15-Nov-2014 16:39:12			
Unit Number	Location:	9108	Fort Morgan		
Recorded By	B Makinson				
Witnessed By	Paul Dekaye				

Disclaimer

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

Contents

1. Header
2. Disclaimer
3. Contents
4. Well Sketch
5. Borehole Size/Casing/Tubing Record
6. Remarks and Equipment Summary
7. Depth Summary
8. ONE 2" Induction

8.1 Integration Summary

8.2 Software Version

8.3 Composite Summary

8.4 Log ( Import of Kerr McGee 2in Induction )

8.5 Parameter Listing
9. ONE 5" Induction


9.1 Integration Summary

9.2 Software Version

9.3 Composite Summary

- 9.4 Log ( EMD 5in Induction )
- 9.5 Parameter Listing
- 10. ONE 5" Induction Repeat Analysis
  - 10.1 Composite Summary
  - 10.2 EMD 5in Induction RA
- 11. Calibration Report
- 12. Tail

Well Sketch






Borehole Size/Casing/Tubing Record

Bit						
Bit Size ( in )	6.25					
Top Driller ( ft )	0					
Top Logger ( ft )	0					
Bottom Driller ( ft )	2725					
Bottom Logger ( ft )	2726					
Casing						
Size ( in )	7					
Weight ( lbm/ft )	20					
Inner Diameter ( in )	6.456					
Grade	J55					
Top Driller ( ft )	0					
Top Logger ( ft )	0					
Bottom Driller ( ft )	493					
Bottom Logger ( ft )	494					

Remarks and Equipment Summary

ONE: Toolstring				ONE: Remarks	
Equip name	Length	MP name	Offset	First run in the well.	
LEH-QT	51.57			Toolstring run as per tool sketch.	
LEH-QT				No bowspring used to eccenter HGNS as per	
DTC-H	48.65			Limestone matrix, MDEN: 2.71	
ECH-KC		CTEM	47.75	Neutron corrections applied: Hole size,	
DTC-H		HV	0.00	Cement volume calculated assuming 4.5"	
AH-184[2]	45.65	ToolStatus	45.65	Down log stretch correction: 0.26 ft.	
		TelStatus	45.65	Caliper check in casing within 0.1" tolerance.	
AH-184[1]	43.65			Mud resistivity measured from AIT AMF.	
GPIT-F	41.65			TD: 2726 ft, CSG: 498 ft.	
GPIH-B		GPIT-F Incl	40.23		
DHRU-F		ometer			
GPIC-F					
HGNS-H:4810	37.65	GPIT	0.00		
HGNH		Temperature	37.62		
NSR-F:5215		GR	36.91		
NPV-N					
HACCZ-H:5955					





Depth Summary			
	ONE		
Depth Measuring Device			
Type	IDW-JA		
Serial Number	6431		
Calibration Date	07-Apr-2014		


Channel	Source	Sampling
---------	--------	----------

AT10	AIT-M:AMIS:AMIS	3in
CALI	HDRS-H:HRCC-H:HRCC-H	1in
GR	HGNS-H:HGNS-H:HGNS-H	6in
ICV	Borehole	6in
SP	AIT-M:AMIS:AMIS	6in
TENS	WLWorkflow	6in
TIME_1900	WLWorkflow	0.1in

TIME\_1900 - Time Marked every 60.00 (s)














Gamma Ray Backup		
Spontaneous Potential (SP) AIT-M		
-160	mV	40
Caliper (CALI) HDRS-H		
4	in	14
Gamma Ray (GR) HGNS-H		
0	gAPI	200

Array Induction Two Foot Resistivity A10 (AT10) AIT-M		
0	ohm.m	10
Array Induction Two Foot Resistivity A10 (AT10) AIT-M		
0	ohm.m	50

Cable Tension (TENS)		
10000	lbf	0

ICV - Integrated Cement Volume every 100.00 (ft3)  
 ICV - Integrated Cement Volume every 10.00 (ft3)  
 TIME\_1900 - Time Marked every 60.00 (s)

Description: AIT Basic Log Two Format: Log ( Import of Kerr McGee 2in Induction ) Index Scale: 2 in per 100 ft Index Unit: ft Index Type: Measured  
 Depth Creation Date: 15-Nov-2014 18:16:29

Channel Processing Parameters				
Parameter	Description	Tool	Value	Unit
ABHM	Array Induction Borehole Correction Mode	AIT-M	Compute Standoff	
ACDE	Array Induction Casing Detection Enable	AIT-M	No	
ASTA	Array Induction Tool Standoff	AIT-M	1	in
BARI	Barite Mud Presence Flag	Borehole	No	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Open	
BS	Bit Size	WLSESSION	6.25	in
CALI_SHIFT	CALI Supplementary Offset	HDRS-H	0	in
CBLO	Casing Bottom (Logger)	WLSESSION	494	ft
CDEN	Cement Density	HGNS-H	2	g/cm3
CSODDRL	Casing Outer Diameter - Zoned along driller depths	WLSESSION	7	in

DFD	Drilling Fluid Density	Borehole	8.8	lbm/gal
FCD	Future Casing (Outer) Diameter	WLSESSION	4.5	in
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	CALI	
GRSE	Generalized Mud Resistivity Selection, from Measured or Computed Mud Resistivity	Borehole	AMF	
SOCO	Standoff Correction Option	HGNS-H	Yes	
SPDR	SP Drift Per Foot	AIT-M	0	mV/ft

Tool Control Parameters				
Parameter	Description	Tool	Value	Unit
MAX_LOG_SPEED	Toolstring Maximum Logging Speed	WLSESSION	3600	ft/h
ONE				
5" Induction				

Integration Summary				
Output Channel(s)	Output Description	Input Parameter	Output Value	Unit
ICV	Integrated Cement Volume	GCSE_UP_PASS, FCD	249.86	ft3
IHV	Integrated Hole Volume	GCSE_UP_PASS	497.6	ft3

Software Version				
Acquisition System			Version	
MaxWell			4.0.9163.3000	
Application Patch			Patch-SP-10767_26570-4.0.9163.3001	
Computation	Description			Version
Borehole	Borehole Ensemble provides common Borehole Parameters and Channels			4.0.9469.3000
Tool Elements	Description		Software Version	Firmware Version
HRCC-H	HILT High-Resolution Control Cartridge, 150 degC		4.0.9575.3000	2.0
HGNS-H	HILT Gamma-Ray and Neutron Sonde, 150 degC		4.0.9575.3000	2.0
AMIS	Array Induction Sonde - M		4.0.9535.3000	1

Pass Summary									
Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
ONE	Log[4]:Up	Up	38.39 ft	2736.62 ft	15-Nov-2014 5:00:13 PM	15-Nov-2014 5:50:10 PM	ON	0.00 ft	No
All depths are referenced to toolstring zero									

Log	Company:Omimex Petroleum Inc			Well:Fiddler Peak Ranch 4-3-5-45			ONE: Log[4]:Up:S002		
-----	------------------------------	--	--	----------------------------------	--	--	---------------------	--	--

Description: AIT Basic Log Two    Format: Log ( EMD 5in Induction )    Index Scale: 5 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 15-Nov-2014 18:16:31

Channel	Source	Sampling
AT10	AIT-M:AMIS:AMIS	3in
AT20	AIT-M:AMIS:AMIS	3in
AT30	AIT-M:AMIS:AMIS	3in
AT60	AIT-M:AMIS:AMIS	3in
AT90	AIT-M:AMIS:AMIS	3in
CALI	HDRS-H:HRCC-H:HRCC-H	1in
GR	HGNS-H:HGNS-H:HGNS-H	6in
ICV	Borehole	6in
IHV	Borehole	6in
SP	AIT-M:AMIS:AMIS	6in
TENS	WLWorkflow	6in



—IHV - Integrated Hole Volume every 10.00 (ft3)



—IHV - Integrated Hole Volume every 100.00 (ft3)



—ICV - Integrated Cement Volume every 10.00 (ft3)


—ICV - Integrated Cement Volume every 100.00 (ft3)


TIME\_1900 - Time Marked every 60.00 (s)








































TIME\_1900 - Time Marked every 60.00 (s)


ICV - Integrated Cement Volume every 100.00 (ft3)

ICV - Integrated Cement Volume every 10.00 (ft3)

— ICV - Integrated Cement Volume every 10.00 (ft3)									
— IHV - Integrated Hole Volume every 10.00 (ft3)									
Description: AIT Basic Log Two    Format: Log ( EMD 5in Induction )    Index Scale: 5 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 15-Nov-2014 18:16:31									
Channel Processing Parameters									
Parameter	Description				Tool		Value		Unit
ABHM	Array Induction Borehole Correction Mode				AIT-M		Compute Standoff		
ACDE	Array Induction Casing Detection Enable				AIT-M		No		
ASTA	Array Induction Tool Standoff				AIT-M		1		in
BARI	Barite Mud Presence Flag				Borehole		No		
BHS	Borehole Status (Open or Cased Hole)				Borehole		Open		
BS	Bit Size				WLSESSION		6.25		in
CALI_SHIFT	CALI Supplementary Offset				HDRS-H		0		in
CBLO	Casing Bottom (Logger)				WLSESSION		494		ft
CDEN	Cement Density				HGNS-H		2		g/cm3
CSODDRL	Casing Outer Diameter - Zoned along driller depths				WLSESSION		7		in
DFD	Drilling Fluid Density				Borehole		8.8		lbm/gal
FCD	Future Casing (Outer) Diameter				WLSESSION		4.5		in
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes				Borehole		BS		
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes				Borehole		CALI		
GRSE	Generalized Mud Resistivity Selection, from Measured or Computed Mud Resistivity				Borehole		AMF		
SOCO	Standoff Correction Option				HGNS-H		Yes		
SPDR	SP Drift Per Foot				AIT-M		0		mV/ft
Tool Control Parameters									
Parameter	Description				Tool		Value		Unit
MAX_LOG_SPEED	Toolstring Maximum Logging Speed				WLSESSION		3600		ft/h
ONE									
5" Induction Repeat Analysis									
Pass Summary									
Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
ONE	Log[3]:Up	Up	2270.67 ft	2738.64 ft	15-Nov-2014 4:47:03 PM	15-Nov-2014 4:55:23 PM	ON	0.26 ft	No
ONE	Log[4]:Up	Up	38.39 ft	2736.62 ft	15-Nov-2014 5:00:13 PM	15-Nov-2014 5:50:10 PM	ON	0.00 ft	No
All depths are referenced to toolstring zero									
Log	Company:Omimex Petroleum Inc				Well:Fiddler Peak Ranch 4-3-5-45				
ONE: Log[3]:Up:S002									
Description: AIT Basic Log Two    Format: EMD 5in Induction RA    Index Scale: 5 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 15-Nov-2014 18:16:32									
— IHV - Integrated Hole Volume every 10.00 (ft3)									
— IHV - Integrated Hole Volume every 100.00 (ft3)									
TIME_1900 - Time Marked every 60.00 (s)									
— ICV - Integrated Cement Volume every 10.00 (ft3)									
— ICV - Integrated Cement Volume every 100.00 (ft3)									
						Main To Repeat			
						Repeat To Main			








Main To Repeat

Repeat To Main

Caliper (CALI) HDRS-H

4 in 14



Main To Repeat

Repeat To Main

Array Induction Two Foot Resistivity A90 (AT90) AIT-M

0.2 ohm.m 2000

Main To Repeat		
Repeat To Main		
Gamma Ray (GR) HGNS-H		
200	gAPI	400
Main To Repeat		
Repeat To Main		
Gamma Ray (GR) HGNS-H		
0	gAPI	200

Main To Repeat		
Repeat To Main		
Array Induction Two Foot Resistivity A10 (AT10) AIT-M		
0.2	ohm.m	2000
Main To Repeat		
Repeat To Main		
Array Induction Two Foot Resistivity A60 (AT60) AIT-M		
0.2	ohm.m	2000
Main To Repeat		
Repeat To Main		
Array Induction Two Foot Resistivity A30 (AT30) AIT-M		
0.2	ohm.m	2000
Main To Repeat		
Repeat To Main		
Array Induction Two Foot Resistivity A20 (AT20) AIT-M		
0.2	ohm.m	2000

└─ICV - Integrated Cement Volume every 100.00 (ft3)

└─ICV - Integrated Cement Volume every 10.00 (ft3)

└TIME\_1900 - Time Marked every 60.00 (s)

└─IHV - Integrated Hole Volume every 100.00 (ft3)

└─IHV - Integrated Hole Volume every 10.00 (ft3)

Description: AIT Basic Log Two    Format: EMD 5in Induction RA    Index Scale: 5 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 15-Nov-2014 18:16:32

Calibration Report							
AIT-M (Array Induction Tool - M) Calibration - Run ONE							
Primary Equipment :							
File code for AIT-MA Sonde Tool Element			AMIS		181		
Auxiliary Equipment :							
AITM Rm/SP Bottom Nose			AMRM		181		
AIT Sonde Calibration - Test Loop Gain							
Master (EEPROM):		23:01:59 22-Sep-2014					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Test Loop Gain - 0		Master	1.000	0.950	1.041	1.050	
Test Loop Phase - 0	deg	Master	0	-3.000	1.805	3.000	
Test Loop Gain - 1		Master	1.000	0.950	1.017	1.050	
Test Loop Phase - 1	deg	Master	0	-3.000	0.902	3.000	
Test Loop Gain - 2		Master	1.000	0.950	1.017	1.050	
Test Loop Phase - 2	deg	Master	0	-3.000	0.392	3.000	
Test Loop Gain - 3		Master	1.000	0.950	1.016	1.050	
Test Loop Phase - 3	deg	Master	0	-3.000	0.089	3.000	
Test Loop Gain - 4		Master	1.000	0.950	1.009	1.050	
Test Loop Phase - 4	deg	Master	0	-3.000	0.141	3.000	
Test Loop Gain - 5		Master	1.000	0.950	0.991	1.050	
Test Loop Phase - 5	deg	Master	0	-3.000	-0.110	3.000	
Test Loop Gain - 6		Master	1.000	0.950	0.998	1.050	
Test Loop Phase - 6	deg	Master	0	-3.000	0.235	3.000	
Test Loop Gain - 7		Master	1.000	0.950	1.010	1.050	

Test Loop Phase - 7	deg	Master	0	-3.000	-0.080	3.000
---------------------	-----	--------	---	--------	--------	-------

## AIT Sonde Calibration - Sonde Error Correction








Master (EEPROM):		23:01:59 22-Sep-2014						
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit		
Sonde Error Correction Real - 0	mS/m	Master	-----	-231.000	-113.093	119.000		
Sonde Error Correction Quad - 0		Master	-----	-2250.000	114.931	2250.000		
Sonde Error Correction Real - 1	mS/m	Master	-----	114.000	157.599	204.000		
Sonde Error Correction Quad - 1		Master	-----	-625.000	-170.942	625.000		
Sonde Error Correction Real - 2	mS/m	Master	-----	66.000	115.105	156.000		
Sonde Error Correction Quad - 2		Master	-----	-350.000	-99.364	350.000		
Sonde Error Correction Real - 3	mS/m	Master	-----	39.000	49.447	89.000		
Sonde Error Correction Quad - 3		Master	-----	-250.000	2.279	250.000		
Sonde Error Correction Real - 4	mS/m	Master	-----	15.000	26.217	35.000		
Sonde Error Correction Quad - 4		Master	-----	-63.000	-3.708	63.000		
Sonde Error Correction Real - 5	mS/m	Master	-----	4.000	10.870	24.000		
Sonde Error Correction Quad - 5		Master	-----	-50.000	21.802	50.000		
Sonde Error Correction Real - 6	mS/m	Master	-----	5.000	9.914	15.000		
Sonde Error Correction Quad - 6		Master	-----	-30.000	2.857	30.000		
Sonde Error Correction Real - 7	mS/m	Master	-----	-5.000	-1.286	5.000		
Sonde Error Correction Quad - 7		Master	-----	30.000	1.520	30.000		

AIT Mud Calibration	Mud Calibration Gain
1	1

Master (EEPROM): 23:01:59 22-Sep-2014							
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Coarse Gain		Master	1.000	0.800	0.847	1.200	
Fine Gain		Master	1.000	0.800	0.816	1.200	

Time	Task	Technician	Notes
08:00	Arrival & Safety Briefing	John Doe	Weather: Clear, 75°F
08:15	Equipment Check	Jane Smith	All tools present
08:30	Site Inspection	Mike Johnson	Location confirmed
08:45	Client Meeting	Sarah Lee	Project scope discussed
09:00	Task Assignment	David Kim	Team briefed on goals
09:15	Work Commencement	Emily White	Initial setup complete
09:30	Progress Update	Chris Brown	On schedule
09:45	Problem Solving	Alex Green	Minor issue resolved
10:00	Client Check-in	Mia Black	Feedback positive
10:15	Task Completion	Noah Gray	Final inspection
10:30	Site Cleanup	Olivia Blue	Area tidied
10:45	Equipment Storage	Liam Red	Tools secured
11:00	Departure	Ava Yellow	Final report filed

Master (EEPROM):		23:01:59 22-Sep-2014		Before (Measured):		23:24:18 08-Jan-2015	
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Thru Cal Mag - 0	V	Master	----	0.366	0.575	0.854	
		Before	----	0.366	0.575	0.854	
		Before-Master	----	----	0.000	----	
Thru Cal Phase - 0	deg	Master	----	137.000	-169.442	-103.000	
		Before	----	137.000	-167.318	-103.000	
		Before-Master	----	----	2.124	----	
Thru Cal Mag - 1	V	Master	----	0.762	1.178	1.778	
		Before	----	0.762	1.178	1.778	
		Before-Master	----	----	0.000	----	
Thru Cal Phase - 1	deg	Master	----	136.000	-170.544	-104.000	
		Before	----	136.000	-168.418	-104.000	
		Before-Master	----	----	2.126	----	
Thru Cal Mag - 2	V	Master	----	0.372	0.584	0.868	
		Before	----	0.372	0.585	0.868	
		Before-Master	----	----	0.001	----	
Thru Cal Phase - 2	deg	Master	----	132.000	-174.186	-108.000	
		Before	----	132.000	-172.060	-108.000	
		Before-Master	----	----	2.126	----	
Thru Cal Mag - 3	V	Master	----	0.420	0.660	0.980	
		Before	----	0.420	0.660	0.980	
		Before-Master	----	----	0.000	----	
Thru Cal Phase - 3	deg	Master	----	131.000	-174.965	-109.000	
		Before	----	131.000	-172.837	-109.000	
		Before-Master	----	----	2.128	----	
Thru Cal Mag - 4	V	Master	----	0.804	1.233	1.876	
		Before	----	0.804	1.233	1.876	
		Before-Master	----	----	0.000	----	
Thru Cal Phase - 4	deg	Master	----	125.000	178.761	-115.000	
		Before	----	125.000	-179.101	-115.000	
		Before-Master	----	----	-357.862	----	
Thru Cal Mag - 5	V	Master	----	1.176	1.795	2.744	
		Before	----	1.176	1.795	2.744	
		Before-Master	----	----	0.000	----	
Thru Cal Phase - 5	deg	Master	----	122.000	177.104	-118.000	
		Before	----	122.000	179.246	-118.000	
		Before-Master	----	----	2.142	----	

Thru Cal Mag - 6	V	Master Before Before-Master	----- ----- -----	1.176 1.176 -----	1.794 1.795 0.001	2.744 2.744 -----	
Thru Cal Phase - 6	deg	Master Before Before-Master	----- ----- -----	121.000 121.000 -----	177.111 179.253 2.142	-119.000 -119.000 -----	
Thru Cal Mag - 7	V	Master Before Before-Master	----- ----- -----	0.846 0.846 -----	1.294 1.295 0.001	1.974 1.974 -----	
Thru Cal Phase - 7	deg	Master Before Before-Master	----- ----- -----	115.000 115.000 -----	176.348 178.542 2.194	-125.000 -125.000 -----	
SPA Zero	mV	Master Before Before-Master	  -----	-50.000 -50.000 -----	0.145 0.142 -0.003	50.000 50.000 -----	
SPA Plus	mV	Master Before Before-Master	  -----	941.000 941.000 -----	992.483 992.329 -0.154	1040.000 1040.000 -----	
Temperature Zero	V	Master Before Before-Master	  -----	-0.050 -0.050 -----	0.000 0.000 0.000	0.050 0.050 -----	
Temperature Plus	V	Master Before Before-Master	  -----	0.870 0.870 -----	0.919 0.919 0.000	0.960 0.960 -----	

Company:	Omimex Petroleum Inc	Schlumberger
Well:	Fiddler Peak Ranch 4-3-5-45	
Field:	Ballyneal	
County:	Yuma	
State:	Colorado	
Platform Express		
Array Induction		
with Linear Correlation		