



## Survey Report

<b>Company:</b>	EnCana Oil & Gas (USA) Inc	<b>Local Co-ordinate Reference:</b>	Well Drieth 1E-6H-A368
<b>Project:</b>	DJ Wattenberg	<b>TVD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Site:</b>	S6-T3N-R68W (Zisch/Drieth)	<b>MD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Well:</b>	Drieth 1E-6H-A368	<b>North Reference:</b>	True
<b>Wellbore:</b>	Hz	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	SURVEYS	<b>Database:</b>	USA EDM 5000 Multi Users DB

<b>Project</b>	DJ Wattenberg		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	Colorado Northern Zone		

Site		S6-T3N-R68W (Zisch/Drieth)			
Site Position:		Northing:	1,333,692.14 ft	Latitude:	40.248510
From:	Lat/Long	Easting:	3,124,995.76 ft	Longitude:	-105.052220
Position Uncertainty:	0.0 ft	Slot Radius:	13.200 in	Grid Convergence:	0.29 °

Well	Drieth 1E-6H-A368					
Well Position	+N/-S	0.0 ft	Northing:	1,337,923.39 ft	Latitude:	40.260070
	+E/-W	0.0 ft	Easting:	3,128,901.18 ft	Longitude:	-105.038150
Position Uncertainty		0.0 ft	Wellhead Elevation:	ft	Ground Level:	5,086.0 ft

<b>Wellbore</b>	Hz				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2010	8/22/2014	8.57	66.78	52,691

<b>Design</b>	SURVEYS				
<b>Audit Notes:</b>					
<b>Version:</b>	1.0	<b>Phase:</b>	ACTUAL	<b>Tie On Depth:</b>	0.0
<b>Vertical Section:</b>	<b>Depth From (TVD)</b>	<b>+N/-S</b>	<b>+E/-W</b>	<b>Direction</b>	
	(ft)	(ft)	(ft)	(°)	
	0.0	0.0	0.0	270.00	

<b>Survey Program</b>	<b>Date</b>	9/1/2014			
<b>From (ft)</b>	<b>To (ft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Description</b>	
143.0	11,493.0	Survey #1 (Hz)	Geolink MWD	Geolink MWD	

<b>Survey</b>										
<b>Measured Depth (ft)</b>	<b>Inclination (°)</b>	<b>Azimuth (°)</b>	<b>Vertical Depth (ft)</b>	<b>+N/-S (ft)</b>	<b>+E/-W (ft)</b>	<b>Vertical Section (ft)</b>	<b>Dogleg Rate (°/100ft)</b>	<b>Build Rate (°/100ft)</b>	<b>Formations / Comments</b>	
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00		
143.0	0.40	160.00	143.0	-0.5	0.2	-0.2	0.28	0.28		
235.0	0.40	209.80	235.0	-1.0	0.1	-0.1	0.37	0.00		
326.0	1.20	192.50	326.0	-2.3	-0.2	0.2	0.91	0.88		
418.0	1.80	161.40	418.0	-4.6	0.0	0.0	1.08	0.65		
510.0	3.10	162.80	509.9	-8.3	1.2	-1.2	1.41	1.41		
601.0	4.20	163.40	600.7	-13.9	2.9	-2.9	1.21	1.21		
692.0	5.40	157.70	691.4	-21.0	5.5	-5.5	1.42	1.32		
795.0	5.80	148.60	793.9	-29.9	10.0	-10.0	0.94	0.39		
916.0	5.50	150.80	914.3	-40.2	16.0	-16.0	0.31	-0.25		
1,007.0	8.00	151.10	1,004.7	-49.6	21.2	-21.2	2.75	2.75		
1,099.0	6.60	145.40	1,095.9	-59.5	27.3	-27.3	1.71	-1.52		
1,190.0	9.40	147.50	1,186.0	-70.1	34.3	-34.3	3.09	3.08		

## Survey Report

<b>Company:</b>	EnCana Oil & Gas (USA) Inc	<b>Local Co-ordinate Reference:</b>	Well Drieth 1E-6H-A368
<b>Project:</b>	DJ Wattenberg	<b>TVD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Site:</b>	S6-T3N-R68W (Zisch/Drieth)	<b>MD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Well:</b>	Drieth 1E-6H-A368	<b>North Reference:</b>	True
<b>Wellbore:</b>	Hz	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	SURVEYS	<b>Database:</b>	USA EDM 5000 Multi Users DB

### Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Formations / Comments
1,282.0	9.40	158.20	1,276.8	-83.4	41.1	-41.1	1.90	0.00	
1,374.0	12.20	154.60	1,367.1	-99.2	48.1	-48.1	3.13	3.04	
1,466.0	13.30	152.90	1,456.9	-117.4	57.1	-57.1	1.26	1.20	
1,557.0	12.00	151.80	1,545.7	-135.0	66.3	-66.3	1.45	-1.43	
1,649.0	13.80	160.70	1,635.3	-153.8	74.4	-74.4	2.91	1.96	
1,740.0	15.20	161.80	1,723.4	-175.4	81.8	-81.8	1.57	1.54	
1,832.0	14.50	150.60	1,812.4	-196.9	91.2	-91.2	3.21	-0.76	
1,924.0	16.00	148.10	1,901.2	-217.7	103.5	-103.5	1.78	1.63	
2,016.0	16.80	151.60	1,989.4	-240.2	116.6	-116.6	1.38	0.87	
2,107.0	16.40	156.80	2,076.6	-263.5	127.9	-127.9	1.69	-0.44	
2,199.0	16.00	155.40	2,165.0	-287.0	138.3	-138.3	0.61	-0.43	
2,290.0	15.30	153.40	2,252.6	-309.1	148.9	-148.9	0.97	-0.77	
2,382.0	14.50	150.40	2,341.5	-330.0	160.0	-160.0	1.21	-0.87	
2,477.0	15.20	151.30	2,433.3	-351.3	171.8	-171.8	0.78	0.74	
2,572.0	15.60	155.30	2,524.9	-373.8	183.2	-183.2	1.19	0.42	
2,666.0	14.30	150.60	2,615.7	-395.4	194.1	-194.1	1.89	-1.38	
2,761.0	13.80	153.30	2,707.9	-415.7	205.0	-205.0	0.87	-0.53	
2,856.0	16.00	156.50	2,799.7	-437.9	215.3	-215.3	2.47	2.32	
2,950.0	15.00	152.10	2,890.3	-460.5	226.2	-226.2	1.64	-1.06	
3,045.0	15.60	152.10	2,981.9	-482.7	237.9	-237.9	0.63	0.63	
3,140.0	15.90	154.30	3,073.4	-505.7	249.5	-249.5	0.70	0.32	
3,235.0	14.60	149.30	3,165.0	-527.7	261.3	-261.3	1.95	-1.37	
3,329.0	15.60	153.50	3,255.8	-549.2	273.0	-273.0	1.58	1.06	
3,424.0	16.10	158.50	3,347.2	-572.9	283.5	-283.5	1.53	0.53	
3,518.0	14.70	153.90	3,437.8	-595.7	293.5	-293.5	1.98	-1.49	
3,613.0	14.40	151.50	3,529.7	-616.9	304.5	-304.5	0.71	-0.32	
3,708.0	13.70	150.50	3,621.9	-637.1	315.6	-315.6	0.78	-0.74	
3,803.0	13.40	149.70	3,714.3	-656.4	326.7	-326.7	0.37	-0.32	
3,897.0	12.00	148.80	3,806.0	-674.2	337.3	-337.3	1.50	-1.49	
3,992.0	10.50	144.50	3,899.1	-689.7	347.4	-347.4	1.81	-1.58	
4,087.0	9.70	152.70	3,992.7	-703.8	356.1	-356.1	1.73	-0.84	
4,182.0	10.20	154.20	4,086.2	-718.5	363.5	-363.5	0.59	0.53	
4,276.0	9.80	152.80	4,178.8	-733.1	370.7	-370.7	0.50	-0.43	
4,371.0	9.00	164.10	4,272.5	-747.5	376.5	-376.5	2.11	-0.84	
4,465.0	5.50	162.20	4,365.8	-758.8	379.9	-379.9	3.73	-3.72	
4,560.0	5.00	163.40	4,460.4	-767.1	382.4	-382.4	0.54	-0.53	
4,655.0	4.10	164.90	4,555.1	-774.4	384.5	-384.5	0.96	-0.95	
4,749.0	3.80	166.10	4,648.8	-780.6	386.1	-386.1	0.33	-0.32	
4,844.0	3.40	143.80	4,743.7	-786.0	388.5	-388.5	1.52	-0.42	
4,938.0	2.80	140.10	4,837.5	-790.0	391.7	-391.7	0.67	-0.64	
5,033.0	1.80	136.10	4,932.4	-792.8	394.2	-394.2	1.07	-1.05	
5,128.0	1.40	135.20	5,027.4	-794.7	396.0	-396.0	0.42	-0.42	
5,222.0	0.60	135.80	5,121.4	-795.9	397.2	-397.2	0.85	-0.85	
5,317.0	0.20	157.00	5,216.4	-796.4	397.6	-397.6	0.44	-0.42	
5,411.0	0.50	295.60	5,310.4	-796.4	397.3	-397.3	0.71	0.32	
5,506.0	1.80	168.80	5,405.4	-797.7	397.2	-397.2	2.25	1.37	
5,601.0	1.10	179.10	5,500.3	-800.0	397.5	-397.5	0.78	-0.74	
5,695.0	1.10	111.00	5,594.3	-801.3	398.4	-398.4	1.31	0.00	
5,790.0	0.90	86.70	5,689.3	-801.5	400.0	-400.0	0.49	-0.21	
5,884.0	0.60	345.30	5,783.3	-801.0	400.6	-400.6	1.25	-0.32	
5,979.0	0.70	336.70	5,878.3	-800.0	400.2	-400.2	0.15	0.11	
6,073.0	1.50	63.30	5,972.3	-798.9	401.1	-401.1	1.72	0.85	
6,168.0	1.10	82.10	6,067.3	-798.3	403.1	-403.1	0.61	-0.42	

## Survey Report

<b>Company:</b>	EnCana Oil & Gas (USA) Inc	<b>Local Co-ordinate Reference:</b>	Well Drieth 1E-6H-A368
<b>Project:</b>	DJ Wattenberg	<b>TVD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Site:</b>	S6-T3N-R68W (Zisch/Drieth)	<b>MD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Well:</b>	Drieth 1E-6H-A368	<b>North Reference:</b>	True
<b>Wellbore:</b>	Hz	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	SURVEYS	<b>Database:</b>	USA EDM 5000 Multi Users DB

### Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Formations / Comments
6,262.0	0.80	56.80	6,161.2	-797.8	404.6	-404.6	0.54	-0.32	
6,357.0	0.80	28.50	6,256.2	-796.8	405.4	-405.4	0.41	0.00	
6,389.0	1.00	19.10	6,288.2	-796.4	405.6	-405.6	0.77	0.62	
6,420.0	2.30	301.90	6,319.2	-795.8	405.2	-405.2	7.41	4.19	
6,452.0	6.10	290.20	6,351.1	-794.9	403.0	-403.0	12.11	11.87	
6,483.0	9.10	287.40	6,381.9	-793.5	399.2	-399.2	9.75	9.68	
6,515.0	11.80	279.80	6,413.3	-792.2	393.5	-393.5	9.46	8.44	
6,546.0	14.10	277.10	6,443.5	-791.2	386.6	-386.6	7.67	7.42	
6,578.0	16.00	273.50	6,474.4	-790.5	378.4	-378.4	6.61	5.94	
6,609.0	17.80	268.10	6,504.1	-790.4	369.4	-369.4	7.70	5.81	
6,641.0	19.70	264.20	6,534.4	-791.1	359.1	-359.1	7.11	5.94	
6,672.0	20.90	262.70	6,563.5	-792.3	348.4	-348.4	4.22	3.87	
6,704.0	21.70	263.40	6,593.3	-793.7	336.9	-336.9	2.62	2.50	
6,735.0	22.60	261.70	6,622.0	-795.2	325.3	-325.3	3.56	2.90	
6,767.0	25.50	261.60	6,651.2	-797.1	312.4	-312.4	9.06	9.06	
6,798.0	28.20	262.50	6,678.9	-799.1	298.5	-298.5	8.81	8.71	
6,830.0	29.20	264.00	6,706.9	-800.9	283.3	-283.3	3.85	3.12	
6,877.0	33.30	266.00	6,747.1	-803.0	259.0	-259.0	9.00	8.72	
6,925.0	37.30	269.90	6,786.3	-803.9	231.3	-231.3	9.56	8.33	
6,972.0	41.40	272.40	6,822.6	-803.3	201.5	-201.5	9.35	8.72	
7,019.0	45.30	271.70	6,856.8	-802.1	169.3	-169.3	8.36	8.30	
7,066.0	49.10	270.20	6,888.7	-801.6	134.8	-134.8	8.42	8.09	
7,114.0	53.50	270.20	6,918.7	-801.4	97.4	-97.4	9.17	9.17	
7,161.0	57.80	269.60	6,945.2	-801.5	58.6	-58.6	9.21	9.15	
7,208.0	62.50	268.80	6,968.6	-802.1	17.8	-17.8	10.11	10.00	
7,255.0	66.50	269.20	6,988.9	-802.8	-24.6	24.6	8.55	8.51	
7,303.0	68.20	269.50	7,007.3	-803.3	-68.9	68.9	3.59	3.54	
7,350.0	69.70	269.90	7,024.2	-803.6	-112.7	112.7	3.29	3.19	
7,398.0	70.70	270.30	7,040.5	-803.5	-157.9	157.9	2.23	2.08	
7,445.0	72.00	270.10	7,055.5	-803.3	-202.4	202.4	2.80	2.77	
7,492.0	74.34	269.50	7,069.1	-803.5	-247.4	247.4	5.13	4.98	
7,539.0	76.25	269.60	7,081.1	-803.8	-292.9	292.9	4.07	4.06	
7,587.0	78.10	270.00	7,091.7	-804.0	-339.7	339.7	3.94	3.85	
7,601.0	78.80	270.00	7,094.5	-804.0	-353.4	353.4	5.00	5.00	
7,700.0	79.50	268.10	7,113.1	-805.6	-450.6	450.6	2.01	0.71	
7,748.0	82.10	267.70	7,120.8	-807.4	-498.0	498.0	5.48	5.42	
7,795.0	84.40	268.00	7,126.3	-809.1	-544.6	544.6	4.93	4.89	
7,842.0	88.40	267.50	7,129.3	-811.0	-591.5	591.5	8.58	8.51	
7,890.0	91.10	267.90	7,129.5	-812.9	-639.4	639.4	5.69	5.62	
7,985.0	93.20	268.40	7,125.9	-815.9	-734.3	734.3	2.27	2.21	
8,079.0	94.30	270.00	7,119.8	-817.3	-828.1	828.1	2.06	1.17	
8,174.0	94.30	270.70	7,112.7	-816.7	-922.8	922.8	0.73	0.00	
8,268.0	94.10	271.40	7,105.8	-815.0	-1,016.5	1,016.5	0.77	-0.21	
8,363.0	94.20	271.70	7,098.9	-812.4	-1,111.3	1,111.3	0.33	0.11	
8,458.0	92.40	271.70	7,093.4	-809.6	-1,206.0	1,206.0	1.89	-1.89	
8,552.0	90.90	270.30	7,090.7	-807.9	-1,300.0	1,300.0	2.18	-1.60	
8,647.0	93.90	270.80	7,086.8	-807.0	-1,394.9	1,394.9	3.20	3.16	
8,742.0	95.60	270.20	7,078.9	-806.2	-1,489.6	1,489.6	1.90	1.79	
8,837.0	95.80	270.70	7,069.5	-805.5	-1,584.1	1,584.1	0.56	0.21	
8,931.0	94.00	271.60	7,061.4	-803.6	-1,677.7	1,677.7	2.14	-1.91	
9,026.0	91.60	272.10	7,056.8	-800.5	-1,772.5	1,772.5	2.58	-2.53	
9,121.0	89.10	269.40	7,056.2	-799.3	-1,867.5	1,867.5	3.87	-2.63	
9,215.0	89.00	267.30	7,057.8	-802.0	-1,961.5	1,961.5	2.24	-0.11	

## Survey Report

<b>Company:</b>	EnCana Oil & Gas (USA) Inc	<b>Local Co-ordinate Reference:</b>	Well Drieth 1E-6H-A368
<b>Project:</b>	DJ Wattenberg	<b>TVD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Site:</b>	S6-T3N-R68W (Zisch/Drieth)	<b>MD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Well:</b>	Drieth 1E-6H-A368	<b>North Reference:</b>	True
<b>Wellbore:</b>	Hz	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	SURVEYS	<b>Database:</b>	USA EDM 5000 Multi Users DB

### Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Formations / Comments
9,310.0	92.10	270.50	7,056.9	-803.8	-2,056.4	2,056.4	4.69	3.26	
9,404.0	90.50	269.30	7,054.7	-804.0	-2,150.4	2,150.4	2.13	-1.70	
9,499.0	90.60	269.70	7,053.8	-804.8	-2,245.4	2,245.4	0.43	0.11	
9,594.0	91.90	269.90	7,051.7	-805.1	-2,340.4	2,340.4	1.38	1.37	
9,688.0	92.30	268.70	7,048.3	-806.3	-2,434.3	2,434.3	1.34	0.43	
9,783.0	92.90	268.80	7,044.0	-808.3	-2,529.2	2,529.2	0.64	0.63	
9,877.0	92.40	270.20	7,039.6	-809.2	-2,623.1	2,623.1	1.58	-0.53	
9,972.0	90.60	271.30	7,037.1	-807.9	-2,718.0	2,718.0	2.22	-1.89	
10,067.0	91.50	271.20	7,035.4	-805.8	-2,813.0	2,813.0	0.95	0.95	
10,161.0	89.40	271.80	7,034.7	-803.4	-2,906.9	2,906.9	2.32	-2.23	
10,256.0	87.70	270.80	7,037.1	-801.2	-3,001.9	3,001.9	2.08	-1.79	
10,350.0	89.30	271.10	7,039.5	-799.7	-3,095.8	3,095.8	1.73	1.70	
10,445.0	89.80	269.70	7,040.3	-799.0	-3,190.8	3,190.8	1.56	0.53	
10,539.0	90.50	269.30	7,040.0	-799.8	-3,284.8	3,284.8	0.86	0.74	
10,634.0	90.20	268.90	7,039.5	-801.3	-3,379.8	3,379.8	0.53	-0.32	
10,729.0	91.00	267.50	7,038.5	-804.3	-3,474.7	3,474.7	1.70	0.84	
10,823.0	91.70	268.00	7,036.2	-808.0	-3,568.6	3,568.6	0.92	0.74	
10,918.0	91.60	269.60	7,033.5	-810.0	-3,663.6	3,663.6	1.69	-0.11	
11,012.0	91.70	276.60	7,030.8	-804.9	-3,757.3	3,757.3	7.44	0.11	
11,059.0	92.40	279.20	7,029.1	-798.5	-3,803.9	3,803.9	5.73	1.49	
11,107.0	91.90	280.60	7,027.3	-790.2	-3,851.1	3,851.1	3.10	-1.04	
11,154.0	90.70	277.10	7,026.2	-783.0	-3,897.5	3,897.5	7.87	-2.55	
11,201.0	90.30	274.00	7,025.8	-778.4	-3,944.3	3,944.3	6.65	-0.85	
11,296.0	91.80	271.20	7,024.1	-774.1	-4,039.2	4,039.2	3.34	1.58	
11,391.0	92.20	270.60	7,020.8	-772.6	-4,134.1	4,134.1	0.76	0.42	
11,441.0	92.50	270.70	7,018.7	-772.1	-4,184.1	4,184.1	0.63	0.60	Last CES Survey @ 11,441' MD
11,493.0	92.50	270.00	7,016.5	-771.8	-4,236.0	4,236.0	1.34	0.00	PTB @ 11,493' MD

## Survey Report

<b>Company:</b>	EnCana Oil & Gas (USA) Inc	<b>Local Co-ordinate Reference:</b>	Well Drieth 1E-6H-A368
<b>Project:</b>	DJ Wattenberg	<b>TVD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Site:</b>	S6-T3N-R68W (Zisch/Drieth)	<b>MD Reference:</b>	WELL @ 5099.0ft (Ensign 135)
<b>Well:</b>	Drieth 1E-6H-A368	<b>North Reference:</b>	True
<b>Wellbore:</b>	Hz	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	SURVEYS	<b>Database:</b>	USA EDM 5000 Multi Users DB

Targets									
Target Name	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- hit/miss target	(°)	(°)	(ft)	(ft)	(ft)	(ft)	(ft)		
- Shape									
Drieth 1E-6H TGT 1 P4	0.00	0.00	7,050.0	-804.8	-2,467.0	1,337,105.75	3,126,438.41	40.257860	-105.046989
- survey misses target center by 3.8ft at 9720.6ft MD (7046.9 TVD, -807.0 N, -2466.8 E)									
- Point									
Drieth 1E-6H PBHL P4	0.00	0.00	7,034.3	-804.7	-4,267.4	1,337,096.48	3,124,638.07	40.257860	-105.053440
- survey misses target center by 48.8ft at 11493.0ft MD (7016.5 TVD, -771.8 N, -4236.0 E)									
- Point									
Drieth 1E-6H PBHL P3	0.00	0.00	6,969.3	-804.7	-4,267.4	1,337,096.48	3,124,638.07	40.257860	-105.053440
- survey misses target center by 65.5ft at 11493.0ft MD (7016.5 TVD, -771.8 N, -4236.0 E)									
- Point									
Drieth 1E-6H TGT 1	0.00	0.00	6,985.0	-804.8	-2,467.0	1,337,105.75	3,126,438.41	40.257860	-105.046989
- survey misses target center by 61.9ft at 9723.5ft MD (7046.8 TVD, -807.1 N, -2469.8 E)									
- Point									
Drieth 1E-6H PBHL	0.00	0.00	7,036.0	-804.7	-4,267.4	1,337,096.48	3,124,638.07	40.257860	-105.053440
- survey misses target center by 49.5ft at 11493.0ft MD (7016.5 TVD, -771.8 N, -4236.0 E)									
- Point									

Survey Annotations				
Measured Depth	Vertical Depth	Local Coordinates		Comment
(ft)	(ft)	+N/-S (ft)	+E/-W (ft)	
11,441.0	7,018.7	-772.1	-4,184.1	Last CES Survey @ 11,441' MD
11,493.0	7,016.5	-771.8	-4,236.0	PTB @ 11,493' MD

Checked By: \_\_\_\_\_ Approved By: \_\_\_\_\_ Date: \_\_\_\_\_