



Job Number: SVGJ-140668  
 Company: PDC  
 Lease/Well: Bailey 5  
 Location: Weld County, CO  
 Rig Name: MS Wireline #6000  
 RKB: 0'  
 G.L. or M.S.L.: GL

State/Country: Colorado/USA  
 Declination: 8.34°  
 Grid: East To True North  
 File name: Y:\WINSER~1\2014SU~1\PDC\GJ\BAILEY\5.SVY  
 Date/Time: 04-Jun-14 / 15:42  
 Curve Name: Surface - 6800' M.D. (Rate Gyro)

### MS Survey

WINSERVE SURVEY CALCULATIONS  
 Minimum Curvature Method  
 Vertical Section Plane .00  
 Vertical Section Referenced to Wellhead  
 Rectangular Coordinates Referenced to Wellhead

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
100.00	.48	27.95	100.00	.37	.20	.37	.42	27.95	.48
200.00	.46	13.24	200.00	1.13	.48	1.13	1.23	23.20	.12
300.00	.41	352.29	299.99	1.88	.53	1.88	1.95	15.73	.17
400.00	.41	329.39	399.99	2.54	.30	2.54	2.56	6.70	.16
500.00	.37	292.10	499.99	2.97	-.18	2.97	2.97	356.47	.25
600.00	.41	293.76	599.99	3.23	-.81	3.23	3.33	345.94	.04
700.00	.39	282.01	699.98	3.45	-1.47	3.45	3.75	336.91	.08
800.00	.35	275.83	799.98	3.55	-2.11	3.55	4.13	329.32	.06
900.00	.33	270.25	899.98	3.58	-2.70	3.58	4.49	323.01	.04

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
1000.00	.37	276.36	999.98	3.62	-3.31	3.62	4.90	317.58	.05
1100.00	.42	266.58	1099.98	3.63	-3.99	3.63	5.40	312.29	.08
1200.00	.41	260.90	1199.97	3.56	-4.71	3.56	5.90	307.03	.04
1300.00	.45	257.64	1299.97	3.41	-5.45	3.41	6.43	302.07	.05
1400.00	.46	259.08	1399.97	3.25	-6.23	3.25	7.03	297.59	.02
1500.00	.51	255.48	1499.96	3.07	-7.05	3.07	7.69	293.50	.06
1600.00	.44	250.88	1599.96	2.83	-7.85	2.83	8.34	289.83	.08
1700.00	.31	252.18	1699.96	2.62	-8.47	2.62	8.86	287.20	.13
1800.00	.25	259.00	1799.96	2.50	-8.94	2.50	9.28	285.60	.07
1900.00	.14	282.09	1899.96	2.48	-9.27	2.48	9.60	284.98	.13
2000.00	.37	44.30	1999.96	2.74	-9.17	2.74	9.57	286.63	.46
2100.00	.74	37.01	2099.95	3.48	-8.55	3.48	9.23	292.16	.38
2200.00	1.02	23.83	2199.94	4.81	-7.80	4.81	9.17	301.67	.34
2300.00	1.24	8.74	2299.92	6.70	-7.28	6.70	9.89	312.61	.37
2400.00	1.86	351.29	2399.88	9.37	-7.36	9.37	11.92	321.85	.77
2500.00	2.12	349.88	2499.82	12.80	-7.93	12.80	15.05	328.21	.26
2600.00	2.22	349.24	2599.75	16.52	-8.62	16.52	18.63	332.45	.10
2700.00	2.15	349.56	2699.68	20.27	-9.32	20.27	22.31	335.30	.07
2800.00	1.86	344.44	2799.62	23.68	-10.10	23.68	25.74	336.91	.34
2900.00	1.61	330.30	2899.57	26.46	-11.23	26.46	28.74	337.01	.49
3000.00	1.60	309.57	2999.53	28.57	-13.00	28.57	31.39	335.53	.58
3100.00	1.70	293.70	3099.49	30.05	-15.43	30.05	33.79	332.82	.47
3200.00	1.83	283.64	3199.44	31.03	-18.34	31.03	36.04	329.41	.34
3300.00	1.83	277.13	3299.39	31.60	-21.48	31.60	38.21	325.80	.21
3400.00	1.82	272.76	3399.34	31.88	-24.65	31.88	40.30	322.29	.14
3500.00	1.72	269.21	3499.30	31.93	-27.74	31.93	42.30	319.02	.15
3600.00	1.66	264.86	3599.25	31.78	-30.68	31.78	44.17	316.01	.14
3700.00	1.66	261.91	3699.21	31.45	-33.56	31.45	45.99	313.14	.09
3800.00	1.52	254.81	3799.17	30.90	-36.27	30.90	47.65	310.43	.24

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
3900.00	1.37	235.84	3899.14	29.88	-38.54	29.88	48.76	307.79	.50
4000.00	1.36	231.35	3999.11	28.47	-40.46	28.47	49.47	305.13	.11
4100.00	1.41	231.58	4099.08	26.96	-42.35	26.96	50.20	302.48	.05
4200.00	1.45	233.72	4199.05	25.45	-44.33	25.45	51.11	299.86	.07
4300.00	1.50	242.07	4299.02	24.08	-46.51	24.08	52.37	297.38	.22
4400.00	1.59	242.41	4398.98	22.83	-48.89	22.83	53.96	295.03	.09
4500.00	1.69	243.12	4498.94	21.52	-51.44	21.52	55.76	292.70	.10
4600.00	1.78	244.58	4598.90	20.19	-54.15	20.19	57.79	290.44	.10
4700.00	1.43	262.65	4698.86	19.36	-56.80	19.36	60.00	288.82	.61
4800.00	1.44	280.22	4798.83	19.42	-59.27	19.42	62.37	288.14	.44
4900.00	1.44	281.89	4898.79	19.91	-61.74	19.91	64.87	287.87	.04
5000.00	1.34	287.55	4998.76	20.52	-64.08	20.52	67.28	287.75	.17
5100.00	1.29	294.07	5098.74	21.33	-66.22	21.33	69.57	287.85	.16
5200.00	1.27	299.01	5198.71	22.33	-68.22	22.33	71.78	288.12	.11
5300.00	1.48	293.07	5298.68	23.37	-70.38	23.37	74.15	288.37	.25
5400.00	1.61	290.16	5398.65	24.36	-72.88	24.36	76.85	288.48	.15
5500.00	1.17	284.89	5498.62	25.11	-75.19	25.11	79.27	288.46	.46
5600.00	.71	267.69	5598.61	25.34	-76.79	25.34	80.87	288.26	.53
5700.00	.46	241.47	5698.60	25.13	-77.77	25.13	81.72	287.91	.36
5800.00	.52	221.53	5798.60	24.59	-78.42	24.59	82.19	287.41	.18
5900.00	.63	205.15	5898.59	23.76	-78.95	23.76	82.45	286.75	.20
6000.00	.63	206.44	5998.59	22.77	-79.43	22.77	82.63	285.99	.01
6100.00	.68	197.03	6098.58	21.71	-79.85	21.71	82.75	285.21	.12
6200.00	.62	183.93	6198.57	20.60	-80.06	20.60	82.67	284.43	.16
6300.00	.63	181.60	6298.57	19.51	-80.11	19.51	82.46	283.69	.03
6400.00	.58	185.01	6398.56	18.46	-80.17	18.46	82.27	282.96	.06
6500.00	.45	180.22	6498.56	17.56	-80.22	17.56	82.12	282.35	.14
6600.00	.67	179.85	6598.55	16.58	-80.22	16.58	81.92	281.68	.22
6700.00	.85	177.82	6698.54	15.26	-80.19	15.26	81.63	280.77	.18

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
Last Survey Depth Recorded									
6800.00	.38	124.86	6798.54	14.33	-79.89	14.33	81.16	280.17	.69