
Schlumberger
Array Induction Imager Tool
Gamma Ray
Bit Size
Caliper
Deep Induction
Medium Induction
Shallow Induction
Spherically Focused Resistivity
Rt
Rxo
Rm
Rmf
Rmc
Mud Type
Mud Density
Mud Resistivity
Mud Filtrate Resistivity
Mud Cake Resistivity
Source of Sample
Rm @ BHT
Rmf @ BHT
Rmc @ BHT
Time Since Circulation
Max Recorded Temperature
Equipment Number
Location
Recorded By
Witnessed By
Run Number
Depth Driller
Depth Logger
Bottom Logged Interval
Top Log Interval
Casing Driller
Casing Logger
Bit Size
Type Fluid in Hole
Density
Viscosity
pH
Fluid Loss
Source of Sample
Rm @ Meas. Temp
Rmf @ Meas. Temp
Rmc @ Meas. Temp
Rm @ BHT
Rmf @ BHT
Rmc @ BHT



Calibration Report

Database File: cbl noble schmidt amoco 44-23-26
Dataset Pathname: pass2
Dataset Creation: Mon Dec 22 11:16:16 2014 by Log ECH 123400

Gamma Ray Calibration Report

Type / Serial	Probe2754dg / 110705

Fri Nov 08 00:38:30 2013

SHOP CALIBRATION

	Counts/Sec	Gain	Offset	Jig	Units
Background	0.0				cps
Calibrator	1.0				cps
		0.4400			GAPI/cps

PRIMARY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI

BEFORE SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI

AFTER SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI

Cement Bond Log Calibration Report

Serial Number:	110602		
Tool Model:	Probe2770gMat		
Performed:	Mon Dec 22 11:09:16 2014		
Depth:	2714.25	ft	
Casing Diameter:	4.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	0.7	0	mV
Calibrated Amplitude:	81.1561	81.1561	mV
Reading at Signal Zero:	-0.00559051	-0.00559545	V
Reading in Free Pipe:	2.46641	2.30244	V
Gain:	33.1752	35.1802	
Offset:	0.673601	0.195627	