

Acquisition and equipment performance limits shall be under the responsibility of the customer and no claim will be granted by the company in connection with the interpretation and use of data or results which may arise as a result of the supplied service. All data and results supplied by the company are given in confidence and may not be passed on to any other person or company without the consent of the company. Interpretations are opinions based on inferences drawn from electrical or other measurements. These interpretations are also supplied on the understanding that neither the company nor any of its employees guarantees the accuracy or correctness of any interpretation and cannot accept any responsibility for any loss, damage or expense incurred as a consequence of any opinion or interpretation made by any of its employees.

Continued...

THANK YOU FOR CHOOSING FTS!

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	ID (in)
CCL	33.57		CCL-GR Mono w/ TTRB/HCS 1.69 Max. OD Roll Prog.	1.48	2.75	00.00
			CBHT-TB(12.2)(5)	2.71	2.75	10.00
TEMP	12.79		CTS-TB/HCS/12.2/5.0kg Centr.w/TTRB&.QUICK-11 Centr.Type:Bow Spring Centralizer Centr.Size:Min.ID: 4" Max.OD: 5.0kg Centr.Material:Steel	2.75	2.75	10.00
tmf01	11.46					
tmf02	11.46					
tmf03	11.46					
tmf04	11.46					
tmf05	11.46					
tmf06	11.46					
tmf07	11.46					
tmf08	11.46					
tmf09	11.46					
tmf10	11.46					
tmf11	11.46					
tmf12	11.46					
tmf13(Dia)	12.79					
tmf14(P)	11.46					
tmf15(Bat)	6.46					
			CBHT-TB(12.2)(10)	2.71	2.75	10.00
GR	1.00		GR-TB(12.2)(30kg)	3.60	2.75	00.00
			Telltale Fish Neck Fish Weight	pcheart 31.25 fishneckfishtopsub 2.00 in 0.00 in 0.00 lb		

Calibration File	pcheart 31.2 dll
Calibrator Configuration	1.0
Calibrator Last Calibrated	Thu, Jan 31 07:19:55 2013 by Log NCH 111110
Tension Calibration	
Depth: 0 Feet	Depth: 0 Feet
Tension: 0 Lbs	Tension: 0 Lbs
Cable Locator	0 Amplitude Amplitude (mV) 22.000 VDL 1.000
Cable Locator Amplitude (mV)	0 Amplitude (mV) 100

Depth (feet)

Calibration File	pcheart 31.2 dll
Calibrator Configuration	1.0
Calibrator Last Calibrated	Thu, Jan 31 07:19:55 2013 by Log NCH 111110
Tension Calibration	
Depth: 0 Feet	Depth: 0 Feet
Tension: 0 Lbs	Tension: 0 Lbs
Cable Locator	0 Amplitude Amplitude (mV) 22.000 VDL 1.000
Cable Locator Amplitude (mV)	0 Amplitude (mV) 100

Depth (feet)

Calibration Report

Calibration File	pcheart 31.2 dll
Calibrator Configuration	1.0
Calibrator Last Calibrated	Thu, Jan 31 07:19:55 2013 by Log NCH 111110

Gamma Ray Calibration Report

Serial Number	111nd
Diameter	2.75 in
Particulars	Short Cut 18.56 lb 08.29 2013
Calibrator Value	1.0 Unit/V
Calibrator Reading	1.0 V
Tolerance Checking	0.0 Unit
Sensitivity	1.0000 Unit/Value

Hydrostatic Calibrator Back-Up Calibration Report

Serial Number	111nd
Part Number	111nd
Calibration Casing Diameter	4.500 in
Calibration Date	2013-01-29

Master Calibration Jan/Feb and Thu Jan 22 12:19:23 2013

	Zero	Cal	Calibration(Up) Zero	Cal	Gain	Results Offset
1	0.000	1.875	0.000	91.158	48.362	0.000
2	0.000	1.875	0.000	91.158	48.362	0.000
3	0.000	1.875	0.000	91.158	48.362	0.000
4	0.000	1.708	0.000	100.000	48.362	0.000
5	0.000	1.708	0.000	100.000	48.362	0.000
6	0.000	1.708	0.000	100.000	48.362	0.000
7	0.000	1.708	0.000	100.000	48.362	0.000
8	0.000	1.708	0.000	100.000	48.362	0.000
9	0.000	1.708	0.000	100.000	48.362	0.000
10	0.000	1.708	0.000	100.000	48.362	0.000

Internal Reference Calibration, performed Thu Jan 31 07:20:55 2013

	Point (1)		Calibration(1)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CCL	0.000	0.000	0.000	1.708	1.000	0.000

Air Zero Calibration, performed Thu Sep 19 07:20:55 2013

	Point (1)	Calibration(1)	Results
	Zero	Zero	Offset
1	0.000	0.000	0.000
2	0.000	0.000	0.000
3	0.000	0.000	0.000
4	0.000	0.000	0.000
5	0.000	0.000	0.000
6	0.000	0.000	0.000
7	0.000	0.000	0.000
8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number	111nd
Diameter	2.75 in
Particulars	Air Jan 18 09:29:22 2013
	Reference
Low Reference	70.00 degF
High Reference	212.00 degF
	Offset
Offset	0.00
Offset Matching	0.00

	Reading
Low Reference	70.00 degF
High Reference	212.00 degF